



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 21

LOCTITE LB 8150 known as Loctite 8150 500g EGFD

SDS No. : 283262

V003.0

Revision: 20.04.2023

printing date: 29.04.2023

Replaces version from: 17.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE LB 8150 known as Loctite 8150 500g EGFD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Lubricant

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSInfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Chronic hazards to the aquatic environment

H412 Harmful to aquatic life with long lasting effects.

Category 3

2.2. Label elements

Label elements (CLP):

Hazard statement:

H412 Harmful to aquatic life with long lasting effects.

Supplemental information

Contains: Polysulfides, di-tert-Bu May produce an allergic reaction.

Precautionary statement: Prevention

P273 Avoid release to the environment.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
aluminium powder (stabilised) 7429-90-5 231-072-3 01-2119529243-45	10- 15 %	Water-react. 2, H261 Flam. Sol. 1, H228		EUEXPL2D
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7 265-157-1 01-2119484627-25	2,5- < 10 %	Asp. Tox. 1, H304		
Ethyl 3-[[bis(1-methylethoxy)phosphinothioyl]thio]propionate 71735-74-5 275-965-6 01-2119976328-24	2,5- < 10 %	Aquatic Chronic 2, H411		
Hydrocarbons, C9, aromatics 64742-95-6 265-199-0 01-2119455851-35	1- < 2,5 %	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 STOT SE 3, H336 Aquatic Chronic 2, H411		
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic 918-481-9 01-2119457273-39	1- < 2,5 %	Asp. Tox. 1, H304		
dilithium azelate 38900-29-7 254-184-4 01-2120119814-57	1- < 2,5 %	Acute Tox. 4, Oral, H302		
Polysulfides, di-tert-Bu 68937-96-2 273-103-3 01-2119540515-43	0,25- < 1 %	Skin Sens. 1, H317 Aquatic Chronic 3, H412	oral:ATE = 2.500 mg/kg	
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1 270-128-1 01-2119491299-23	0,1- < 1 %	Aquatic Chronic 3, H412 Repr. 2, H361f STOT RE 2, H373		
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5 202-414-9 01-2119777867-13	0- < 0,025 %	Acute Tox. 4, Oral, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 10 M chronic = 1	

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media**Suitable extinguishing media:**

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

Scrape up as much material as possible.

Sweep up spilled material. Avoid creating dust.

Store in a partly filled, closed container until disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store in a cool, dry place.

Do not store near sources of heat or ignition, or reactive materials.

Refer to Technical Data Sheet

7.3. Specific end use(s)

Lubricant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Graphite 7782-42-5			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Graphite 7782-42-5		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Graphite 7782-42-5		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Aluminium 7429-90-5			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Aluminium 7429-90-5		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Aluminium 7429-90-5		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9		4	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	oral				9,33 mg/kg		
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic	Air						no hazard identified
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5	aqua (freshwater)		0,03 µg/l				
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5	aqua (marine water)		0,003 µg/l				
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5	aqua (intermittent releases)		0,3 µg/l				
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5	sewage treatment plant (STP)		0,27 mg/l				
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5	sediment (freshwater)				0,376 mg/kg		
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5	aqua (marine water)				0,0376 mg/kg		
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5	Soil				0,075 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	Workers	inhalation	Long term exposure - local effects		5,4 mg/m ³	
Hydrocarbons, C9, aromatics 64742-95-6	Workers	inhalation	Long term exposure - systemic effects		151 mg/m ³	
Hydrocarbons, C9, aromatics 64742-95-6	Workers	dermal	Long term exposure - systemic effects		12,5 mg/kg	
Hydrocarbons, C9, aromatics 64742-95-6	General population	inhalation	Long term exposure - systemic effects		32 mg/m ³	
Hydrocarbons, C9, aromatics 64742-95-6	General population	dermal	Long term exposure - systemic effects		7,5 mg/kg	
Hydrocarbons, C9, aromatics 64742-95-6	General population	oral	Long term exposure - systemic effects		7,5 mg/kg	
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5	Workers	dermal	Acute/short term exposure - systemic effects		2 mg/kg	
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5	Workers	Inhalation	Acute/short term exposure - systemic effects		14 mg/m ³	
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5	Workers	dermal	Long term exposure - systemic effects		0,06 mg/kg	
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5	Workers	Inhalation	Long term exposure - systemic effects		0,46 mg/m ³	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Aluminium 7429-90-5	Aluminum	Urine	Sampling time: End of shift.	200 µg/l	DE BAT		
Aluminium 7429-90-5 [Aluminum]	Aluminum	Creatinine in urine	Sampling time: End of work week.	50 µg/g	DE BGW		

8.2. Exposure controls:**Engineering controls:**

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Dust mask, P2 particle filter.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Delivery form	solid
Colour	grey
Odor	characteristic
Physical state	solid
Melting point	Not available.
Solidification temperature	Not applicable, Product is a solid.
Initial boiling point	> 316 °C (> 600.8 °F)
Flammability	Not applicable
Explosive limits	
lower	0,6 % (V);
upper	7,5 % (V);
Flash point	> 60 °C (> 140 °F)
Auto-ignition temperature	Not applicable, Product is a solid.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic

pH	peroxide and does not decompose under foreseen conditions of use
Viscosity (kinematic)	Not applicable, Product is non-polar/aprotic.
Solubility (qualitative)	Not applicable, Product is a solid.
(20 °C (68 °F); Solvent: Water)	Not miscible or difficult to mix
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure	Mixture
(20 °C (68 °F))	< 0,1 hPa
Density	0,9 g/cm3 None
(20 °C (68 °F))	
Relative vapour density:	Not applicable, Product is a solid.
Particle characteristics	Currently under determination

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used properly.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

None if used properly.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
aluminium powder (stabilised) 7429-90-5	LD50	> 15.900 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Hydrocarbons, C9, aromatics 64742-95-6	LD50	3.492 mg/kg	rat	not specified
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic	LD50	> 15.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Polysulfides, di-tert-Bu 68937-96-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Polysulfides, di-tert-Bu 68937-96-2	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2-(2-Heptadec-8-enyl-2- imidazolin-1-yl)ethanol 95-38-5	LD50	1.265 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C9, aromatics 64742-95-6	LD50	> 3.160 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic	LD50	> 5.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
dilithium azelate 38900-29-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Polysulfides, di-tert-Bu 68937-96-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	LD50	> 2.000 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
aluminium powder (stabilised) 7429-90-5	LC50	> 5 mg/l	dust/mist	4 h	rat	not specified
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	LC50	> 5,53 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C9, aromatics 64742-95-6	LC50	> 10,2 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic	LC50	> 5,6 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
aluminium powder (stabilised) 7429-90-5	not irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	not irritating	24 h	rabbit	not specified
Hydrocarbons, C9, aromatics 64742-95-6	mildly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic	mildly irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	mildly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-(2-Heptadec-8-enyl-2- imidazolin-1-yl)ethanol 95-38-5	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
aluminium powder (stabilised) 7429-90-5	not irritating		rabbit	FDA Guideline
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Hydrocarbons, C9, aromatics 64742-95-6	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
aluminium powder (stabilised) 7429-90-5	not sensitising	Draize Test	guinea pig	Draize Test
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Hydrocarbons, C9, aromatics 64742-95-6	not sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
Polysulfides, di-tert-Bu 68937-96-2	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
aluminium powder (stabilised) 7429-90-5	positive	in vitro mammalian cell micronucleus test	without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
aluminium powder (stabilised) 7429-90-5	positive	in vitro mammalian chromosome aberration test	without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
aluminium powder (stabilised) 7429-90-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Hydrocarbons, C9, aromatics 64742-95-6	negative	sister chromatid exchange assay in mammalian cells	with and without		equivalent or similar to OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
Hydrocarbons, C9, aromatics 64742-95-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hydrocarbons, C9, aromatics 64742-95-6	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Hydrocarbons, C9, aromatics 64742-95-6	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	not carcinogenic	dermal	78 w various	mouse	female	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
aluminium powder (stabilised) 7429-90-5	NOAEL P 1.000 mg/kg NOAEL F1 1.000 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1	NOAEL 25 mg/kg	oral: gavage	M: 28 d / F: 53 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5	NOAEL 20 mg/kg	oral: gavage	31/51 days (m/f) daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	20 mm ² /s	40 °C	not specified	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic	1,13 mm ² /s	40 °C	not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	LL50	> 100 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethyl 3-[[bis(1- methylethoxy)phosphinothioyl]thio]propionate 71735-74-5	LC50	1,73 mg/l	96 h	Danio rerio (reported as Brachydanio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydrocarbons, C9, aromatics 64742-95-6	LL50	9,2 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydrocarbons, C10-C13, n- alkanes, isoalkanes, cyclics, < 2% aromatic	LL50	> 1.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
dilithium azelate 38900-29-7	LC50	> 100 mg/l	96 h	Cyprinus carpio	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-(2-Heptadec-8-enyl-2- imidazolin-1-yl)ethanol 95-38-5	LC50	0,3 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	EL50	> 10.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethyl 3-[[bis(1- methylethoxy)phosphinothioyl]thio]propionate 71735-74-5	EC50	4,01 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C9, aromatics 64742-95-6	EL50	3,2 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C10-C13, n- alkanes, isoalkanes, cyclics, < 2% aromatic	EL50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
dilithium azelate 38900-29-7	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Polysulfides, di-tert-Bu 68937-96-2	EL50	63 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-(2-Heptadec-8-enyl-2- imidazolin-1-yl)ethanol 95-38-5	EC50	0,163 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	NOELR	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Ethyl 3-[[bis(1- methylethoxy)phosphinothioyl thio]propionate 71735-74-5	EC10	0,196 mg/l	21 day	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	EL50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	NOELR	100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethyl 3-[[bis(1-methylethoxy)phosphinothioyl]thio]propionate 71735-74-5	EC50	8,28 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethyl 3-[[bis(1-methylethoxy)phosphinothioyl]thio]propionate 71735-74-5	EC10	3,93 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C9, aromatics 64742-95-6	NOELR	1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C9, aromatics 64742-95-6	EL50	2,9 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C10-C13, n- alkanes, isoalkanes, cyclics, < 2% aromatic	EL50	> 1.000 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C10-C13, n- alkanes, isoalkanes, cyclics, < 2% aromatic	NOELR	1.000 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
dilithium azelate 38900-29-7	EC50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
dilithium azelate 38900-29-7	NOEC	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Polysulfides, di-tert-Bu 68937-96-2	EL50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Polysulfides, di-tert-Bu 68937-96-2	NOELR	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-(2-Heptadec-8-enyl-2- imidazolin-1-yl)ethanol 95-38-5	NOEC	0,011 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-(2-Heptadec-8-enyl-2- imidazolin-1-yl)ethanol 95-38-5	EC50	0,03 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl 3-[[bis(1-methylethoxy)phosphinothioyl]thio]propionate 71735-74-5	IC50	100 mg/l	3 h	activated sludge, domestic	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
2-(2-Heptadec-8-enyl-2- imidazolin-1-yl)ethanol 95-38-5	IC50	26 mg/l	3 h	activated sludge, domestic	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	not readily biodegradable.	aerobic	31 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Ethyl 3-[[bis(1- methylethoxy)phosphinothioyl thio]propionate 71735-74-5	not readily biodegradable.	aerobic	33 %	28 day	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Hydrocarbons, C9, aromatics 64742-95-6	readily biodegradable	aerobic	78 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydrocarbons, C10-C13, n- alkanes, isoalkanes, cyclics, < 2% aromatic	readily biodegradable, but failing 10-day window	aerobic	80 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
dilithium azelate 38900-29-7	readily biodegradable	aerobic	> 79 - < 89 %	19 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Polysulfides, di-tert-Bu 68937-96-2	not readily biodegradable.	aerobic	13 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
2-(2-Heptadec-8-enyl-2- imidazolin-1-yl)ethanol 95-38-5	not readily biodegradable.	aerobic	1 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Hydrocarbons, C9, aromatics 64742-95-6	> 4		QSAR (Quantitative Structure Activity Relationship)
dilithium azelate 38900-29-7	1,57	25 °C	not specified

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
aluminium powder (stabilised) 7429-90-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C9, aromatics 64742-95-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol 95-38-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

14 06 03 Other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

- 14.1. UN number or ID number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Maritime transport in bulk according to IMO instruments**
not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 5 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK:	WGK 3: highly hazardous to water (Ordinance on facilities for handling substances that are hazardous to water (AwSV)) Classification according to AwSV, Annex 1 (5.2)
Storage class according to TRGS 510:	11

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
H228 Flammable solid.
H261 In contact with water releases flammable gases.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.