

# Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 1

SDS No.: 178501

Revision: 17.01.2024

printing date: 22.01.2024

Replaces version from: 02.03.2023

LOCTITE EA 3472 known as Loctite 3472 A&B/Loctite 3472

# **Kit/Multi-component Product**

1. SDS No.173479 - LOCTITE EA 3472 Part A

2. SDS No.173480 - LOCTITE EA 3472 Part B



LOCTITE EA 3472 Part A

# Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 16

SDS No.: 173479 V005.0

Revision: 17.01.2024

printing date: 22.01.2024

Replaces version from: 16.01.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE EA 3472 Part A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Epoxy adhesive

#### 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

#### 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment Category 2

H411 Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

#### Label elements (CLP):



**Contains** 

SDS No.: 173479 V005.0 Page 2 of 16

1,3-Propanediol, 2,2-bis(hydroxymethyl)-, polymer with (chloromethyl)oxirane oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Signal word:	Warning

Hazard statement:	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H319 Causes serious eye irritation.
	H411 Toxic to aquatic life with long lasting effects.

Precautionary statement: P273 Avoid release to the environment.
Prevention P280 Wear protective gloves.

Precautionary statement:	P302+P352 IF ON SKIN: Wash with plenty of soap and water.
Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
	P337+P313 If eye irritation persists: Get medical advice/attention.

#### 2.3. Other hazards

None if used properly.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Bisphenol A Diglycidyl Ether 1675-54-3 216-823-5 01-2119456619-26	25-< 40 %	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 %	
1,3-Propanediol, 2,2- bis(hydroxymethyl)-, polymer with (chloromethyl)oxirane 30973-88-7	2,5-< 5 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412		
oxirane, mono[(C12-14- alkyloxy)methyl] derivs. 68609-97-2 271-846-8 01-2119485289-22	0,1-< 1 %	Skin Irrit. 2, H315 Skin Sens. 1, H317		

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the H - statements and other abbreviations see section 16 "Other information".

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

### Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

SDS No.: 173479 V005.0 Page 3 of 16

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

water, carbon dioxide, foam, powder

#### Extinguishing media which must not be used for safety reasons:

High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### **Additional information:**

In case of fire, keep containers cool with water spray.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

#### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

#### 6.4. Reference to other sections

See advice in section 8

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

SDS No.: 173479 V005.0 Page 4 of 16

#### Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

# 7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place.

Refer to Technical Data Sheet

# 7.3. Specific end use(s)

Epoxy adhesive

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

#### **Occupational Exposure Limits**

Valid for

Germany

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Titanium dioxide 13463-67-7			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Titanium dioxide 13463-67-7		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Titanium dioxide 13463-67-7		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

SDS No.: 173479 V005.0 Page 5 of 16

# **Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
		F	mg/l	ppm	mg/kg	others	
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	aqua (freshwater)		0,006 mg/l				
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	Freshwater - intermittent		0,018 mg/l				
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	aqua (marine water)		0,001 mg/l				
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	Marine water - intermittent		0,002 mg/l				
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	sewage treatment plant (STP)		10 mg/l				
2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	sediment (freshwater)				0,341 mg/kg		
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	sediment (marine water)				0,034 mg/kg		
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	Air						no hazard identified
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	Soil				0,065 mg/kg		
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	oral				11 mg/kg		
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	aqua (freshwater)		0,106 mg/l				
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	aqua (intermittent releases)		0,072 mg/l				
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	aqua (marine water)		0,011 mg/l				
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	sewage treatment plant (STP)		10 mg/l				
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	sediment (freshwater)				307,16 mg/kg		
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	sediment (marine water)				30,72 mg/kg		
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	Soil				1,234 mg/kg		

SDS No.: 173479 V005.0 Page 6 of 16

#### **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	Workers	inhalation	Long term exposure - systemic effects		4,93 mg/m3	no hazard identified
2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	Workers	dermal	Long term exposure - systemic effects		0,75 mg/kg	no hazard identified
2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	General population	inhalation	Long term exposure - systemic effects		0,87 mg/m3	no hazard identified
2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	General population	dermal	Long term exposure - systemic effects		0,0893 mg/kg	no hazard identified
2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	no hazard identified
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	Workers	Inhalation	Long term exposure - systemic effects		3,6 mg/m3	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	Workers	dermal	Long term exposure - systemic effects		1 mg/kg	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	General population	Inhalation	Long term exposure - systemic effects		0,87 mg/m3	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	General population	dermal	Long term exposure - systemic effects		0,5 mg/kg	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	

### **Biological Exposure Indices:**

None

#### 8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

# Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

#### Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

SDS No.: 173479 V005.0 Page 7 of 16

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Delivery form liquid
Colour grey
Odor charact

Odor characteristic Physical state liquid

Melting point Not applicable, Product is a liquid

Initial boiling point  $> 100 \,^{\circ}\text{C} (> 212 \,^{\circ}\text{F})$ 

Flammability The product is not flammable.

Explosive limits Not applicable, The product is not flammable. Flash point  $> 110 \, ^{\circ}\text{C} (> 230 \, ^{\circ}\text{F})$ 

Auto-ignition temperature Not applicable, The product is not flammable.

Decomposition temperature Not applicable, Substance/mixture is not self-reactive, no organic

peroxide and does not decompose under foreseen conditions of use

6 - 9

(20 °C (68 °F); Conc.: 100 % product)

Viscosity (kinematic) > 20,5 mm2/s

(40 °C (104 °F); )

Viscosity, dynamic 70.000 - 90.000 mPa.s LCT STM 10; Viscosity Brookfield

(Brookfield; speed of rotation: 2,5 min-1)

Solubility (qualitative) Not miscible

(20 °C (68 °F); Solvent: Water)

Partition coefficient: n-octanol/water Not applicable Mixture

Vapour pressure 0,01 hPa

(20 °C (68 °F))

Density 2,35 g/cm3 None (20 °C (68 °F))

Relative vapour density: Currently under determination

Particle characteristics Not applicable Product is a liquid

### 9.2. Other information

Other information not applicable for this product

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Reacts with strong oxidants. Reaction with strong acids.

# 10.2. Chemical stability

Stable under recommended storage conditions.

#### 10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

SDS No.: 173479 V005.0 Page 8 of 16

#### 10.5. Incompatible materials

See section reactivity.

#### 10.6. Hazardous decomposition products

carbon oxides.

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Bisphenol A Diglycidyl Ether	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
1675-54-3				
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	LD50	26.800 mg/kg	rat	not specified

#### Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value	Value	Species	Method
	type	2.000 #		OFGD G 1111 402 (A D 1 T . 1 1 )
Bisphenol A Diglycidyl	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Ether				
1675-54-3				
oxirane, mono[(C12-14-	LD50	> 4.000 mg/kg	rabbit	not specified
alkyloxy)methyl] derivs.				·
68609-97-2				

#### Acute inhalative toxicity:

No data available.

#### Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Bisphenol A Diglycidyl	moderately	24 h	rabbit	Draize Test
Ether	irritating			
1675-54-3				
oxirane, mono[(C12-14-	moderately	24 h	rabbit	EPA OTS 798.4470 (Acute Dermal Irritation)
alkyloxy)methyl] derivs.	irritating			
68609-97-2				

#### Serious eye damage/irritation:

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Bisphenol A Diglycidyl Ether 1675-54-3	slightly irritating		rabbit	Draize Test
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

SDS No.: 173479 V005.0 Page 9 of 16

# Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
Bisphenol A Diglycidyl	sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
Ether		assay (LLNA)		Local Lymph Node Assay)
1675-54-3				, ,
oxirane, mono[(C12-14-	sensitising	Buehler test	guinea pig	EPA OPPTS 870.2600 (Skin
alkyloxy)methyl] derivs.				Sensitisation)
68609-97-2				·

# Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Bisphenol A Diglycidyl Ether 1675-54-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Bisphenol A Diglycidyl Ether 1675-54-3	negative with metabolic activation	mammalian cell gene mutation assay	with and without		not specified
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Bisphenol A Diglycidyl Ether 1675-54-3	negative	oral: gavage		mouse	not specified
Bisphenol A Diglycidyl Ether 1675-54-3	negative	oral: gavage		rat	OECD Guideline 488 (In Vivo Transgenic Cell Gene Mutation Assays)
Bisphenol A Diglycidyl Ether 1675-54-3	negative	oral: gavage		mouse	not specified
Bisphenol A Diglycidyl Ether 1675-54-3	negative	oral: gavage		mouse	not specified
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

# Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Bisphenol A Diglycidyl Ether 1675-54-3	not carcinogenic	oral: gavage	24 m daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Bisphenol A Diglycidyl Ether 1675-54-3	not carcinogenic	dermal	2 y 3 times/w	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

SDS No.: 173479 V005.0 Page 10 of 16

# Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Test type	Route of	Species	Method
CAS-No.			application		
Bisphenol A Diglycidyl	NOAEL $P >= 50 \text{ mg/kg}$	Two	oral: gavage	rat	OECD Guideline 416 (Two-
Ether		generation			Generation Reproduction
1675-54-3	NOAEL F1 $>= 750 \text{ mg/kg}$	study			Toxicity Study)
		1			
	NOAEL F2 $>= 750 \text{ mg/kg}$				

# STOT-single exposure:

No data available.

# STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of	Species	Method
CIAD ING.		пррисшион	treatment		
Bisphenol A Diglycidyl	NOAEL 50 mg/kg	oral: gavage	14 w	rat	OECD Guideline 408
Ether			daily		(Repeated Dose 90-Day
1675-54-3					Oral Toxicity in Rodents)
Bisphenol A Diglycidyl	NOAEL 100 mg/kg	dermal	13 w	mouse	OECD Guideline 411
Ether			3 times/w		(Subchronic Dermal
1675-54-3					Toxicity: 90-Day Study)
oxirane, mono[(C12-14-	NOAEL >= 1 mg/kg	oral: gavage	13 w	rat	OECD Guideline 411
alkyloxy)methyl] derivs.			5 d/w		(Subchronic Dermal
68609-97-2					Toxicity: 90-Day Study)

### **Aspiration hazard:**

No data available.

### 11.2 Information on other hazards

not applicable

SDS No.: 173479 V005.0 Page 11 of 16

# **SECTION 12: Ecological information**

#### General ecological information:

Do not empty into drains / surface water / ground water.

#### 12.1. Toxicity

# **Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Bisphenol A Diglycidyl Ether 1675-54-3	LC50	1,2 mg/l	96 h	Oncorhynchus mykiss	EPA-660 (Methods for Acute Toxicity Tests with Fish, Macroinvertebrates and Amphibians)
1,3-Propanediol, 2,2- bis(hydroxymethyl)-, polymer with (chloromethyl)oxirane 30973-88-7	LC50	12,7 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	LL50	> 100 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

#### **Toxicity (aquatic invertebrates):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Bisphenol A Diglycidyl Ether 1675-54-3	EC50	2,7 mg/l	48 h	Daphnia magna	other guideline:
1,3-Propanediol, 2,2- bis(hydroxymethyl)-, polymer with (chloromethyl)oxirane 30973-88-7	EC50	23,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	EL50	7,2 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.		Value	Exposure time	Species	Method
- 12 111	type				
Bisphenol A Diglycidyl Ether	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
1675-54-3					magna, Reproduction Test)
oxirane, mono[(C12-14-	NOELR	56 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
alkyloxy)methyl] derivs.					magna, Reproduction Test)
68609-97-2					

# Toxicity (Algae):

SDS No.: 173479 V005.0 Page 12 of 16

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Bisphenol A Diglycidyl Ether 1675-54-3	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	other guideline:
Bisphenol A Diglycidyl Ether 1675-54-3	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	other guideline:
1,3-Propanediol, 2,2- bis(hydroxymethyl)-, polymer with (chloromethyl)oxirane 30973-88-7	NOEC	1,7 mg/l		Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,3-Propanediol, 2,2- bis(hydroxymethyl)-, polymer with (chloromethyl)oxirane 30973-88-7	EC50	15 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### **Toxicity (microorganisms):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Bisphenol A Diglycidyl Ether	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
1675-54-3		_		_	

#### 12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Bisphenol A Diglycidyl Ether 1675-54-3	not inherently biodegradable	not specified	12 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Bisphenol A Diglycidyl Ether 1675-54-3	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
1,3-Propanediol, 2,2- bis(hydroxymethyl)-, polymer with (chloromethyl)oxirane 30973-88-7	not readily biodegradable.		< 60 %	28 day	OECD 301 A - F
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	readily biodegradable	aerobic	87 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

### 12.3. Bioaccumulative potential

No substance data available.

No data available.

SDS No.: 173479 V005.0 Page 13 of 16

#### 12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
Bisphenol A Diglycidyl Ether	> 2,64 - 3,78	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
1675-54-3			Method)
oxirane, mono[(C12-14-	3,77	20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake
alkyloxy)methyl] derivs.			Flask Method)
68609-97-2			

#### 12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
Bisphenol A Diglycidyl Ether	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
1675-54-3	Bioaccumulative (vPvB) criteria.
oxirane, mono[(C12-14-alkyloxy)methyl]	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
derivs.	Bioaccumulative (vPvB) criteria.
68609-97-2	

#### 12.6. Endocrine disrupting properties

not applicable

#### 12.7. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

#### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

#### Waste code

08 04 09\* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SDS No.: 173479 V005.0 Page 14 of 16

# **SECTION 14: Transport information**

#### 14.1. UN number or ID number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

# 14.2. UN proper shipping name

ADR ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Bisphenol-A Epichlorhydrin resin)

RID ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Bisphenol-A Epichlorhydrin resin)

ADN ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Bisphenol-A Epichlorhydrin resin)

IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Bisphenol-A Epichlorhydrin resin)

IATA Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin

resin)

# 14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

#### 14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

# 14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous

IMDG Marine Pollutant

IATA Environmentally Hazardous

### 14.6. Special precautions for user

ADR not applicable

SDS No.: 173479 V005.0 Page 15 of 16

RID not applicable
ADN not applicable
IMDG not applicable
IATA not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable Not applicable Not applicable

VOC content (2010/75/EC) < 3,00 % Combined A/B

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

#### National regulations/information (Germany):

WGK:	WGK 3: highly hazardous to water (Ordinance on facilities for handling
	substances that are hazardous to water (AwSV))
	Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 10

SDS No.: 173479 V005.0 Page 16 of 16

#### **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL: Substance with a Union workplace exposure limit
EU EXPLD 1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2 Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC: Substance of very high concern (REACH Candidate List)
PBT: Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

#### **Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

#### Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.



LOCTITE EA 3472 Part B

# Safety Data Sheet according to (EC) No 1907/2006 as amendedPage 1 of 29

SDS No.: 173480 V005.0

Revision: 17.01.2024

printing date: 22.01.2024

Replaces version from: 16.01.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE EA 3472 Part B

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Epoxy Hardener

#### 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

#### 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification (CLP):

Skin corrosion Category 1B

H314 Causes severe skin burns and eye damage.

Serious eye damage Category 1

H318 Causes serious eye damage.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment Category 3

H412 Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

#### Label elements (CLP):

Hazard pictogram:



Contains Isophorone diamine

SDS No.: 173480 V005.0 Page 2 of 29

Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and

triethylenetetramine

N-(3-(Trimethoxysilyl)propyl)ethylenediamine

3,6-diazaoctanethylenediamine

Formaldehyde, polymer with benzenamine, hydrogenated

4,4'-Methylenebis(cyclohexylamine)

Signal word: Danger

**Hazard statement:** H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statement:** P273 Avoid release to the environment.

**Prevention** P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement:

Response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER or doctor.

#### 2.3. Other hazards

None if used properly.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

SDS No.: 173480 V005.0 Page 3 of 29

# Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Isophorone diamine 2855-13-2 220-666-8 01-2119514687-32	5- < 10 %	Skin Sens. 1A, H317 Eye Dam. 1, H318 Skin Corr. 1B, H314 Acute Tox. 4, Oral, H302	Skin Sens. 1A; H317; C >= 0,001 % ====== oral:ATE = 1.030 mg/kg inhalation:ATE = 5,011 mg/l;	
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	3-< 5%	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411		
benzyl alcohol 100-51-6 202-859-9 01-2119492630-38	2,5-< 5 %	Acute Tox. 4, Oral, H302 Acute Tox. 4, Inhalation, H332 Eye Irrit. 2, H319	dermal:ATE = 2.500 mg/kg inhalation:ATE = 4,17 mg/l;dust/mist	
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2 603-894-6 01-2119983522-33	1- < 2,5 %	Acute Tox. 3, Oral, H301 Skin Corr. 1C, H314 STOT RE 2, H373 Aquatic Chronic 3, H412 Eye Dam. 1, H318 Skin Sens. 1, H317	dermal:ATE = > 2.000 mg/kg	
1,5-Pentanediamine, 2-methyl- 15520-10-2 239-556-6 01-2119976310-41	1- < 2,5 %	Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312 Acute Tox. 4, Inhalation, H332 Eye Dam. 1, H318 Skin Corr. 1A, H314 STOT SE 3, H335	inhalation:ATE = 1,225 mg/l;dust/mist	
Salicylic acid 69-72-7 200-712-3 01-2119486984-17	1-< 2,5 %	Repr. 2, H361d Acute Tox. 4, Oral, H302 Eye Dam. 1, H318		
2,4,6- tris(dimethylaminomethyl)phenol 90-72-2 202-013-9 01-2119560597-27	1- < 2,5 %	Acute Tox. 4, Oral, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319		
N-(3- (Trimethoxysilyl)propyl)ethylene diamine 1760-24-3 217-164-6 01-2119970215-39	0,1-< 1 %	Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 4, Inhalation, H332 STOT RE 2, Inhalation, H373	inhalation:ATE = 1,49 mg/l;dust/mist	
3,6-diazaoctanethylenediamine 112-24-3 203-950-6 01-2119487919-13	0,25-< 1 %	Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312 Skin Sens. 1, H317 Skin Corr. 1B, H314 Aquatic Chronic 3, H412		
4,4'- Methylenebis(cyclohexylamine) 1761-71-3 217-168-8 01-2119541673-38 01-2119979542-27	0,1-< 1 %	Acute Tox. 4, Oral, H302 Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT RE 2, Oral, H373 Eye Dam. 1, H318		

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the H - statements and other abbreviations see section 16 "Other information".

SDS No.: 173480 V005.0 Page 4 of 29

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

SKIN: Rash, Urticaria.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

water, carbon dioxide, foam, powder

#### Extinguishing media which must not be used for safety reasons:

High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### **Additional information:**

In case of fire, keep containers cool with water spray.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

Avoid dust formation.

#### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

# 6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

Scrape up as much material as possible.

Sweep up spilled material. Avoid creating dust.

Store in a partly filled, closed container until disposal.

SDS No.: 173480 V005.0 Page 5 of 29

#### 6.4. Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid skin and eye contact. See advice in section 8

#### Hygiene measures:

Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Good industrial hygiene practices should be observed.

# 7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container. Store in a cool, well-ventilated place. Refer to Technical Data Sheet

#### 7.3. Specific end use(s)

Epoxy Hardener

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **Occupational Exposure Limits**

Valid for

Germany

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Benzyl alcohol 100-51-6			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Benzyl alcohol 100-51-6	5	22	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Benzyl alcohol 100-51-6			Skin designation:	Can be absorbed through the skin.	TRGS 900

SDS No.: 173480 V005.0 Page 6 of 29

# **Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
	compartment	periou	mg/l	ppm	mg/kg	others	
3-Aminomethyl-3,5,5-	aqua		0,06 mg/l				
trimethylcyclohexylamine	(freshwater)						
2855-13-2							
3-Aminomethyl-3,5,5-	aqua (marine		0,006 mg/l				
trimethylcyclohexylamine	water)						
2855-13-2			0.22/1				
3-Aminomethyl-3,5,5- trimethylcyclohexylamine	aqua (intermittent		0,23 mg/l				
2855-13-2	releases)						
3-Aminomethyl-3,5,5-	sediment				5,784		
trimethylcyclohexylamine	(freshwater)				mg/kg		
2855-13-2	(======================================				88		
3-Aminomethyl-3,5,5-	sediment				0,578		
trimethylcyclohexylamine	(marine water)				mg/kg		
2855-13-2							
3-Aminomethyl-3,5,5-	Soil				1,121		
trimethylcyclohexylamine					mg/kg		
2855-13-2							
3-Aminomethyl-3,5,5-	sewage		3,18 mg/l				
trimethylcyclohexylamine	treatment plant						
2855-13-2 Fatty acids, C18 unsaturated, dimers,	(STP)		0.00424				
	aqua (frachyyatar)		0,00434				
polymers with tall oil fatty acids and triethylenetetramine	(freshwater)		mg/l				
68082-29-1							
Fatty acids, C18 unsaturated, dimers,	agua (marine		0,00043				
polymers with tall oil fatty acids and	water)		mg/l				
triethylenetetramine	water)		ing/i				
68082-29-1							
Fatty acids, C18 unsaturated, dimers,	aqua		0,0434				
polymers with tall oil fatty acids and	(intermittent		mg/l				
triethylenetetramine	releases)						
68082-29-1							
Fatty acids, C18 unsaturated, dimers,	sewage		3,84 mg/l				
polymers with tall oil fatty acids and	treatment plant						
triethylenetetramine	(STP)						
68082-29-1					121.02		
Fatty acids, C18 unsaturated, dimers,	sediment				434,02		
polymers with tall oil fatty acids and triethylenetetramine	(freshwater)				mg/kg		
68082-29-1							
Fatty acids, C18 unsaturated, dimers,	sediment				43,4 mg/kg		
polymers with tall oil fatty acids and	(marine water)				15,1 1116/116		
triethylenetetramine	(marme water)						
68082-29-1							
Fatty acids, C18 unsaturated, dimers,	Soil				86,78		
polymers with tall oil fatty acids and					mg/kg		
triethylenetetramine							
68082-29-1	~				0.153		
Benzyl alcohol	Soil				0,456		
100-51-6 Benzyl alcohol	covic ~ c		39 mg/l	1	mg/kg		
100-51-6	sewage treatment plant		Jy IIIg/I				
100 51-0	(STP)						
Benzyl alcohol	sediment				5,27 mg/kg		
100-51-6	(freshwater)				-,2,g/Ng		
Benzyl alcohol	sediment				0,527		
100-51-6	(marine water)				mg/kg		
Benzyl alcohol	aqua (marine	<u></u>	0,1 mg/l				
100-51-6	water)						
Benzyl alcohol	aqua		2,3 mg/l				
100-51-6	(intermittent						
D 1 1 1 1	releases)		1 8	<b> </b>			
Benzyl alcohol	aqua		1 mg/l				
100-51-6 Benzyl alcohol	(freshwater) Predator						no notantial fac
100-51-6	riedator						no potential for bioaccumulation
Formaldehyde, polymer with benzenamine	, aqua		0,015 mg/l	<del>                                     </del>			bioaccumulation
i ormalucityuc, porymer with benzenamme	, aqua		10,013 IIIg/I	I	I	L	l

SDS No.: 173480 V005.0 Page 7 of 29

hydrogenated 135108-88-2	(freshwater)			
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	aqua (marine water)	0,002 mg/l		
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	aqua (intermittent releases)	0,15 mg/l		
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	sewage treatment plant (STP)	1,9 mg/l		
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	sediment (freshwater)		15 mg/kg	
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	sediment (marine water)		1,5 mg/kg	
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	Soil		1,8 mg/kg	
2-Methylpentane-1,5-diamine 15520-10-2	aqua (freshwater)	0,42 mg/l		
2-Methylpentane-1,5-diamine 15520-10-2	aqua (marine water)	0,042 mg/l		
2-Methylpentane-1,5-diamine 15520-10-2	sewage treatment plant (STP)	1250 mg/l		
2-Methylpentane-1,5-diamine 15520-10-2	sediment (freshwater)		7,58 mg/kg	
2-Methylpentane-1,5-diamine 15520-10-2	sediment (marine water)		0,758 mg/kg	
2-Methylpentane-1,5-diamine 15520-10-2	Soil		1,27 mg/kg	
2-Methylpentane-1,5-diamine 15520-10-2	aqua (intermittent releases)	0,42 mg/l		
Salicylic acid 69-72-7	aqua (freshwater)	0,2 mg/l		
Salicylic acid 69-72-7	aqua (marine water)	0,02 mg/l		
Salicylic acid 69-72-7	aqua (intermittent releases)	1 mg/l		
Salicylic acid 69-72-7	sewage treatment plant (STP)	162 mg/l		
Salicylic acid 69-72-7	sediment (freshwater)		1,42 mg/kg	
Salicylic acid 69-72-7	sediment (marine water)		0,142 mg/kg	
Salicylic acid 69-72-7	Soil		0,166 mg/kg	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	aqua (freshwater)	0,046 mg/l		
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	aqua (marine water)	0,005 mg/l		
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Freshwater - intermittent	0,46 mg/l		
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Marine water - intermittent	0,046 mg/l		
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	sewage treatment plant (STP)	0,2 mg/l		
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	sediment (freshwater)		0,262 mg/kg	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	sediment (marine water)		0,026 mg/kg	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Soil		0,025 mg/kg	
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	aqua (freshwater)	0,05 mg/l		
N-(3- (Trimethoxysilyl)propyl)ethylenediamine	aqua (marine water)	0,005 mg/l		

SDS No.: 173480 V005.0 Page 8 of 29

1760-24-3				
N-(3-	Freshwater -	0,072 mg/l		
(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	intermittent	3,3.2.11.2		
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	sediment (freshwater)		0,181 mg/kg	
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	sediment (marine water)		0,018 mg/kg	
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Soil		0,007 mg/kg	
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	sewage treatment plant (STP)	20 mg/l		
3,6-diazaoctanethylenediamine 112-24-3	aqua (freshwater)	0,027 mg/l		
3,6-diazaoctanethylenediamine 112-24-3	aqua (marine water)	0,003 mg/l		
3,6-diazaoctanethylenediamine 112-24-3	Sewage treatment plant	0,13 mg/l		
3,6-diazaoctanethylenediamine 112-24-3	sediment (freshwater)		8,572 mg/kg	
3,6-diazaoctanethylenediamine 112-24-3	sediment (marine water)		0,857 mg/kg	
3,6-diazaoctanethylenediamine 112-24-3	Soil		1,25 mg/kg	
3,6-diazaoctanethylenediamine 112-24-3	Freshwater - intermittent	0,2 mg/l		
3,6-diazaoctanethylenediamine 112-24-3	Marine water - intermittent	0,02 mg/l		
4,4'-Methylenebis(cyclohexylamine) 1761-71-3	aqua (intermittent releases)	0,08 mg/l		
4,4'-Methylenebis(cyclohexylamine) 1761-71-3	sediment (freshwater)		136,6 mg/kg	
4,4'-Methylenebis(cyclohexylamine) 1761-71-3	aqua (marine water)	0,008 mg/l		
4,4'-Methylenebis(cyclohexylamine) 1761-71-3	sediment (marine water)		13,7 mg/kg	
4,4'-Methylenebis(cyclohexylamine) 1761-71-3	sewage treatment plant (STP)	3,2 mg/l		
4,4'-Methylenebis(cyclohexylamine) 1761-71-3	Soil		27,3 mg/kg	
4,4'-Methylenebis(cyclohexylamine) 1761-71-3	aqua (freshwater)	0,08 mg/l		

SDS No.: 173480 V005.0 Page 9 of 29

# **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
3-Aminomethyl-3,5,5- trimethylcyclohexylamine	Workers	inhalation	Long term exposure - local		0,073 mg/m3	
2855-13-2 3-Aminomethyl-3,5,5-	Workers	inhalation	effects Acute/short term		0,073 mg/m3	
trimethylcyclohexylamine 2855-13-2			exposure - local effects			
3-Aminomethyl-3,5,5- trimethylcyclohexylamine	General population	oral	Long term exposure -		0,526 mg/kg	
2855-13-2 Fatty acids, C18 unsaturated, dimers,	Workers	inhalation	systemic effects Long term		3,9 mg/m3	
polymers with tall oil fatty acids and triethylenetetramine 68082-29-1			exposure - systemic effects			
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	Workers	dermal	Long term exposure - systemic effects		1,1 mg/kg	
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	General population	inhalation	Long term exposure - systemic effects		0,97 mg/m3	
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	General population	dermal	Long term exposure - systemic effects		0,56 mg/kg	
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	General population	oral	Long term exposure - systemic effects		0,56 mg/kg	
Benzyl alcohol 100-51-6	General population	oral	Acute/short term exposure - systemic effects		20 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	oral	Long term exposure - systemic effects		4 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	Workers	inhalation	Acute/short term exposure - systemic effects		110 mg/m3	no potential for bioaccumulation
Benzyl alcohol 100-51-6	Workers	inhalation	Long term exposure - systemic effects		22 mg/m3	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	inhalation	Acute/short term exposure - systemic effects		27 mg/m3	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	inhalation	Long term exposure - systemic effects		5,4 mg/m3	no potential for bioaccumulation
Benzyl alcohol 100-51-6	Workers	dermal	Acute/short term exposure - systemic effects		40 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	Workers	dermal	Long term exposure - systemic effects		8 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	dermal	Acute/short term exposure - systemic effects		20 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	dermal	Long term exposure - systemic effects		4 mg/kg	no potential for bioaccumulation
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	Workers	inhalation	Long term exposure - systemic effects		0,2 mg/m3	
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	Workers	inhalation	Acute/short term exposure - systemic effects		2 mg/m3	
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	Workers	dermal	Long term exposure - systemic effects		2 mg/kg	
Formaldehyde, polymer with benzenamine,	Workers	dermal	Acute/short term		6 mg/kg	

SDS No.: 173480 V005.0 Page 10 of 29

hydrogenated 135108-88-2			exposure - systemic effects		
2-Methylpentane-1,5-diamine 15520-10-2	Workers	inhalation	Long term exposure - local effects	0,25 mg/m3	
2-Methylpentane-1,5-diamine 15520-10-2	Workers	inhalation	Acute/short term exposure - local effects	0,5 mg/m3	
2-Methylpentane-1,5-diamine 15520-10-2	Workers	dermal	Long term exposure - systemic effects	1,5 mg/kg	
2-Methylpentane-1,5-diamine 15520-10-2	General population	inhalation	Long term exposure - local effects	0,125 mg/m3	
2-Methylpentane-1,5-diamine 15520-10-2	General population	inhalation	Acute/short term exposure - local effects	0,25 mg/m3	
2-Methylpentane-1,5-diamine 15520-10-2	General population	dermal	Long term exposure - systemic effects	0,75 mg/kg	
2-Methylpentane-1,5-diamine 15520-10-2	General population	oral	Long term exposure - systemic effects	0,75 mg/kg	
Salicylic acid 69-72-7	Workers	dermal	Long term exposure - systemic effects	2,3 mg/kg	
Salicylic acid 69-72-7	Workers	inhalation	Long term exposure - systemic effects	5 mg/m3	
Salicylic acid 69-72-7	General population	oral	Acute/short term exposure - systemic effects	4 mg/kg	
Salicylic acid 69-72-7	General population	dermal	Long term exposure - systemic effects	1 mg/kg	
Salicylic acid 69-72-7	General population	inhalation	Long term exposure - systemic effects	4 mg/m3	
Salicylic acid 69-72-7	General population	oral	Long term exposure - systemic effects	1 mg/kg	
Salicylic acid 69-72-7	Workers	inhalation	Long term exposure - local effects	5 mg/m3	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Workers	inhalation	Long term exposure - systemic effects	0,53 mg/m3	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Workers	inhalation	Acute/short term exposure - systemic effects	2,1 mg/m3	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Workers	dermal	Long term exposure - systemic effects	0,15 mg/kg	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Workers	dermal	Acute/short term exposure - systemic effects	0,6 mg/kg	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	inhalation	Long term exposure - systemic effects	0,13 mg/m3	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	inhalation	Acute/short term exposure - systemic effects	0,13 mg/m3	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	dermal	Long term exposure - systemic effects	0,075 mg/kg	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	dermal	Acute/short term exposure - systemic effects	0,075 mg/kg	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	oral	Long term exposure - systemic effects	0,075 mg/kg	
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	inhalation	Long term exposure - systemic effects	130 mg/m3	
N-(3-	Workers	inhalation	Acute/short term	5,36 mg/m3	

SDS No.: 173480 V005.0 Page 11 of 29

(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3			exposure - local effects		
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	inhalation	Long term exposure - systemic effects	26 mg/m3	
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	oral	Long term exposure - systemic effects	4 mg/kg	
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	inhalation	Acute/short term exposure - local effects	4 mg/m3	
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	inhalation	Long term exposure - local effects	0,6 mg/m3	
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	inhalation	Long term exposure - local effects	0,1 mg/m3	
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	inhalation	Acute/short term exposure - systemic effects	26400 mg/m3	
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	dermal	Long term exposure - local effects		
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	dermal	Acute/short term exposure - local effects		
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	dermal	Long term exposure - local effects		
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	dermal	Acute/short term exposure - local effects		
3,6-diazaoctanethylenediamine 112-24-3	Workers	inhalation	Long term exposure - systemic effects	0,54 mg/m3	
3,6-diazaoctanethylenediamine 112-24-3	General population	inhalation	Long term exposure - systemic effects	0,096 mg/m3	
3,6-diazaoctanethylenediamine 112-24-3	General population	oral	Long term exposure - systemic effects	0,14 mg/kg	
4,4'-Methylenebis(cyclohexylamine) 1761-71-3	Workers	inhalation	Long term exposure - systemic effects	0,13 mg/m3	
4,4'-Methylenebis(cyclohexylamine) 1761-71-3	Workers	dermal	Long term exposure - systemic effects	0,053 mg/kg	
4,4'-Methylenebis(cyclohexylamine) 1761-71-3	Workers	inhalation	Long term exposure - local effects		
4,4'-Methylenebis(cyclohexylamine) 1761-71-3	Workers	inhalation	Acute/short term exposure - local effects		
4,4'-Methylenebis(cyclohexylamine) 1761-71-3	Workers	dermal	Long term exposure - local effects		
4,4'-Methylenebis(cyclohexylamine) 1761-71-3	Workers	dermal	Long term exposure - local effects		

# **Biological Exposure Indices:**

None

# 8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

SDS No.: 173480 V005.0 Page 12 of 29

#### Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

#### Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

#### Eve protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

#### Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

#### Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

#### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Delivery form paste
Colour grey
Odor amine-like
Physical state solid

Solidification temperature Not applicable, Product is a solid.

Initial boiling point  $> 200 \, ^{\circ}\text{C} (> 392 \, ^{\circ}\text{F})$ 

Flammability

The product is not flammable.

Explosive limits

Not applicable, Product is a solid.

Flash point  $> 100 \,^{\circ}\text{C} (> 212 \,^{\circ}\text{F})$ 

Auto-ignition temperature Not applicable, Product is a solid.

Decomposition temperature

Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use

9 - 12

(20 °C (68 °F); Conc.: 100 %)

Viscosity (kinematic) Not applicable, Product is a solid.

Solubility (qualitative) Insoluble

(20 °C (68 °F); Solvent: Water)

Partition coefficient: n-octanol/water Not applicable Mixture

Vapour pressure 0,02 hPa (20 °C (68 °F))

Density 2,45 g/cm3 None (20 °C (68 °F))

Relative vapour density: Not applicable, Product is a solid.

Particle characteristics Not applicable, mixture is a paste.

#### 9.2. Other information

Other information not applicable for this product

SDS No.: 173480 V005.0 Page 13 of 29

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Reacts with strong oxidants.

Acids.

Reaction with strong acids.

Strong bases.

#### 10.2. Chemical stability

Stable under recommended storage conditions.

#### 10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

#### 10.5. Incompatible materials

See section reactivity.

#### 10.6. Hazardous decomposition products

carbon oxides.

Rapid polymerisation may generate excessive heat and pressure.

May produce fumes when heated to decomposition. Fumes may contain carbon monoxide and other toxic fumes.

SDS No.: 173480 V005.0 Page 14 of 29

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

# Acute oral toxicity:

Hazardous substances	Value	Value	Species	Method
CAS-No. Isophorone diamine 2855-13-2	Acute toxicity estimate	1.030 mg/kg		Expert judgement
Fatty acids, C18 unsaturated, dimers, polymers with tall oil	(ATE) LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
fatty acids and triethylenetetramine 68082-29-1				
benzyl alcohol 100-51-6	LD50	1.620 mg/kg	rat	not specified
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	LD50	300 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
1,5-Pentanediamine, 2- methyl- 15520-10-2	LD50	1.170 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Salicylic acid 69-72-7	LD50	891 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
2,4,6- tris(dimethylaminomethyl )phenol 90-72-2	LD50	1.200 mg/kg	rat	not specified
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	LD50	2.295 mg/kg	rat	EPA OPPTS 870.1100 (Acute Oral Toxicity)
3,6- diazaoctanethylenediamin e 112-24-3	LD50	1.591 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
4,4'- Methylenebis(cyclohexyla mine) 1761-71-3	LD50	380 mg/kg	rat	EPA OPP 81-1 (Acute Oral Toxicity)

SDS No.: 173480 V005.0 Page 15 of 29

# Acute dermal toxicity:

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Isophorone diamine 2855-13-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
benzyl alcohol 100-51-6	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	Acute toxicity estimate (ATE)	> 2.000 mg/kg	rabbit	Expert judgement
1,5-Pentanediamine, 2- methyl- 15520-10-2	LD50	1.870 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Salicylic acid 69-72-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	LD50	> 2.000 mg/kg	rat	EPA OPPTS 870.1200 (Acute Dermal Toxicity)
3,6- diazaoctanethylenediamin e 112-24-3	LD50	1.465 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
4,4'- Methylenebis(cyclohexyla mine) 1761-71-3	LD50	2.110 mg/kg	rabbit	not specified

SDS No.: 173480 V005.0 Page 16 of 29

# Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value	Value	Test atmosphere	Exposure time	Species	Method
Isophorone diamine 2855-13-2	LC50	> 5,01 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Isophorone diamine 2855-13-2	Acute toxicity estimate (ATE)	5,011 mg/l				Expert judgement
benzyl alcohol 100-51-6	Acute toxicity estimate (ATE)	4,17 mg/l	dust/mist			Expert judgement
benzyl alcohol 100-51-6	LC50	> 4,178 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
1,5-Pentanediamine, 2- methyl- 15520-10-2	Acute toxicity estimate (ATE)	1,225 mg/l	dust/mist	4 h		Expert judgement
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	LC50	1,49 - 2,44 mg/l	dust/mist	4 h	rat	EPA OPPTS 870.1300 (Acute inhalation toxicity)
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	Acute toxicity estimate (ATE)	1,49 mg/l	dust/mist			Expert judgement

# Skin corrosion/irritation:

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Fatty acids, C18	irritating or		Human,	OECD Guideline 439 (In Vitro Skin Irritation:
unsaturated, dimers,	corrosive		EpiDermTM SIT	Reconstructed Human Epidermis (RHE) Test Method)
polymers with tall oil			(EPI-200),	
fatty acids and			Reconstructed	
triethylenetetramine			Human	
68082-29-1			Epidermis (RHE)	
Fatty acids, C18	not corrosive		Human, in vitro	OECD Guideline 431 (In Vitro Skin Corrosion:
unsaturated, dimers,			skin model	Reconstructed Human Epidermis (RHE) Test Method)
polymers with tall oil				
fatty acids and				
triethylenetetramine				
68082-29-1				
benzyl alcohol	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
100-51-6				
Formaldehyde, polymer	Category 1C		Corrositex	OECD Guideline 435 (In Vitro Membrane Barrier Test
with benzenamine,	(corrosive)		Biobarrier	Method for Skin Corrosion)
hydrogenated			Membrane	
135108-88-2			(reconstituted	
			collagen matrix)	
1,5-Pentanediamine, 2-	highly	3 min	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
methyl-	corrosive			
15520-10-2				
Salicylic acid	slightly		rabbit	not specified
69-72-7	irritating			
2.4.6-	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
tris(dimethylaminomethyl				,
)phenol				
90-72-2				
2,4,6-	Sub-Category		Corrositex	OECD Guideline 435 (In Vitro Membrane Barrier Test
tris(dimethylaminomethyl	1C (corrosive)		Biobarrier	Method for Skin Corrosion)
)phenol	- (		Membrane	
90-72-2			(reconstituted	
<del>-</del>			collagen matrix)	
N-(3-	mildly	4 h	rabbit	EPA OPPTS 870.2500 (Acute Dermal Irritation)

SDS No.: 173480 V005.0 Page 17 of 29

(Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	irritating			
3,6- diazaoctanethylenediamin e 112-24-3	corrosive		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
4,4'- Methylenebis(cyclohexyla mine) 1761-71-3	corrosive	2,75 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

# Serious eye damage/irritation:

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Isophorone diamine 2855-13-2	corrosive		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
benzyl alcohol 100-51-6	irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Salicylic acid 69-72-7	highly irritating		rabbit	Draize Test
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
4,4'- Methylenebis(cyclohexyla mine) 1761-71-3	Category 1 (irreversible effects on the eye)		rabbit	not specified

SDS No.: 173480 V005.0 Page 18 of 29

# Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Isophorone diamine 2855-13-2	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	sensitising	Buehler test	guinea pig	Buehler test
Salicylic acid 69-72-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,4,6- tris(dimethylaminomethyl )phenol 90-72-2	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2,4,6- tris(dimethylaminomethyl )phenol 90-72-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	Sub-Category 1A (sensitising)	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
3,6- diazaoctanethylenediamin e 112-24-3	sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)

SDS No.: 173480 V005.0 Page 19 of 29

# Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Isophorone diamine 2855-13-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
benzyl alcohol 100-51-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Salicylic acid 69-72-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Salicylic acid 69-72-7	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Salicylic acid 69-72-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2,4,6- tris(dimethylaminomethyl )phenol 90-72-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,4,6- tris(dimethylaminomethyl )phenol 90-72-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2,4,6- tris(dimethylaminomethyl )phenol 90-72-2	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
3,6- diazaoctanethylenediamin e 112-24-3	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
3,6- diazaoctanethylenediamin e 112-24-3	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	with and without		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)

# Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
benzyl alcohol 100-51-6	not carcinogenic	oral: gavage	104 weeks once daily, 5 days/week	rat	male/female	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
Salicylic acid 69-72-7	not carcinogenic	oral: feed	2 years daily	rat	male/female	not specified

SDS No.: 173480 V005.0 Page 20 of 29

# Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Test type	Route of	Species	Method
CAS-No.			application		
benzyl alcohol 100-51-6	NOAEL P 200 mg/kg	screening	oral: gavage	mouse	not specified
Salicylic acid 69-72-7	NOAEL P 250 mg/kg	three- generation study	oral: feed	rat	equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

# STOT-single exposure:

No data available.

# STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Isophorone diamine 2855-13-2	NOAEL < 60 mg/kg	oral: drinking water	13 weeks	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
benzyl alcohol 100-51-6	NOAEL 400 mg/kg	oral: gavage	13 weeks once daily, 5 days/week	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	NOAEL 15 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Salicylic acid 69-72-7	NOAEL 50 mg/kg	oral: feed	2 years daily	rat	not specified
3,6- diazaoctanethylenediamin e 112-24-3	LOAEL 50 mg/kg	oral: gavage	26 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
3,6- diazaoctanethylenediamin e 112-24-3	NOAEL 50 mg/kg	oral: gavage	26 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
4,4'- Methylenebis(cyclohexyla mine) 1761-71-3	NOAEL 15 mg/kg	oral: gavage	M: 36 d / F: 48-52 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

### **Aspiration hazard:**

No data available.

# 11.2 Information on other hazards

not applicable

SDS No.: 173480 V005.0 Page 21 of 29

# **SECTION 12: Ecological information**

### General ecological information:

Do not empty into drains / surface water / ground water.

#### 12.1. Toxicity

# **Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Isophorone diamine 2855-13-2	LC50	110 mg/l	96 h	Leuciscus idus	EU Method C.1 (Acute Toxicity for Fish)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	LC50	7,07 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
benzyl alcohol 100-51-6	LC50	460 mg/l	96 h	Pimephales promelas	EPA OPP 72-1 (Fish Acute Toxicity Test)
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	LC50	96 mg/l	96 h	Poecilia reticulata	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,5-Pentanediamine, 2- methyl- 15520-10-2	LC50	1.825 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Salicylic acid 69-72-7	LC50	1.370 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,4,6- tris(dimethylaminomethyl)phe nol 90-72-2	LC50	153 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	ISO 7346-1 (Determination of the Acute Lethal Toxicity of Substances to a Freshwater Fish [Brachydanio rerio Hamilton-Buchanan (Teleostei, Cyprinidae)]
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	LC50	168 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
3,6- diazaoctanethylenediamine 112-24-3	LC50	570 mg/l	96 h	Poecilia reticulata	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'- Methylenebis(cyclohexylamin e) 1761-71-3	LC50	> 100 mg/l	96 h	Leuciscus idus	DIN 38412-15

#### **Toxicity (aquatic invertebrates):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Isophorone diamine 2855-13-2	EC50	23 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	EC50	7,07 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
benzyl alcohol 100-51-6	EC50	230 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Formaldehyde, polymer with	EC50	15,4 mg/l	48 h	Daphnia magna	OECD Guideline 202

SDS No.: 173480 V005.0 Page 22 of 29

benzenamine, hydrogenated 135108-88-2					(Daphnia sp. Acute Immobilisation Test)
1,5-Pentanediamine, 2-methyl- 15520-10-2	EC50	19,8 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Salicylic acid 69-72-7	EC50	870 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2,4,6- tris(dimethylaminomethyl)phe nol 90-72-2	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	EC50	87,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3,6- diazaoctanethylenediamine 112-24-3	EC50	31 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'- Methylenebis(cyclohexylamin e) 1761-71-3	EC50	7,07 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

# ${\bf Chronic\ toxicity\ (aquatic\ invertebrates):}$

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Isophorone diamine	NOEC	3 mg/l	21 d	Daphnia magna	OECD Guideline 202
2855-13-2					(Daphnia sp. Chronic
					Immobilisation Test)
benzyl alcohol	NOEC	51 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
100-51-6					magna, Reproduction Test)
1,5-Pentanediamine, 2-methyl-	NOEC	4,16 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
15520-10-2					magna, Reproduction Test)
Salicylic acid	NOEC	10 mg/l	21 d	Daphnia magna	OECD Guideline 202
69-72-7					(Daphnia sp. Chronic
					Immobilisation Test)
N-(3-	NOEC	> 1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
(Trimethoxysilyl)propyl)ethyl					magna, Reproduction Test)
enediamine					
1760-24-3					
4,4'-	NOEC	4 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
Methylenebis(cyclohexylamin					magna, Reproduction Test)
e)					
1761-71-3					

# **Toxicity (Algae):**

SDS No.: 173480 V005.0 Page 23 of 29

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Isophorone diamine 2855-13-2	EC10	11,2 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)
Isophorone diamine 2855-13-2	EC50	> 50 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	EC50	4,34 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	NOEC	0,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzyl alcohol 100-51-6	EC50	770 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzyl alcohol 100-51-6	NOEC	310 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	EC10	1,2 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	EC50	43,94 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)
1,5-Pentanediamine, 2-methyl- 15520-10-2	EC50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,5-Pentanediamine, 2-methyl- 15520-10-2	NOEC	10 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Salicylic acid 69-72-7	EC50	> 100 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,4,6- tris(dimethylaminomethyl)phe nol 90-72-2	EC50	46,7 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,4,6- tris(dimethylaminomethyl)phe nol 90-72-2	NOEC	6,44 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	EC50	8,8 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	NOEC	3,1 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
3,6- diazaoctanethylenediamine 112-24-3	EC50	20 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'- Methylenebis(cyclohexylamin e) 1761-71-3	EC50	> 140 - 200 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
4,4'- Methylenebis(cyclohexylamin e) 1761-71-3	EC10	100 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09

# Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Isophorone diamine	EC10	1.120 mg/l	18 h	Pseudomonas putida	DIN 38412, part 8

SDS No.: 173480 V005.0 Page 24 of 29

2855-13-2					(Pseudomonas Zellvermehrungshemm- Test)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	EC10	130 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
benzyl alcohol 100-51-6	EC10	658 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
Salicylic acid 69-72-7	EC50	> 1.000 mg/l	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
2,4,6- tris(dimethylaminomethyl)phe nol 90-72-2	EC0	27 mg/l	16 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	EC 50	435 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
3,6- diazaoctanethylenediamine 112-24-3	EC0	137 mg/l	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
4,4'- Methylenebis(cyclohexylamin e) 1761-71-3	EC20	> 1.000 mg/l	3 h	activated sludge, industrial	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

# 12.2. Persistence and degradability

SDS No.: 173480 V005.0 Page 25 of 29

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Isophorone diamine 2855-13-2	not readily biodegradable.	aerobic	8 %	28 d	EU Method C.4-A (Determination of the "Ready" BiodegradabilityDissolved Organic Carbon (DOC) Die-Away Test)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	not readily biodegradable.	no data	0 - 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
benzyl alcohol 100-51-6	readily biodegradable	aerobic	92 - 96 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
1,5-Pentanediamine, 2-methyl- 15520-10-2	readily biodegradable	aerobic	100 %	21 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Salicylic acid 69-72-7	readily biodegradable	aerobic	88,1 %	15 d	EU Method C.4-F (Determination of the "Ready" BiodegradabilityMITI Test)
Salicylic acid 69-72-7	inherently biodegradable	aerobic	100 %	4 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
2,4,6- tris(dimethylaminomethyl)phe nol 90-72-2	not readily biodegradable.	aerobic	4 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3		aerobic	50 %		OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
3,6- diazaoctanethylenediamine 112-24-3	not inherently biodegradable	aerobic	0 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
3,6- diazaoctanethylenediamine 112-24-3	not readily biodegradable.	aerobic	0 %	162 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
4,4'- Methylenebis(cyclohexylamin e) 1761-71-3	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

# ${\bf 12.3.\ Bioaccumulative\ potential}$

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Bioconcentratio	Exposure time	Temperature	Species	Method
CAS-No.	n factor (BCF)				
Formaldehyde, polymer with	18 - 219	56 d		Cyprinus carpio	OECD Guideline 305 C
benzenamine, hydrogenated					(Bioaccumulation: Test for the
135108-88-2					Degree of Bioconcentration in
					Fish)
4,4'-	< 60	60 d	24 °C	Cyprinus carpio	OECD Guideline 305 C
Methylenebis(cyclohexylamin					(Bioaccumulation: Test for the
e)					Degree of Bioconcentration in
1761-71-3					Fish)

SDS No.: 173480 V005.0 Page 26 of 29

# 12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	LogPow	Temperature	Method
CAS-No.		<b>F</b>	
Isophorone diamine 2855-13-2	0,99	23 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	10,34		QSAR (Quantitative Structure Activity Relationship)
benzyl alcohol 100-51-6	1,05	20 °C	EU Method A.8 (Partition Coefficient)
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	2,68	21 °C	EU Method A.8 (Partition Coefficient)
1,5-Pentanediamine, 2- methyl- 15520-10-2	<= 1	25 °C	other guideline:
Salicylic acid 69-72-7	2,26	20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2,4,6- tris(dimethylaminomethyl)phe nol 90-72-2	-0,66	21,5 °C	EPA OPPTS 830.7550 (Partition Coefficient, n-octanol / H2O, Shake Flask Method)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	-1,67		not specified
3,6- diazaoctanethylenediamine 112-24-3	-2,65		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
4,4'- Methylenebis(cyclohexylamin e) 1761-71-3	2,2	23 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

# 12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
Isophorone diamine	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
2855-13-2	Bioaccumulative (vPvB) criteria.
Fatty acids, C18 unsaturated, dimers, polymers	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
with tall oil fatty acids and triethylenetetramine	Bioaccumulative (vPvB) criteria.
68082-29-1	N. (C.1C.11; D. ' ( D. ' ) 1 (' ) 1 TE ' (DDT) D. ' ( ) 1
benzyl alcohol	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
100-51-6	Bioaccumulative (vPvB) criteria.
Formaldehyde, polymer with benzenamine,	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
hydrogenated	Bioaccumulative (vPvB) criteria.
135108-88-2	
1,5-Pentanediamine, 2-methyl-	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
15520-10-2	Bioaccumulative (vPvB) criteria.
Salicylic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
69-72-7	Bioaccumulative (vPvB) criteria.
2,4,6-tris(dimethylaminomethyl)phenol	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
90-72-2	Bioaccumulative (vPvB) criteria.
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
1760-24-3	Bioaccumulative (vPvB) criteria.
3,6-diazaoctanethylenediamine	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
112-24-3	Bioaccumulative (vPvB) criteria.
4,4'-Methylenebis(cyclohexylamine)	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
1761-71-3	Bioaccumulative (vPvB) criteria.

# 12.6. Endocrine disrupting properties

SDS No.: 173480 V005.0 Page 27 of 29

#### 12.7. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

#### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

#### Waste code

08 04 09\* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

# **SECTION 14: Transport information**

#### 14.1. UN number or ID number

ADR	1759
RID	1759
ADN	1759
IMDG	1759
IATA	1759

# 14.2. UN proper shipping name

ADR	CORROSIVE SOLID, N.O.S. (Isophoronediamine,2-Methylpentane-1,5-diamine)
RID	CORROSIVE SOLID, N.O.S. (Isophoronediamine,2-Methylpentane-1,5-diamine)
ADN	CORROSIVE SOLID, N.O.S. (Isophoronediamine,2-Methylpentane-1,5-diamine)
IMDG	CORROSIVE SOLID, N.O.S. (Isophoronediamine,2-Methylpentane-1,5-diamine)
IATA	Corrosive solid, n.o.s. (Isophoronediamine, 2-Methylpentane-1,5-diamine)

# 14.3. Transport hazard class(es)

ADR	8
RID	8
ADN	8
IMDG	8
IATA	8

#### 14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

#### 14.5. Environmental hazards

ADR	not applicable
RID	not applicable

SDS No.: 173480 V005.0 Page 28 of 29

ADN not applicable IMDG not applicable IATA not applicable

#### 14.6. Special precautions for user

ADR not applicable
Tunnelcode: (E)
RID not applicable
ADN not applicable
IMDG not applicable
IATA not applicable

# 14.7. Maritime transport in bulk according to IMO instruments

not applicable

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):

Not applicable Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable

VOC content 7,55 %

(2010/75/EC)

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

# National regulations/information (Germany):

WGK: WGK 3: highly hazardous to water (Ordinance on facilities for handling

substances that are hazardous to water (AwSV) ) Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 8A

SDS No.: 173480 V005.0 Page 29 of 29

#### **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL: Substance with a Union workplace exposure limit
EU EXPLD 1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2 Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC: Substance of very high concern (REACH Candidate List)
PBT: Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

#### **Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

#### Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.