



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 19

TEROSON MS 9320 GY

SDS No. : 634013

V009.0

Revision: 13.02.2024

printing date: 26.02.2024

Replaces version from: 10.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON MS 9320 GY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

MS Sealant

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin sensitizer

H317 May cause an allergic skin reaction.

Category 1

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine

Reaction mass of pentamethyl-4-piperidylsebacates

Signal word:

Warning

Hazard statement: H317 May cause an allergic skin reaction.**Supplemental information** Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.**Precautionary statement:** P280 Wear protective gloves.
Prevention

2.3. Other hazards

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene ----- 01-2119471843-32	5- < 10 %	Flam. Liq. 3, H226 Asp. Tox. 1, Oral, H304 STOT SE 3, H336 Aquatic Chronic 3, H412		
Titanium dioxide < 1% particles with diameter \leq 10 μ m 13463-67-7 236-675-5 01-2119489379-17	1- < 3 %			
N-[3- (dimethoxymethylsilyl)propyl]et hylene diamine 3069-29-2 221-336-6 01-2119963926-21	0,1- < 1 %	Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 4, Oral, H302 Skin Irrit. 2, H315	oral:ATE = 500 mg/kg inhalation:ATE = 5,21 mg/l;dust/mist	
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5 915-687-0 01-2119491304-40	0,01- < 0,1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Skin Sens. 1A, H317 Repr. 2, H361f	M acute = 1 M chronic = 1 ===== dermal:ATE = 3.171 mg/kg	
ethylenebis(oxyethylene) bis[3- (5-tert-butyl-4-hydroxy-m- tolyl)propionate] 36443-68-2 253-039-2 01-2119956160-44	0,01- < 0,016 %	Aquatic Chronic 1, H410	M chronic = 10	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water.

In case of adverse health effects seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures:

Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.
Temperatures between + 10 °C and + 25 °C.

7.3. Specific end use(s)

MS Sealant

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Limestone 1317-65-3		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Limestone 1317-65-3			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Calcium carbonate 471-34-1		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Calcium carbonate 471-34-1		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Calcium carbonate 471-34-1			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Titanium dioxide 13463-67-7		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Titanium dioxide 13463-67-7		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Titanium dioxide 13463-67-7			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
N-[3-(Dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	aqua (freshwater)		0,062 mg/l				
N-[3-(Dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	aqua (marine water)		0,0062 mg/l				
N-[3-(Dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	aqua (intermittent releases)		0,62 mg/l				
N-[3-(Dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	sediment (freshwater)				0,024 mg/kg		
N-[3-(Dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	sediment (marine water)				0,0024 mg/kg		
N-[3-(Dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	Soil				0,01 mg/kg		
N-[3-(Dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	sewage treatment plant (STP)		25 mg/l				
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	aqua (freshwater)		0,002 mg/l				
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	aqua (marine water)		0,00022 mg/l				
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	Freshwater - intermittent		0,009 mg/l				
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	sewage treatment plant (STP)		1 mg/l				
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	sediment (freshwater)				1,05 mg/kg		
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	sediment (marine water)				0,11 mg/kg		
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	Soil				0,21 mg/kg		
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	Predator						no potential for bioaccumulation
Ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate] 36443-68-2	aqua (freshwater)		0,001 mg/l				
Ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate] 36443-68-2	sediment (freshwater)				0,195 mg/kg		
Ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate] 36443-68-2	sediment (marine water)				0,019 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	Workers	dermal	Long term exposure - systemic effects		77 mg/kg	
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	Workers	Inhalation	Long term exposure - systemic effects		871 mg/m3	
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	General population	dermal	Long term exposure - systemic effects		46 mg/kg	
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	General population	Inhalation	Long term exposure - systemic effects		185 mg/m3	
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	General population	oral	Long term exposure - systemic effects		46 mg/kg	
N-[3-(Dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	Workers	inhalation	Long term exposure - systemic effects		12 mg/m3	
N-[3-(Dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	Workers	dermal	Long term exposure - systemic effects		1,7 mg/kg	
N-[3-(Dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	
N-[3-(Dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	General population	inhalation	Long term exposure - systemic effects		2,9 mg/m3	
N-[3-(Dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	Workers	inhalation	Long term exposure - systemic effects		1,27 mg/m3	no potential for bioaccumulation
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	Workers	dermal	Long term exposure - systemic effects		1,8 mg/kg	no potential for bioaccumulation
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	General population	dermal	Long term exposure - systemic effects		0,9 mg/kg	no potential for bioaccumulation
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	General population	inhalation	Long term exposure - systemic effects		0,31 mg/m3	no potential for bioaccumulation
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	General population	oral	Long term exposure - systemic effects		0,18 mg/kg	no potential for bioaccumulation
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	Workers	dermal	Long term exposure - local effects			no potential for bioaccumulation
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	Workers	dermal	Acute/short term exposure - local effects			no potential for bioaccumulation

Biological Exposure Indices:
None

8.2. Exposure controls:

Engineering controls:
Ensure good ventilation/extraction.

Respiratory protection:

The product should only be used at workplaces with intensive ventilation/extraction.

If intensive ventilation/extraction is not possible respiratory protection equipment with ABEK P2 filter (EN 14387) should be worn.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	paste
Colour	grey
Odor	alcohol-like
Physical state	solid
Melting point	Not applicable, Determination technically not possible
Solidification temperature	Not applicable, Product is a solid.
Initial boiling point	> 300 °C (> 572 °F)
Flammability	The product is not flammable.
Explosive limits	Not applicable, Product is a solid.
Flash point	Not applicable, Product is a solid.
Auto-ignition temperature	Not applicable, Product is a solid.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product reacts with water.
Viscosity (kinematic)	Not applicable, Product is a solid.
Solubility (qualitative)	Reacts with water.
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure	Mixture
(20 °C (68 °F))	< 0,1 hPa
Density	1,53 g/cm ³ no method / method unknown
(20 °C (68 °F))	
Bulk density	1,53 g/cm ³
Relative vapour density:	Not applicable, Product is a solid.
Particle characteristics	Not applicable, mixture is a paste.

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity**10.1. Reactivity**

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information**General toxicological information:**

An allergic reaction cannot be excluded after repeated skin contact.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
N-[3- (dimethoxymethylsilyl)pr opyl]ethylenediamine 3069-29-2	LD50	301 - 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
N-[3- (dimethoxymethylsilyl)pr opyl]ethylenediamine 3069-29-2	Acute toxicity estimate (ATE)	500 mg/kg		Expert judgement
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	LD50	3.230 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4- hydroxy-m- tolyl)propionate] 36443-68-2	LD50	> 7.000 mg/kg	rat	equivalent or similar to OECD Guideline 423 (Acute Oral toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	LD50	> 5.000 mg/kg	rabbit	not specified
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	LD50	≥ 10.000 mg/kg	hamster	not specified
N-[3- (dimethoxymethylsilyl)pr opyl]ethylenediamine 3069-29-2	LD50	15.520 mg/kg	rabbit	not specified
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	LD50	> 3.170 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	Acute toxicity estimate (ATE)	3.171 mg/kg		Expert judgement
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4- hydroxy-m- tolyl)propionate] 36443-68-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	LC50	> 5,6 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified
N-[3- (dimethoxymethylsilyl)pr opyl]ethylenediamine 3069-29-2	LC50	> 5,2 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
N-[3- (dimethoxymethylsilyl)pr opyl]ethylenediamine 3069-29-2	Acute toxicity estimate (ATE)	5,21 mg/l	dust/mist	4 h		Expert judgement

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	not irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
N-[3- (dimethoxymethylsilyl)pr opyl]ethylenediamine 3069-29-2	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4- hydroxy-m- tolyl)propionate] 36443-68-2	not irritating	24 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
N-[3- (dimethoxymethylsilyl)pr opyl]ethylenediamine 3069-29-2	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4- hydroxy-m- tolyl)propionate] 36443-68-2	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
N-[3- (dimethoxymethylsilyl)pr opyl]ethylenediamine 3069-29-2	Sub-Category 1A (sensitising)	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4- hydroxy-m- tolyl)propionate] 36443-68-2	not sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	not carcinogenic	inhalation	24 m 6 h/d; 5 d/w	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	NOAEL P > 1.000 mg/kg NOAEL F1 > 1.000 mg/kg		oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	NOAEL P < 221 mg/kg NOAEL F1 221 mg/kg		oral: feed	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	Category 3 with narcotic effects.			

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	NOAEL 1.000 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	0,91 mm ² /s	25 °C	not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains, soil or bodies of water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	LL50	> 10 - < 30 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	LC50	Toxicity > Water solubility	48 h	Danio rerio	other guideline:
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	NOEC	Toxicity > Water solubility	8 d	Danio rerio	OECD Guideline 212 (Fish, Short-term Toxicity Test on Embryo and Sac-Fry Stages)
N-[3- (dimethoxymethylsilyl)propyl] ethylenediamine 3069-29-2	LC50	597 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	EU Method C.1 (Acute Toxicity for Fish)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	LC50	0,9 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy- m-tolyl)propionate] 36443-68-2	LC50	Toxicity > Water solubility	96 h	Lepomis macrochirus	OECD Guideline 203 (Fish, Acute Toxicity Test)
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy- m-tolyl)propionate] 36443-68-2	NOEC	0,0088 mg/l	32 d	Pimephales promelas	OECD Guideline 210 (fish early lite stage toxicity test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	EL50	> 22 - < 46 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
N-[3- (dimethoxymethylsilyl)propyl] ethylenediamine 3069-29-2	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy- m-tolyl)propionate] 36443-68-2	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Reaction mass of pentamethyl- 4-piperidylsebacates 1065336-91-5	NOEC	1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy- m-tolyl)propionate] 36443-68-2	NOEC	0,0055 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	EL50	> 1.000 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	NOELR	< 1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass of pentamethyl- 4-piperidylsebacates 1065336-91-5	NOEC	0,22 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass of pentamethyl- 4-piperidylsebacates 1065336-91-5	EC50	1,68 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy- m-tolyl)propionate] 36443-68-2	EC50	Toxicity > Water solubility	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	EU Method C.3 (Algal Inhibition test)
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy- m-tolyl)propionate] 36443-68-2	EC10	Toxicity > Water solubility	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	EU Method C.3 (Algal Inhibition test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	EC50	Toxicity > Water solubility	3 h	activated sludge	ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)
N-[3- (dimethoxymethylsilyl)propyl] ethylenediamine 3069-29-2	EC10	25 mg/l	16 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
Reaction mass of pentamethyl- 4-piperidylsebacates 1065336-91-5	IC50	100 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy- m-tolyl)propionate] 36443-68-2	IC50	Toxicity > Water solubility	3 h	activated sludge, domestic	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	readily biodegradable	aerobic	89 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
N-[3- (dimethoxymethylsilyl)propyl] ethylenediamine 3069-29-2	not readily biodegradable.	aerobic	39 %	28 day	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
Reaction mass of pentamethyl- 4-piperidylsebacates 1065336-91-5	not readily biodegradable.	aerobic	38 %	28 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy- m-tolyl)propionate] 36443-68-2	not readily biodegradable.	aerobic	8 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	< 31,4	56 d	24,5 °C	Cyprinus carpio	other guideline:
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy- m-tolyl)propionate] 36443-68-2	> 0,11 - 2,45	56 d		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	4 - 5,7		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	1	20 °C	QSAR (Quantitative Structure Activity Relationship)
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	> 2,37 - 2,77	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate] 36443-68-2	4,7	23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Naphtha (petroleum), hydrotreated light, < 0.1 % benzene -----	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	According to Annex XIII to Regulation (EC) No 1907/2006, a PBT and vPvB assessment shall not be conducted for inorganic substances.
N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine 3069-29-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Reaction mass of pentamethyl-4-piperidylsebacates 1065336-91-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate] 36443-68-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

SECTION 14: Transport information

- 14.1. UN number or ID number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Maritime transport in bulk according to IMO instruments**
not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	9,9 %

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

National regulations/information (Germany):

WGK: WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV))
Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 11

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.