

## Teroson RB 276 Alu

March 2017

### PRODUCT DESCRIPTION

Teroson RB 276 Alu provides the following product characteristics:

<b>Technology</b>	Butyl Rubber
Product Type	Sealant
<b>Application</b>	Assembly
Appearance	Black

Teroson RB 276 Alu is a flexible, versatile applicable adhesive and sealing tape based on butyl rubber.

The product consists of a pressure sensitive, plasto-elastic butyl rubber compound with high tack and is laminated on one side with a plastic/aluminium sandwich foil which is tear-, UV- and weather-resistant. Because of its high moisture vapour resistance, the product serves as a moisture barrier.

#### Application Areas:

Teroson RB 276 Alu is used for bonding and sealing in the following applications:

- Sealing seams and overlap joints for interior and exterior applications (metal constructions, container manufacture, winter garden constructions, air-conditioning and ducting)
- Repair of refurbishment of weather-beaten joints (e.g. greenhouse)
- Sealing connections, seams or butts, when gas or moisture vapour resistance are required.

Due to varying conditions, Teroson RB 276 Alu can only be recommended with additional fixing in case of sealing overhead applications

### TECHNICAL DATA

Application temperature, °C:	5 to 40
In service temperature range, °C:	-40 to +80 (the product becomes tougher and less adhesive with lower temperatures and vice versa)

### DIRECTIONS OF USE

#### Preliminary statement:

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

#### Pre-Treatment:

The substrates must be clean, dry, free of oil, grease and other

anti-adhesive contaminants (e.g. release agents). For pretreatment Teroson VR 10 is suitable.

#### Application:

Teroson RB 276 Alu can be used on smooth surfaces, such as aluminium, galvanized sheet metal, polyester, glass, roofing membranes based on ECB, EPDM, PIB, CR, etc. When applied in connection with roofing membranes based on PVC priming with Teroson SB 914 is recommended. Teroson RB 276 Alu can be used on acrylic glass (Plexiglas®, Perspex®) and polycarbonate (Makrolon®). In the case of other plastics, please consult us for advice or conduct your own trials.

Unroll Teroson RB 276 Alu and cut it to the desired length. After removal of the separating foil the tape is applied on the substrate and carefully pressed onto it (particularly important in the case of overlaps). An even better initial adhesion is achieved by means of a roller press.

#### Notice:

For the sealing window or door connections in balconies or terraces, the DIN 18195 should be observed.

### STORAGE

Frost-Sensitive	No
Recommended Storage Temperature, °C	5 to 35
Shelf-life (in unopened original packaging), 24 months	

### ADDITIONAL INFORMATION

#### Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable

mandatory product liability law.

**In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage:** [Except as otherwise noted] All trademarks in this document are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.

Reference 0.1