



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 26

TEROSON RB R2000 HS WH 1L EGFD

SDS No. : 683953
V003.0

Revision: 09.06.2022

printing date: 24.12.2022

Replaces version from: 12.11.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON RB R2000 HS WH 1L EGFD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Underbody coating

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

ua-productsafety.de@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapour.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C9-unsatd., polymd.

Signal word:

Danger

Hazard statement:

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

**Precautionary statement:
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing vapors.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/eye protection.

**Precautionary statement:
Response**P370+P378 In case of fire: Use CO₂, dry chemical, or foam for extinction.**Precautionary statement:
Storage**

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

The solvent vapors are heavier than air and may collect in high concentrations at floor level.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration $\geq 0,1\%$ and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration \geq the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 921-024-6 01-2119475514-35	20- 40 %	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411		
Xylene - mixture of isomeres 1330-20-7 215-535-7 01-2119488216-32	5- < 10 %	Asp. Tox. 1, H304 Acute Tox. 4, Inhalation, H332 Acute Tox. 4, Dermal, H312 Skin Irrit. 2, H315 Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412		EU OEL
cyclohexane 110-82-7 203-806-2 01-2119463273-41	1- < 3 %	Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Flam. Liq. 2, H225 Skin Irrit. 2, H315	M acute = 1 M chronic = 1	EU OEL
ethylbenzene 100-41-4 202-849-4 01-2119489370-35	1- < 3 %	Flam. Liq. 2, H225 Acute Tox. 4, Inhalation, H332 Asp. Tox. 1, H304 STOT RE 2, H373 Aquatic Chronic 3, H412 Eye Irrit. 2, H319 STOT SE 3, H335 STOT SE 3, H336		EU OEL
Hydrocarbons, C9-unsatd., polymd. 71302-83-5 01-2119555292-40	1- < 3 %	Aquatic Chronic 3, H412 Skin Sens. 1A, H317		
n-Hexane 110-54-3 203-777-6 01-2119480412-44	0,1- < 1 %	Flam. Liq. 2, H225 Repr. 2, H361f Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	STOT RE 2; H373; C >= 5 %	EU OEL
zinc oxide 1314-13-2 215-222-5 01-2119463881-32	0,1- < 1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water.

In case of adverse health effects seek medical advice.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

Vapors may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

Water jet (solvent-containing product).

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

Inform authorities in the event of product spillage to water courses or sewage systems.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid open flames and sources of ignition.

Ground/bond container and receiving equipment.

Use explosion proof electric equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

7.3. Specific end use(s)

Underbody coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Limestone 1317-65-3		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Limestone 1317-65-3		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	50	221	Time Weighted Average (TWA):	Indicative	ECTLV
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	100	442	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Xylene 1330-20-7			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Xylene 1330-20-7			Skin designation:	Can be absorbed through the skin.	TRGS 900
Xylene 1330-20-7	50	220	Exposure limit(s):	2	TRGS 900
Calcium carbonate 471-34-1			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Calcium carbonate 471-34-1		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Calcium carbonate 471-34-1		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Cyclohexane 110-82-7 [CYCLOHEXANE]	200	700	Time Weighted Average (TWA):	Indicative	ECTLV
Cyclohexane 110-82-7	200	700	Exposure limit(s):	4	TRGS 900
Cyclohexane 110-82-7			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Ethylbenzene 100-41-4 [ETHYLBENZENE]	100	442	Time Weighted Average (TWA):	Indicative	ECTLV
Ethylbenzene 100-41-4 [ETHYLBENZENE]	200	884	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Ethylbenzene 100-41-4			Skin designation:	Can be absorbed through the skin.	TRGS 900
Ethylbenzene 100-41-4	20	88	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Ethylbenzene 100-41-4			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Calcium carbonate			Short Term Exposure	Category II: substances with a	TRGS 900

471-34-1			Classification:	resorptive effect.	
Calcium carbonate 471-34-1		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Calcium carbonate 471-34-1		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Titanium dioxide 13463-67-7			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Titanium dioxide 13463-67-7		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Titanium dioxide 13463-67-7		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
n-Hexane 110-54-3 [N-HEXANE]	20	72	Time Weighted Average (TWA):	Indicative	ECLTV
n-Hexane 110-54-3	50	180	Exposure limit(s):	8 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
n-Hexane 110-54-3			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Zinc oxide 1314-13-2			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Zinc oxide 1314-13-2		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Zinc oxide 1314-13-2		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Xylene - mixture of isomeres 1330-20-7	aqua (freshwater)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	sediment (freshwater)				12,46 mg/kg		
Xylene - mixture of isomeres 1330-20-7	Soil				2,31 mg/kg		
Xylene - mixture of isomeres 1330-20-7	aqua (marine water)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	aqua (intermittent releases)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	sewage treatment plant (STP)		6,58 mg/l				
Xylene - mixture of isomeres 1330-20-7	sediment (marine water)				12,46 mg/kg		
cyclohexane 110-82-7	aqua (freshwater)		0,207 mg/l				
cyclohexane 110-82-7	aqua (marine water)		0,207 mg/l				
cyclohexane 110-82-7	aqua (intermittent releases)		0,207 mg/l				
cyclohexane 110-82-7	sediment (freshwater)				16,68 mg/kg		
cyclohexane 110-82-7	sediment (marine water)				16,68 mg/kg		
cyclohexane 110-82-7	Soil				3,38 mg/kg		
cyclohexane 110-82-7	sewage treatment plant (STP)		3,24 mg/l				
cyclohexane 110-82-7	Air						
cyclohexane 110-82-7	Predator						no potential for bioaccumulation
ethylbenzene 100-41-4	aqua (intermittent releases)		0,1 mg/l				
ethylbenzene 100-41-4	aqua (freshwater)		0,1 mg/l				
ethylbenzene 100-41-4	sediment (marine water)				1,37 mg/kg		
ethylbenzene 100-41-4	sediment (freshwater)				13,7 mg/kg		
ethylbenzene 100-41-4	sewage treatment plant (STP)		9,6 mg/l				
ethylbenzene 100-41-4	aqua (marine water)		0,01 mg/l				
ethylbenzene 100-41-4	Soil				2,68 mg/kg		
ethylbenzene 100-41-4	oral				20 mg/kg		
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	Sewage treatment plant		2,2 mg/l				
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	aqua (freshwater)		0,0258 mg/l				
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	aqua (intermittent releases)		0,258 mg/l				
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	aqua (marine water)		0,00258 mg/l				
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	sediment (freshwater)				3137 mg/kg		
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	sediment (marine water)				314 mg/kg		
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	Soil				625 mg/kg		

Hydrocarbons, C9-unsatd., polymd. 71302-83-5	oral				8,89 mg/kg		
zinc oxide 1314-13-2	aqua (freshwater)		0,0206 mg/l				
zinc oxide 1314-13-2	aqua (marine water)		0,0061 mg/l				
zinc oxide 1314-13-2	sewage treatment plant (STP)		0,1 mg/l				
zinc oxide 1314-13-2	sediment (freshwater)				117,8 mg/kg		
zinc oxide 1314-13-2	sediment (marine water)				56,5 mg/kg		
zinc oxide 1314-13-2	Soil				35,6 mg/kg		
zinc oxide 1314-13-2	Air						no hazard identified
zinc oxide 1314-13-2	oral						no potential for bioaccumulation

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Workers	dermal	Long term exposure - systemic effects		773 mg/kg	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Workers	inhalation	Long term exposure - systemic effects		2035 mg/m3	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	General population	dermal	Long term exposure - systemic effects		699 mg/kg	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	General population	inhalation	Long term exposure - systemic effects		608 mg/m3	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	General population	oral	Long term exposure - systemic effects		699 mg/kg	
Xylene - mixture of isomers 1330-20-7	Workers	inhalation	Long term exposure - systemic effects		221 mg/m3	
Xylene - mixture of isomers 1330-20-7	Workers	inhalation	Acute/short term exposure - systemic effects		442 mg/m3	
Xylene - mixture of isomers 1330-20-7	Workers	inhalation	Long term exposure - local effects		221 mg/m3	
Xylene - mixture of isomers 1330-20-7	Workers	inhalation	Acute/short term exposure - local effects		442 mg/m3	
Xylene - mixture of isomers 1330-20-7	Workers	dermal	Long term exposure - systemic effects		212 mg/kg	
Xylene - mixture of isomers 1330-20-7	General population	inhalation	Long term exposure - systemic effects		65,3 mg/m3	
Xylene - mixture of isomers 1330-20-7	General population	inhalation	Acute/short term exposure - systemic effects		260 mg/m3	
Xylene - mixture of isomers 1330-20-7	General population	inhalation	Long term exposure - local effects		65,3 mg/m3	
Xylene - mixture of isomers 1330-20-7	General population	inhalation	Acute/short term exposure - local effects		260 mg/m3	
Xylene - mixture of isomers 1330-20-7	General population	dermal	Long term exposure - systemic effects		125 mg/kg	
Xylene - mixture of isomers 1330-20-7	General population	oral	Long term exposure - systemic effects		12,5 mg/kg	
cyclohexane 110-82-7	Workers	inhalation	Acute/short term exposure - local effects		700 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	Workers	inhalation	Acute/short term exposure - systemic effects		700 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	Workers	inhalation	Long term exposure - systemic effects		700 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	Workers	inhalation	Long term exposure - local effects		700 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	Workers	dermal	Long term exposure - systemic effects		2016 mg/kg	no potential for bioaccumulation
cyclohexane 110-82-7	General population	inhalation	Acute/short term exposure - systemic effects		412 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	General population	inhalation	Acute/short term exposure - local effects		412 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	General population	dermal	Long term exposure -		1186 mg/kg	no potential for bioaccumulation

			systemic effects			
cyclohexane 110-82-7	General population	oral	Long term exposure - systemic effects		59,4 mg/kg	no potential for bioaccumulation
cyclohexane 110-82-7	General population	inhalation	Long term exposure - systemic effects		206 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	General population	inhalation	Long term exposure - local effects		206 mg/m3	no potential for bioaccumulation
ethylbenzene 100-41-4	Workers	inhalation	Acute/short term exposure - local effects		293 mg/m3	
ethylbenzene 100-41-4	General population	inhalation	Long term exposure - systemic effects		15 mg/m3	
ethylbenzene 100-41-4	General population	oral	Long term exposure - systemic effects		1,6 mg/kg	
ethylbenzene 100-41-4	Workers	dermal	Long term exposure - systemic effects		180 mg/kg	
ethylbenzene 100-41-4	Workers	inhalation	Long term exposure - systemic effects		77 mg/m3	
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	Workers	inhalation	Long term exposure - systemic effects		1,41 mg/m3	
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	Workers	dermal	Long term exposure - systemic effects		3,5 mg/kg	
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	General population	inhalation	Long term exposure - systemic effects		0,348 mg/m3	
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	General population	dermal	Long term exposure - systemic effects		0,42 mg/kg	
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	General population	oral	Long term exposure - systemic effects		0,2 mg/kg	
n-Hexane 110-54-3	General population	inhalation	Long term exposure - systemic effects		16 mg/m3	
n-Hexane 110-54-3	Workers	dermal	Long term exposure - systemic effects		11 mg/kg	
n-Hexane 110-54-3	General population	dermal	Long term exposure - systemic effects		5,3 mg/kg	
n-Hexane 110-54-3	Workers	inhalation	Long term exposure - systemic effects		75 mg/m3	
n-Hexane 110-54-3	General population	oral	Long term exposure - systemic effects		4 mg/kg	
zinc oxide 1314-13-2	Workers	Inhalation	Long term exposure - systemic effects		5 mg/m3	no hazard identified
zinc oxide 1314-13-2	Workers	dermal	Long term exposure - systemic effects		83 mg/kg	no hazard identified
zinc oxide 1314-13-2	Workers	inhalation	Long term exposure - local effects		0,5 mg/m3	no hazard identified
zinc oxide 1314-13-2	General population	Inhalation	Long term exposure - systemic effects		2,5 mg/m3	no hazard identified
zinc oxide 1314-13-2	General population	dermal	Long term exposure - systemic effects		83 mg/kg	no hazard identified
zinc oxide 1314-13-2	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	no hazard identified

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Xylene 1330-20-7	Methylhippuric (toluric) acid (all isomers)	Urine	Sampling time: End of shift.	2.000 mg/l	DE BGW		
Cyclohexane 110-82-7	1,2-Cyclohexane diol, with hydrolysis	Creatinine in urine	Sampling time period is for long-term exposures, at the end of the shift after several preceding ones./ Sampling time period is at end of exposure or at end of shift.	150 mg/g	DE BGW		
Ethylbenzene 100-41-4	Mandelic acid plus phenylglyoxylic acid ethylbenzene	Creatinine in urine	Sampling time: End of shift.	800 mg/g	DE BAT		
Ethylbenzene 100-41-4		Blood	Sampling time: End of shift.	1 mg/l	DE BAT		
Ethylbenzene 100-41-4	Mandelic acid plus phenylglyoxylic acid	Creatinine in urine	Sampling time: End of shift.	250 mg/g	DE BGW		
n-Hexane 110-54-3	Hexane-2,5-dione plus 4,5-Dihydroxy-2-hexanone	Urine	Sampling time: End of shift.	5 mg/l	DE BAT		
n-Hexane 110-54-3	Hexane-2,5-dione plus 4,5-Dihydroxy-2-hexanone (with hydrolysis)	Urine	Sampling time: End of shift.	5 mg/l	DE BGW		

8.2. Exposure controls:**Engineering controls:**

Use only in well ventilated areas.

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Fluorinated rubber (FKM; ≥ 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Fluorinated rubber (FKM; ≥ 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Delivery form	liquid
Colour	beige
Odor	aromatic
Melting point	Currently under determination
Initial boiling point	81 - 89 °C (177.8 - 192.2 °F)
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	11,1 °C (51.98 °F)
Auto-ignition temperature	Currently under determination
Decomposition temperature	Currently under determination
pH	Product is non-soluble (in water).
Viscosity (kinematic)	Currently under determination
Solubility (qualitative)	Currently under determination
Partition coefficient: n-octanol/water	Currently under determination
Vapour pressure (50 °C (122 °F))	290 mbar
Density (20 °C (68 °F))	1,22 - 1,26 g/ml Dichte Pyknometer; HT-Methode; Henkel Iberica NS-06
Relative vapour density:	Currently under determination
Particle characteristics	Currently under determination

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Oxidizers.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Heat, flames, sparks and other sources of ignition.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Xylene - mixture of isomeres 1330-20-7	LD50	3.523 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))
cyclohexane 110-82-7	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
ethylbenzene 100-41-4	LD50	3.500 mg/kg	rat	not specified
Hydrocarbons, C9-unsatd., polyimd. 71302-83-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
n-Hexane 110-54-3	LD50	16.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
zinc oxide 1314-13-2	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Xylene - mixture of isomeres 1330-20-7	LD50	12.126 mg/kg	rabbit	not specified
cyclohexane 110-82-7	LD50	> 2.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
ethylbenzene 100-41-4	LD50	15.433 mg/kg	rabbit	not specified
Hydrocarbons, C9-unsatd., polyimd. 71302-83-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
n-Hexane 110-54-3	LD50	> 2.000 mg/kg	rabbit	not specified
zinc oxide 1314-13-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	LC50	> 25,2 mg/l	vapour	4 h	rat	not specified
Xylene - mixture of isomeres 1330-20-7	LC50	11 mg/l	vapour	4 h	rat	not specified
cyclohexane 110-82-7	LC50	> 32,880 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
ethylbenzene 100-41-4	LC50	17,2 mg/l	vapour	4 h	rat	not specified
Hydrocarbons, C9-unsatd., polyimd. 71302-83-5	LC50	> 5,14 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
n-Hexane 110-54-3	LC50	> 31,86 mg/l	vapour	4 h	rat	not specified
zinc oxide 1314-13-2	LC50	> 5,7 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	moderately irritating		rabbit	not specified
ethylbenzene 100-41-4	moderately irritating	24 h	rabbit	not specified
n-Hexane 110-54-3	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
zinc oxide 1314-13-2	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
cyclohexane 110-82-7	slightly irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
ethylbenzene 100-41-4	slightly irritating		rabbit	not specified
n-Hexane 110-54-3	not irritating		rabbit	not specified
zinc oxide 1314-13-2	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Xylene - mixture of isomeres 1330-20-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
cyclohexane 110-82-7	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
n-Hexane 110-54-3	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
zinc oxide 1314-13-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Xylene - mixture of isomeres 1330-20-7	negative	in vitro mammalian chromosome aberration test	with and without		EU Method B.10 (Mutagenicity)
Xylene - mixture of isomeres 1330-20-7	negative	sister chromatid exchange assay in mammalian cells	with and without		EU Method B.19 (Sister Chromatid Exchange Assay In Vitro)
cyclohexane 110-82-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
cyclohexane 110-82-7	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
ethylbenzene 100-41-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
ethylbenzene 100-41-4	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
ethylbenzene 100-41-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
ethylbenzene 100-41-4	negative	sister chromatid exchange assay in mammalian cells	with and without		not specified
n-Hexane 110-54-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
n-Hexane 110-54-3	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
zinc oxide 1314-13-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
zinc oxide 1314-13-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
zinc oxide 1314-13-2	ambiguous	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Xylene - mixture of isomeres 1330-20-7	negative	intraperitoneal		rat	OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)
cyclohexane 110-82-7	negative	inhalation: vapour		rat	equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
ethylbenzene 100-41-4	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
ethylbenzene 100-41-4	negative	inhalation		mouse	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
n-Hexane 110-54-3	negative	inhalation: vapour		mouse	not specified
n-Hexane 110-54-3	negative	inhalation: vapour		rat	not specified
zinc oxide 1314-13-2	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Xylene - mixture of isomeres 1330-20-7	not carcinogenic	oral: gavage	103 w 5 d/w	rat	male/female	EU Method B.32 (Carcinogenicity Test)
ethylbenzene 100-41-4	carcinogenic	inhalation: vapour	104 w 6 h/d, 5 d/w	rat	male/female	equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
n-Hexane 110-54-3	not carcinogenic	inhalation: vapour	2 y 6 h/d; 5 d/w	mouse	female	OECD Guideline 451 (Carcinogenicity Studies)
zinc oxide 1314-13-2	not carcinogenic	oral: drinking water	1 y daily	mouse	male/female	not specified

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
cyclohexane 110-82-7	NOAEL F1 7000 ppm	two- generation study	inhalation: vapour	rat	equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
ethylbenzene 100-41-4	NOAEL P 1000 ppm NOAEL F1 100 ppm	One generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 415 (One- Generation Reproduction Toxicity Study)
ethylbenzene 100-41-4	NOAEL P 500 ppm NOAEL F1 500 ppm NOAEL F2 500 ppm	Two generation study	inhalation	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
n-Hexane 110-54-3	NOAEL P 9000 ppm NOAEL F1 3000 ppm NOAEL F2 3000 ppm	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
zinc oxide 1314-13-2	NOAEL P 7,5 mg/kg NOAEL F1 15 mg/kg	Two generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Xylene - mixture of isomeres 1330-20-7	NOAEL 150 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
cyclohexane 110-82-7		inhalation: vapour	13-14 w 6 h/d, 5 d/w	mouse	EPA OPPTS 870.3465 (90-Day Inhalation Toxicity)
ethylbenzene 100-41-4	NOAEL 75 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
n-Hexane 110-54-3	NOAEL 568 mg/kg	oral: gavage	90 d 5 d/w	rat	not specified
n-Hexane 110-54-3	NOAEL 500 ppm	inhalation: vapour	90 d 6 h/d; 5 d/w	mouse	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
zinc oxide 1314-13-2	NOAEL 31,52 mg/kg	oral: feed	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
zinc oxide 1314-13-2	NOAEL 1.5 mg/m ³	inhalation	3 m 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane	0,61 mm ² /s	25 °C	not specified	
cyclohexane 110-82-7	0,41 mm ² /s	40 °C	not specified	
ethylbenzene 100-41-4	0,641 mm ² /s	40 °C	OECD Test Guideline 114	
n-Hexane 110-54-3	0,45 mm ² /s	25 °C	not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	LL50	11,4 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Xylene - mixture of isomeres 1330-20-7	LC50	2,6 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Xylene - mixture of isomeres 1330-20-7	NOEC	> 1,3 mg/l	56 d	Oncorhynchus mykiss	other guideline:
cyclohexane 110-82-7	LC50	4,53 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
ethylbenzene 100-41-4	LC50	4,2 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	LL50	25,8 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
n-Hexane 110-54-3	LC50	> 1 - 10 mg/l	96 h	not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)
zinc oxide 1314-13-2	LC50	0,142 mg/l	96 h	Thymallus arcticus	OECD Guideline 203 (Fish, Acute Toxicity Test)
zinc oxide 1314-13-2	NOEC	0,44 mg/l	72 d	Oncorhynchus mykiss	other guideline:

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EL50	3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Xylene - mixture of isomeres 1330-20-7	EC50	3,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
cyclohexane 110-82-7	EC50	0,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
ethylbenzene 100-41-4	EC50	> 1,8 - 2,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	EL50	54 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
n-Hexane 110-54-3	EC50	2,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
zinc oxide 1314-13-2	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	NOEC	0,17 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Xylene - mixture of isomers 1330-20-7	NOEC	0,96 mg/l	7 d	Ceriodaphnia dubia	other guideline:
ethylbenzene 100-41-4	NOEC	0,96 mg/l	7 d	Ceriodaphnia dubia	OECD 211 (Daphnia magna, Reproduction Test)
zinc oxide 1314-13-2	NOEC	0,058 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EL50	> 30 - 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	NOELR	3 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Xylene - mixture of isomers 1330-20-7	EC50	4,36 mg/l	73 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Xylene - mixture of isomers 1330-20-7	EC10	1,9 mg/l	73 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
cyclohexane 110-82-7	EC50	9,317 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
cyclohexane 110-82-7	NOEC	0,95 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
ethylbenzene 100-41-4	EC50	7,7 mg/l	96 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
ethylbenzene 100-41-4	NOEC	4,5 mg/l	96 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	EL50	> 100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	NOELR	100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
n-Hexane 110-54-3	EC50	> 1 - 10 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
zinc oxide 1314-13-2	NOEC	0,017 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
zinc oxide 1314-13-2	EC50	0,17 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
cyclohexane 110-82-7	IC50	29 mg/l	15 h	other:	not specified
ethylbenzene 100-41-4	EC50	> 152 mg/l	30 min	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	EC50	> 100 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
n-Hexane 110-54-3	EC50	> 1 - 10 mg/l	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
zinc oxide 1314-13-2	IC50	5,2 mg/l	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Xylene - mixture of isomeres 1330-20-7	readily biodegradable	aerobic	90 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
cyclohexane 110-82-7	readily biodegradable	aerobic	77 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
ethylbenzene 100-41-4	readily biodegradable	aerobic	69 %	33 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 310 (Ready Biodegradability CO ₂ in Sealed Vessels (Headspace Test))
n-Hexane 110-54-3	readily biodegradable	aerobic	81 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Xylene - mixture of isomeres 1330-20-7	25,9	56 d		Oncorhynchus mykiss	not specified
cyclohexane 110-82-7	167			Pimephales promelas	QSAR (Quantitative Structure Activity Relationship)
ethylbenzene 100-41-4	1	42 d	10 °C	Oncorhynchus kisutch	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Xylene - mixture of isomers 1330-20-7	3,16	20 °C	not specified
cyclohexane 110-82-7	3,44	25 °C	QSAR (Quantitative Structure Activity Relationship)
ethylbenzene 100-41-4	3,6	20 °C	EU Method A.8 (Partition Coefficient)
n-Hexane 110-54-3	4	20 °C	other guideline:

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Xylene - mixture of isomers 1330-20-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
cyclohexane 110-82-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
ethylbenzene 100-41-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
n-Hexane 110-54-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
zinc oxide 1314-13-2	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

SECTION 14: Transport information

14.1. UN number

ADR	1139
RID	1139
ADN	1139
IMDG	1139
IATA	1139

14.2. UN proper shipping name

ADR	COATING SOLUTION
RID	COATING SOLUTION
ADN	COATING SOLUTION
IMDG	COATING SOLUTION (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)
IATA	Coating solution

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	Special provision 640D Tunnelcode: (D/E)
RID	Special provision 640D
ADN	Special provision 640D
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	37,5 %

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

National regulations/information (Germany):

WGK:

WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV))
Classification according to AwSV, Annex 1 (5.2)

BG regulations, rules, infos:

BG data sheet: BGI 621 Solvents

Storage class according to TRGS 510: 3

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H361f Suspected of damaging fertility.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.