



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 21

TEROSON WX 980 UBC AE

SDS No. : 490354

V010.0

Revision: 05.02.2024

printing date: 08.02.2024

Replaces version from: 21.06.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TEROSON WX 980 UBC AE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Underbody coating

#### 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSInfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Flammable aerosols

Category 1

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure

Category 3

H336 May cause drowsiness or dizziness.

Target organ: Central nervous system

Chronic hazards to the aquatic environment

Category 3

H412 Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Label elements (CLP):

**Hazard pictogram:**



**Contains**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Sulfonic acids, petroleum, calcium salts

**Signal word:**

Danger

**Hazard statement:**

H222 Extremely flammable aerosol.  
H229 Pressurized container: May burst if heated.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

**Supplemental information**

EUH066 Repeated exposure may cause skin dryness or cracking.

**Precautionary statement:  
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P280 Wear protective gloves.  
P273 Avoid release to the environment.

**Precautionary statement:  
Storage**

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50.DEGREE.C/122.DEGREE.F.

### 2.3. Other hazards

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.  
The solvent vapors are heavier than air and may collect in high concentrations at floor level.  
The aerosol container is under pressure. Do not expose to high temperatures.

**Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):**

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9 01-2119463258-33	20- 40 %	Asp. Tox. 1, H304 Flam. Liq. 3, H226 STOT SE 3, H336		
Butane, n- (<0.1 % butadiene) 106-97-8 203-448-7 01-2119474691-32	10- 20 %	Press. Gas H280 Flam. Gas 1A, H220		
Propane 74-98-6 200-827-9 01-2119486944-21	10- 20 %	Flam. Gas 1A, H220 Press. Gas H280		
Sulfonic acids, petroleum, calcium salts 61789-86-4 263-093-9 01-2119488992-18	1- < 3 %	Skin Sens. 1B, H317		
Nonane 111-84-2 203-913-4	1- < 3 %	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
Isobutane 75-28-5 200-857-2 01-2119485395-27	1- < 3 %	Flam. Gas 1A, H220 Press. Gas Liquef. Gas, H280		
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5 265-091-3 01-2119487067-30	1- < 3 %	Asp. Tox. 1, H304		
zinc oxide 1314-13-2 215-222-5 01-2119463881-32	0,1- < 0,25 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

The hazard classification of this product is based solely on the mixture present within the aerosol, excluding the propellant gases. The information provided in Section 3 is based on the combination of the mixture and propellant gases.

**SECTION 4: First aid measures****4.1. Description of first aid measures**

Inhalation:

Move to fresh air, consult doctor if complaint persists.

**Skin contact:**

IF ON SKIN: Wash with plenty of soap and water.  
In case of adverse health effects seek medical advice.

**Eye contact:**

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

**Ingestion:**

not relevant.

**4.2. Most important symptoms and effects, both acute and delayed**

SKIN: Rash, Urticaria.

Vapors may cause drowsiness and dizziness.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

## SECTION 5: Firefighting measures

**5.1. Extinguishing media**

**Suitable extinguishing media:**

Carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

Water jet (solvent-containing product).

**5.2. Special hazards arising from the substance or mixture**

In case of fire toxic gases can be released.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus.

Wear protective equipment.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

Danger of slipping on spilled product.

**6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

Inform authorities in the event of product spillage to water courses or sewage systems.

**6.3. Methods and material for containment and cleaning up**

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

**6.4. Reference to other sections**

See advice in section 8

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**

Ground/bond container and receiving equipment.  
Use explosion proof electric equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid open flames and sources of ignition.

Hygiene measures:

Wash hands before work breaks and after finishing work.  
Do not eat, drink or smoke while working.

**7.2. Conditions for safe storage, including any incompatibilities**

Ensure good ventilation/extraction.  
Store in a cool, frost-free place.  
Protect from direct sunlight.  
Storage at 5 to 25°C is recommended.

**7.3. Specific end use(s)**

Underbody coating

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational Exposure Limits**Valid for  
Germany

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Butane 106-97-8	1.000	2.400	Exposure limit(s):	4	TRGS 900
Butane 106-97-8			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Propane 74-98-6	1.000	1.800	Exposure limit(s):	4	TRGS 900
Propane 74-98-6			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Sulfonic acids, petroleum, calcium salts 61789-86-4		5	Exposure limit(s):	4	TRGS 900
Sulfonic acids, petroleum, calcium salts 61789-86-4			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Nonane 111-84-2		600	Exposure limit(s):	2	TRGS 900
Nonane 111-84-2			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Calcium carbonate 471-34-1		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Calcium carbonate 471-34-1		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Calcium carbonate 471-34-1			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Isobutane 75-28-5			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Isobutane 75-28-5	1.000	2.400	Exposure limit(s):	4	TRGS 900
Zinc oxide 1314-13-2		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Zinc oxide 1314-13-2		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Zinc oxide 1314-13-2			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Sulfonic acids, petroleum, calcium salts 61789-86-4	aqua (freshwater)		1,00 mg/l				
Sulfonic acids, petroleum, calcium salts 61789-86-4	aqua (marine water)		1,0 mg/l				
Sulfonic acids, petroleum, calcium salts 61789-86-4	sewage treatment plant (STP)		1000,00 mg/l				
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	oral				9,33 mg/kg		
zinc oxide 1314-13-2	aqua (freshwater)		14,4 µg/l				
zinc oxide 1314-13-2	aqua (marine water)		7,2 µg/l				
zinc oxide 1314-13-2	sewage treatment plant (STP)		100 µg/l				
zinc oxide 1314-13-2	sediment (freshwater)				146,9 mg/kg		
zinc oxide 1314-13-2	sediment (marine water)				162,2 mg/kg		
zinc oxide 1314-13-2	Soil				83,1 mg/kg		

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	Workers	dermal	Long term exposure - systemic effects		300 mg/kg	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	Workers	Inhalation	Long term exposure - systemic effects		1500 mg/m3	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	General population	dermal	Long term exposure - systemic effects		300 mg/kg	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	General population	Inhalation	Long term exposure - systemic effects		900 mg/m3	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	General population	oral	Long term exposure - systemic effects		300 mg/kg	
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	Workers	inhalation	Long term exposure - local effects		5,58 mg/m3	
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	General population	inhalation	Long term exposure - local effects		1,2 mg/m3	
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	Workers	inhalation	Long term exposure - systemic effects		5,4 mg/m3	

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

Engineering controls:

In case of aerosol forming ensure sufficient suction and ventilation.

**Respiratory protection:**

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

**Hand protection:**

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR;  $\geq 0.7$  mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR;  $\geq 0.7$  mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

**Skin protection:**

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Advices to personal protection equipment:**

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Delivery form	aerosol
Colour	black
Odor	hydrocarbons
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	< -50 °C (< -58 °F)
Initial boiling point (1.013 hPa)	150 °C (302 °F)no method / method unknown
Flammability	Flammable liquid
Explosive limits	
lower	1,62 %(V); Upper explosion limit not applicable for safe processing practices.
Flash point	36 °C (96.8 °F)
Auto-ignition temperature	> 237 °C (> 458.6 °F)
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic) (40 °C (104 °F); )	37 mm <sup>2</sup> /s
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Not miscible
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure (20 °C (68 °F))	Mixture 960 Pa
Vapour pressure (50 °C (122 °F))	4900 Pa
Density (20 °C (68 °F))	0,85 g/cm <sup>3</sup> no method / method unknown
Relative vapour density:	1,16



(20 °C)  
Particle characteristics

Not applicable  
Product is a liquid

## 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

Aerosols:

Classified as Aerosol category 1 because it contains more than 1 % (by mass) flammable components or has a heat of combustion of at least 20 kJ/g and is not submitted to the flammability classification procedures

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Oxidizers.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Heat, flames, sparks and other sources of ignition.  
Temperatures over appr. 50 °C

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

No decomposition if used according to specifications.

## SECTION 11: Toxicological information

### General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Sulfonic acids, petroleum, calcium salts 61789-86-4	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Nonane 111-84-2	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
zinc oxide 1314-13-2	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	LD50	> 5.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Sulfonic acids, petroleum, calcium salts 61789-86-4	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Nonane 111-84-2	LD50	> 2.000 mg/kg	rabbit	not specified
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
zinc oxide 1314-13-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	LC50	> 5,6 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	LC50	> 9,3 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	274200 ppm	gas	4 h	rat	not specified
Propane 74-98-6	LC50	> 800000 ppm	gas	15 min	rat	not specified
Isobutane 75-28-5	LC50	260200 ppm	gas	4 h	mouse	not specified
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	LC50	> 5,53 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
zinc oxide 1314-13-2	LC50	> 5,7 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	mildly irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Sulfonic acids, petroleum, calcium salts 61789-86-4	not irritating	4 h	rabbit	EPA OPPTS 870.2500 (Acute Dermal Irritation)
Nonane 111-84-2	irritating		rabbit	Weight of evidence
zinc oxide 1314-13-2	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Sulfonic acids, petroleum, calcium salts 61789-86-4	not irritating		rabbit	EPA OPPTS 870.2400 (Acute Eye Irritation)
zinc oxide 1314-13-2	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Sulfonic acids, petroleum, calcium salts 61789-86-4	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
zinc oxide 1314-13-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Propane 74-98-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propane 74-98-6	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isobutane 75-28-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isobutane 75-28-5	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
zinc oxide 1314-13-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
zinc oxide 1314-13-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
zinc oxide 1314-13-2	ambiguous	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	inhalation: gas		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Propane 74-98-6	negative			Drosophila melanogaster	not specified
Propane 74-98-6	negative	inhalation: gas		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isobutane 75-28-5	negative	oral: feed		Drosophila melanogaster	not specified
Isobutane 75-28-5	negative	inhalation: gas		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
zinc oxide 1314-13-2	negative	inhalation: aerosol		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
zinc oxide 1314-13-2	negative	inhalation: aerosol		rat	OECD Guideline 489 (In Vivo Mammalian Alkaline Comet Assay)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
zinc oxide 1314-13-2	not carcinogenic	oral: drinking water	1 y daily	mouse	male/female	not specified

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	NOAEL P 21,4 mg/l NOAEL F1 21,4 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Propane 74-98-6	NOAEL P 21,6 mg/l NOAEL F1 21,6 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Isobutane 75-28-5	NOAEL P 21,4 mg/l NOAEL F1 21,4 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
zinc oxide 1314-13-2	NOAEL P 7,5 mg/kg NOAEL F1 15 mg/kg	Two generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

**STOT-single exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
Nonane 111-84-2	Category 3 with narcotic effects.			

**STOT-repeated exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8		inhalation: gas	28 d 6 h/d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Propane 74-98-6		inhalation: gas	28 d 6 h/d, 7 d/w	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	NOAEL 1.000 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Isobutane 75-28-5	NOAEL 9000 ppm	inhalation: gas	28 d 6 h/d, 7 d/w	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
zinc oxide 1314-13-2	NOAEL 31,52 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
zinc oxide 1314-13-2	NOAEL 1.5 mg/m <sup>3</sup>	inhalation	3 m 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
zinc oxide 1314-13-2	NOAEL 1.000 mg/kg	dermal	90 d 6 h/d, daily	rat	OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

**Aspiration hazard:**

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	1,02 mm <sup>2</sup> /s	40 °C	calculated	
Distillates (petroleum), solvent-refined light paraffinic, < 3% DMSO 64741-89-5	11 mm <sup>2</sup> /s	40 °C		

**11.2 Information on other hazards**

not applicable

**SECTION 12: Ecological information****General ecological information:**

Do not empty into drains, soil or bodies of water.

**12.1. Toxicity****Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	LL50	Toxicity > Water solubility	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	27,98 mg/l	96 h		not specified
Sulfonic acids, petroleum, calcium salts 61789-86-4	LL50	> 1.000 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	LC50	> 1.000 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
zinc oxide 1314-13-2	LC50	0,142 mg/l	96 h	Thymallus arcticus	OECD Guideline 203 (Fish, Acute Toxicity Test)
zinc oxide 1314-13-2	NOEC	0,44 mg/l	72 d	Oncorhynchus mykiss	other guideline:

**Toxicity (aquatic invertebrates):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	EL50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	14,22 mg/l	48 h		not specified
Sulfonic acids, petroleum, calcium salts 61789-86-4	EC50	> 1.000 mg/l	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
Nonane 111-84-2	EC50	0,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	EC50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
zinc oxide 1314-13-2	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

**Chronic toxicity (aquatic invertebrates):**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
----------------------	-------	-------	---------------	---------	--------

CAS-No.	type				
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	NOEC	1.000 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
zinc oxide 1314-13-2	NOEC	0,058 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

**Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	EL50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	NOELR	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	7,71 mg/l	96 h		not specified
Sulfonic acids, petroleum, calcium salts 61789-86-4	NOELR	100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	EL50	> 100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	NOELR	100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
zinc oxide 1314-13-2	NOEC	0,017 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
zinc oxide 1314-13-2	EC50	0,17 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

**Toxicity (microorganisms):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Sulfonic acids, petroleum, calcium salts 61789-86-4	EC50	> 10.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
zinc oxide 1314-13-2	IC50	5,2 mg/l	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

**12.2. Persistence and degradability**



The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	readily biodegradable	aerobic	80 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	readily biodegradable	aerobic	> 60 %	28 d	OECD 301 A - F
Propane 74-98-6	readily biodegradable	aerobic	> 60 %	28 d	OECD 301 A - F
Sulfonic acids, petroleum, calcium salts 61789-86-4	not readily biodegradable.	aerobic	8 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Nonane 111-84-2	readily biodegradable	aerobic	100 %	25 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Isobutane 75-28-5	readily biodegradable	aerobic	71,43 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	not readily biodegradable.	aerobic	22 - 29 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	2,31	20 °C	other (measured)
Sulfonic acids, petroleum, calcium salts 61789-86-4	22,12	25 °C	QSAR (Quantitative Structure Activity Relationship)
Nonane 111-84-2	5,65		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Isobutane 75-28-5	2,88	20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

#### 12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Butane, n- (< 0.1 % butadiene) 106-97-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Propane 74-98-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Sulfonic acids, petroleum, calcium salts 61789-86-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Nonane 111-84-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Isobutane 75-28-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
zinc oxide 1314-13-2	According to Annex XIII to Regulation (EC) No 1907/2006, a PBT and vPvB assessment shall not be conducted for inorganic substances.

#### 12.6. Endocrine disrupting properties

not applicable

#### 12.7. Other adverse effects

No data available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

## SECTION 14: Transport information

### 14.1. UN number or ID number

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

### 14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS
IATA	Aerosols, flammable

### 14.3. Transport hazard class(es)

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

### 14.4. Packing group

ADR	
RID	
ADN	
IMDG	
IATA	

### 14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

### 14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	62,9 %

### VOC Paints and Varnishes (EU):

Regulatory Basis:	Directive 2004/42/EC
Product (sub)category:	B(e) Special finishes
Phase I (from 1.1.2007):	840 g/l
max. VOC content:	523,6 g/l

### 15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

### National regulations/information (Germany):

WGK:	WGK 1: slightly hazardous to water (Ordinance on facilities for handling substances that are hazardous to water (AwSV) ) Classification according to AwSV, Annex 1 (5.2)
------	---

BG regulations, rules, infos:

	BG data sheet: BGI 621 Solvents
Storage class according to TRGS 510:	2B

## SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H220 Extremely flammable gas.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

### Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,  
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**