

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 19

LOCTITE SI 5616 B known as Loctite SI 5616 B

SDS No. : 312315 V004.0 Revision: 07.03.2024 printing date: 11.03.2024 Replaces version from: 28.06.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier
 - LOCTITE SI 5616 B known as Loctite SI 5616 B
- **1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use: Silicone sealant
- **1.3. Details of the supplier of the safety data sheet** Henkel AG & Co. KGaA

Henkelstr. 67 40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP): Serious eye irritation

H319 Causes serious eye irritation.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Warning

Hazard statement:

H319 Causes serious eye irritation.

Category 2

Precautionary statement: P337+P313 If eye irritation persists: Get medical advice/attention. **Response**

2.3. Other hazards

None if used properly. Self-classification according to Article 12(b) of (EU) 1272/2008.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

octamethylcyclotetrasiloxane PBT/vPvB 556-67-2

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Trimethoxy(methyl)silane 1185-55-3 214-685-0 01-2119517436-40	1-< 5%	Flam. Liq. 2, H225		
3-(Trimethoxysilyl)propylamine 13822-56-5 237-511-5 01-2119510159-45	1- < 3 %	Skin Irrit. 2, Dermal, H315 Eye Dam. 1, H318		
Hexamethyldisiloxane 107-46-0 203-492-7 01-2119496108-31	0,1- < 1 %	Flam. Liq. 2, H225 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	M acute = 1	
Hexamethyldisilizane 999-97-3 213-668-5 01-2119438176-38	0,1- < 1 %	Flam. Liq. 2, H225 Acute Tox. 4, Oral, H302 Acute Tox. 3, Dermal, H311 Acute Tox. 4, Inhalation, H332 Aquatic Chronic 3, H412	inhalation:ATE = 10,1 mg/l;vapour	
octamethylcyclotetrasiloxane 556-67-2 209-136-7 01-2119529238-36	0,01-< 0,1 %	Aquatic Chronic 1, H410 Repr. 2, H361f Flam. Liq. 3, H226	M chronic = 10	SVHC PBT/vPvB

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice. Skin contact: Rinse with running water and soap. Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

Prolonged or repeated contact may cause skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media Suitable extinguishing media: water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons: High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released. Silicon dioxide

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Wear protective equipment. Ensure adequate ventilation. Avoid dust formation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13. Scrape up as much material as possible. Sweep up spilled material. Avoid creating dust. Store in a partly filled, closed container until disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact. See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed. Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction. Refer to Technical Data Sheet.

7.3. Specific end use(s) Silicone sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Limestone 1317-65-3		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Limestone			Short Term Exposure	Category II: substances with a	TRGS 900
1317-65-3			Classification:	resorptive effect.	

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
	Compartment	periou	mg/l	ppm	mg/kg	others	
Trimethoxy(methyl)silane 1185-55-3	aqua (freshwater)		1,3 mg/l	PP			
Trimethoxy(methyl)silane 1185-55-3	aqua (marine water)		0,13 mg/l				
Trimethoxy(methyl)silane 1185-55-3	sewage treatment plant		6,9 mg/l				
Trimethoxy(methyl)silane	(STP) sediment				4,8 mg/kg		
1185-55-3 Trimethoxy(methyl)silane	(freshwater) sediment				0,48 mg/kg		
1185-55-3 Trimethoxy(methyl)silane	(marine water) Soil				0,19 mg/kg		
1185-55-3 Trimethoxy(methyl)silane	sediment				0,73 mg/kg		
1185-55-3	(freshwater)						
Trimethoxy(methyl)silane 1185-55-3	sediment (marine water)				0,073 mg/kg		
Trimethoxy(methyl)silane 1185-55-3	Soil				0,03 mg/kg		
3-(Trimethoxysilyl)propylamine 13822-56-5	aqua (freshwater)		0,5 mg/l				
3-(Trimethoxysilyl)propylamine 13822-56-5	aqua (marine water)		0,05 mg/l				
3-(Trimethoxysilyl)propylamine 13822-56-5	oral				11,1 mg/kg		
3-(Trimethoxysilyl)propylamine 13822-56-5	sediment (freshwater)				1,8 mg/kg		
3-(Trimethoxysilyl)propylamine 13822-56-5	sediment (marine water)				0,18 mg/kg		
3-(Trimethoxysilyl)propylamine 13822-56-5	Soil				0,069 mg/kg		
3-(Trimethoxysilyl)propylamine 13822-56-5	Sewage treatment plant		0,81 mg/l				
3-(Trimethoxysilyl)propylamine 13822-56-5	Freshwater - intermittent		2,05 mg/l				
Hexamethyldisiloxane 107-46-0	aqua (freshwater)		0,002 mg/l				
Hexamethyldisiloxane 107-46-0	aqua (marine water)		0 mg/l				
Hexamethyldisiloxane 107-46-0	sediment (freshwater)				8,9 mg/kg		
Hexamethyldisiloxane 107-46-0	sediment (marine water)				0,89 mg/kg		
Hexamethyldisiloxane 107-46-0	Soil				0,083 mg/kg		
Hexamethyldisiloxane 107-46-0	Sewage treatment plant		10 mg/l		mg/Kg		
Hexamethyldisiloxane 107-46-0	Freshwater - intermittent		0,003 mg/l				
Hexamethyldisiloxane 107-46-0	oral				5,3 mg/kg		
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	sediment (freshwater)				2 mg/kg		
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	sediment (marine water)			1	0,2 mg/kg		
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Soil				0,25 mg/kg		
Octamethylcyclotetrasiloxane 556-67-2	aqua (freshwater)		0,0015 mg/l				
Octamethylcyclotetrasiloxane	aqua (marine		0,00015				
556-67-2 Octamethylcyclotetrasiloxane	water) sewage		mg/l 10 mg/l				
556-67-2	treatment plant (STP)						
Octamethylcyclotetrasiloxane 556-67-2	sediment (freshwater)				3 mg/kg		

Octamethylcyclotetrasiloxane 556-67-2	sediment (marine water)		0,3 mg/kg	
Octamethylcyclotetrasiloxane 556-67-2	oral		41 mg/kg	
Octamethylcyclotetrasiloxane 556-67-2	Soil		0,84 mg/kg	

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Trimethoxy(methyl)silane 1185-55-3	Workers	inhalation	Long term exposure - systemic effects		25,6 mg/m3	
Trimethoxy(methyl)silane 1185-55-3	Workers	dermal	Long term exposure - systemic effects		3,6 mg/kg	
Trimethoxy(methyl)silane 1185-55-3	General population	inhalation	Long term exposure - systemic effects		6,25 mg/m3	
Trimethoxy(methyl)silane 1185-55-3	General population	oral	Long term exposure - systemic effects		0,26 mg/kg	
Trimethoxy(methyl)silane 1185-55-3	General population	dermal	Long term exposure - systemic effects		7,2 mg/kg	
3-(Trimethoxysilyl)propylamine 13822-56-5	Workers	inhalation	Long term exposure - systemic effects		7,1 mg/m3	
3-(Trimethoxysilyl)propylamine 13822-56-5	Workers	dermal	Long term exposure - systemic effects		1 mg/kg	
3-(Trimethoxysilyl)propylamine 13822-56-5	General population	inhalation	Long term exposure - systemic effects		1,7 mg/m3	
3-(Trimethoxysilyl)propylamine 13822-56-5	General population	dermal	Long term exposure - systemic effects		0,5 mg/kg	
3-(Trimethoxysilyl)propylamine 13822-56-5	General population	oral	Long term exposure - systemic effects		8 mg/kg	
3-(Trimethoxysilyl)propylamine 13822-56-5	Workers	inhalation	Acute/short term exposure - systemic effects		260 mg/m3	
3-(Trimethoxysilyl)propylamine 13822-56-5	General population	inhalation	Acute/short term exposure - systemic effects		50 mg/m3	
3-(Trimethoxysilyl)propylamine 13822-56-5	Workers	inhalation	Long term exposure - systemic effects		260 mg/m3	
Hexamethyldisiloxane 107-46-0	Workers	inhalation	Long term exposure - systemic effects		53,4 mg/m3	
Hexamethyldisiloxane 107-46-0	Workers	dermal	Long term exposure - systemic effects		333 mg/kg	
Hexamethyldisiloxane 107-46-0	General population	inhalation	Long term exposure - systemic effects		13,3 mg/m3	
Hexamethyldisiloxane 107-46-0	General population	dermal	Long term exposure - systemic effects		167 mg/kg	
Hexamethyldisiloxane 107-46-0	General population	oral	Long term exposure - systemic effects		0,27 mg/kg	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	inhalation	Long term exposure - systemic effects		53 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	inhalation	Acute/short term exposure - systemic effects		53 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	inhalation	Long term exposure - local effects		133 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	inhalation	Acute/short term exposure - local effects		133 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	dermal	Long term exposure -		7,5 mg/kg	

SDS No.: 312315 V004.0

I	1	1	systemic effects	1	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	dermal	Acute/short term exposure - systemic effects	7,5 mg/kg	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	General population	inhalation	Long term exposure - systemic effects	3,7 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	General population	inhalation	Acute/short term exposure - systemic effects	3,7 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	General population	inhalation	Long term exposure - local effects	1,7 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	General population	inhalation	Acute/short term exposure - local effects	1,7 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	General population	oral	Long term exposure - systemic effects	1,1 mg/kg	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	General population	oral	Acute/short term exposure - systemic effects	1,1 mg/kg	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - systemic effects	73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - local effects	73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - systemic effects	13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - local effects	13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	oral	Long term exposure - systemic effects	3,7 mg/kg	

Biological Exposure Indices: None

8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	paste
Colour	white
Odor	alcohol-like
Physical state	solid
Melting point	< -20 °C (< -4 °F)
Solidification temperature	Not applicable, Product is a solid.
Initial boiling point	> 300 °C (> 572 °F)
Flammability	The product is not flammable.
Explosive limits	Not applicable, Product is a solid.
Flash point	> 100,00 °C ($>$ 212 °F); no method / method unknown
Auto-ignition temperature	Not applicable, Product is a solid.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic)	Not applicable, Product is a solid.
Viscosity, dynamic	10.000 - 60.000 mPa.s LCT STM 738; Rheological Data from flow
(; 25 °C (77 °F); Shear gradient: 20 s-1)	curves
Solubility (qualitative)	Reacts with water.
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	0,11 Pa
(20 °C (68 °F))	
Vapour pressure	1,7 Pa
(50 °C (122 °F))	
Density	1,6500 g/cm3 None
0	
Bulk density	1,55 - 1,75 g/cm3
Relative vapour density:	Not applicable, Product is a solid.
Particle characteristics	Not applicable
	Product is not powder.
	-
9.2. Other information	

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with oxidants, acids and lyes

10.2. Chemical stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use. Excessive heat.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Trimethoxy(methyl)silane	LD50	11.685 mg/kg	rat	not specified
1185-55-3				
3-	LD50	3.030 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
(Trimethoxysilyl)propyla				Toxicity)
mine				
13822-56-5				
Hexamethyldisiloxane	LD50	> 12.000 mg/kg	rat	not specified
107-46-0				
Hexamethyldisilizane	LD50	851 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
999-97-3				
octamethylcyclotetrasilox	LD50	>4.800 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
ane				Toxicity)
556-67-2				

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Trimethoxy(methyl)silane	LD50	> 9.500 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
1185-55-3				
3-	LD50	11.300 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute
(Trimethoxysilyl)propyla				Dermal Toxicity)
mine				
13822-56-5				
Hexamethyldisiloxane	LD50	> 2.000 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute
107-46-0				Dermal Toxicity)
Hexamethyldisilizane	LD50	547 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
999-97-3				
octamethylcyclotetrasilox	LD50	> 2.375 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute
ane				Dermal Toxicity)
556-67-2				

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	-	Species	Method
CAS-No.	type			time		
Trimethoxy(methyl)silane	LC50	> 42,1 mg/l	vapour	6 h	rat	OECD Guideline 403 (Acute
1185-55-3						Inhalation Toxicity)
Hexamethyldisiloxane	LC50	106 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
107-46-0		_				Inhalation Toxicity)
Hexamethyldisilizane	Acute	10,1 mg/l	vapour			Expert judgement
999-97-3	toxicity	-				
	estimate					
	(ATE)					
octamethylcyclotetrasilox	LC50	36 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
ane		_				Inhalation Toxicity)
556-67-2						

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Trimethoxy(methyl)silane 1185-55-3	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
3- (Trimethoxysilyl)propyla mine 13822-56-5	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hexamethyldisiloxane 107-46-0	not irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
octamethylcyclotetrasilox ane 556-67-2	not irritating		rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Trimethoxy(methyl)silane	not irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1185-55-3				
3-	corrosive		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye
(Trimethoxysilyl)propyla				Irritation / Corrosion)
mine				
13822-56-5				
Hexamethyldisiloxane	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye
107-46-0				Irritation / Corrosion)
octamethylcyclotetrasilox	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye
ane				Irritation / Corrosion)
556-67-2				

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Trimethoxy(methyl)silane 1185-55-3	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
3- (Trimethoxysilyl)propyla mine 13822-56-5	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Hexamethyldisiloxane 107-46-0	not sensitising		human	Patch Test
octamethylcyclotetrasilox ane 556-67-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Trimethoxy(methyl)silane 1185-55-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hexamethyldisiloxane 107-46-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hexamethyldisiloxane 107-46-0	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Hexamethyldisiloxane 107-46-0	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Hexamethyldisilizane 999-97-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hexamethyldisilizane 999-97-3	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
octamethylcyclotetrasilox ane 556-67-2	negative	bacterial gene mutation assay	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
octamethylcyclotetrasilox ane 556-67-2	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
octamethylcyclotetrasilox ane 556-67-2	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Hexamethyldisiloxane 107-46-0	negative	intraperitoneal		rat	equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
octamethylcyclotetrasilox ane 556-67-2	negative	inhalation		rat	equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
octamethylcyclotetrasilox ane 556-67-2	negative	oral: gavage		rat	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Test type	Route of	Species	Method
CAS-No.			application		
Hexamethyldisiloxane	NOAEL P \geq 5000 ppm	two-	inhalation:	rat	OECD Guideline 416 (Two-
107-46-0		generation	vapour		Generation Reproduction
		study			Toxicity Study)
octamethylcyclotetrasilox	NOAEL P 300 ppm	two-	inhalation	rat	equivalent or similar to
ane		generation			OECD Guideline 416 (Two-
556-67-2	NOAEL F1 300 ppm	study			Generation Reproduction
		-			Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Route of	Exposure time /	Species	Method
CAS-No.		application	Frequency of		
			treatment		
Hexamethyldisiloxane	NOAEL 160 mg/kg	oral: gavage	28 d	rat	OECD Guideline 407
107-46-0			once daily (7d/w)		(Repeated Dose 28-Day
					Oral Toxicity in Rodents)
octamethylcyclotetrasilox	LOAEL 35 ppm	inhalation	6 h nose only	rat	OECD Guideline 412
ane			inhalation		(Repeated Dose
556-67-2			5 days/week for 13		Inhalation Toxicity:
			weeks		28/14-Day)
octamethylcyclotetrasilox	NOAEL 960 mg/kg	dermal	3 w	rabbit	equivalent or similar to
ane			5 d/w		OECD Guideline 410
556-67-2					(Repeated Dose Dermal
					Toxicity: 21/28-Day
					Study)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water. Self-classification according to Article 12(b) of (EU) 1272/2008.

12.1. Toxicity

Toxicity (Fish):

LC50 (fish) > 100 mg/l (expert judgement) NOEC (fish) > 1 mg/l (expert judgement)

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
Trimethoxy(methyl)silane 1185-55-3	LC50	> 746 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
3- (Trimethoxysilyl)propylamine 13822-56-5	LC50	> 934 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hexamethyldisiloxane 107-46-0	LC50	0,46 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hexamethyldisiloxane 107-46-0	NOEC	> 0,027 mg/l	90 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early lite stage toxicity test)
Hexamethyldisilizane 999-97-3	LC50	88 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
octamethylcyclotetrasiloxane 556-67-2	NOEC	0,0044 mg/l	93 d	Salmo gairdneri (new name: Oncorhynchus mykiss)	EPA OPPTS 797.1600 (Fish Early Life Stage Toxicity Test)
octamethylcyclotetrasiloxane 556-67-2	LC50	Toxicity > Water solubility	96 h	Oncorhynchus mykiss	EPA OTS 797.1400 (Fish Acute Toxicity Test)

Toxicity (aquatic invertebrates):

EC50 (dafnia) >100 mg/l (OECD 211)

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Trimethoxy(methyl)silane 1185-55-3	EC50	> 816 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3- (Trimethoxysilyl)propylamine 13822-56-5	EC50	331 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hexamethyldisilizane 999-97-3	EC50	80 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
octamethylcyclotetrasiloxane 556-67-2	EC50	Toxicity > Water solubility	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)

Chronic toxicity (aquatic invertebrates):

NOEC (dafnia) > 1 mg/l (OECD 211)

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hexamethyldisiloxane 107-46-0	NOEC	0,08 mg/l	21 d	1 0	OECD 211 (Daphnia magna, Reproduction Test)
octamethylcyclotetrasiloxane 556-67-2	NOEC	7.9 μg/l	21 d		EPA OTS 797.1330 (Daphnid Chronic Toxicity

		Test)

Toxicity (Algae):

 $\begin{array}{l} NOEC \; (Algae) > 1 \; mg/l \; (OECD \; 201) \\ EC50 \; (Algae) > 100 \; mg/l \; (OECD \; 201) \end{array}$

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
Trimethoxy(methyl)silane 1185-55-3	EC50	> 913 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Trimethoxy(methyl)silane 1185-55-3	NOEC	> 913 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
3- (Trimethoxysilyl)propylamine 13822-56-5	EC50	> 1.000 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)
3- (Trimethoxysilyl)propylamine 13822-56-5	NOEC	1,3 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)
Hexamethyldisiloxane 107-46-0	EC50	Toxicity > Water solubility	70 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hexamethyldisiloxane 107-46-0	EC10	0,09 mg/l	70 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hexamethyldisilizane 999-97-3	EC10	7,5 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
Hexamethyldisilizane 999-97-3	EC50	50 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
octamethylcyclotetrasiloxane 556-67-2	EC50	Toxicity > Water solubility	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
octamethylcyclotetrasiloxane 556-67-2	EC10	0,022 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Hexamethyldisiloxane	EC50	Toxicity > Water	3 h	activated sludge, domestic	OECD Guideline 209
107-46-0		solubility			(Activated Sludge,
					Respiration Inhibition Test)
octamethylcyclotetrasiloxane	EC50	Toxicity > Water	3 h	activated sludge	ISO 8192 (Test for
556-67-2		solubility			Inhibition of Oxygen
					Consumption by Activated
					Sludge)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Trimethoxy(methyl)silane 1185-55-3	not readily biodegradable.	aerobic	54 %		OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
3- (Trimethoxysilyl)propylamine 13822-56-5	readily biodegradable	aerobic	80,2 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hexamethyldisiloxane 107-46-0	not readily biodegradable.	aerobic	2 %	28 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Hexamethyldisilizane 999-97-3	not readily biodegradable.	no data	15,3 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
octamethylcyclotetrasiloxane 556-67-2	not readily biodegradable.	aerobic	3,7 %	29 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Hexamethyldisiloxane 107-46-0	776 - 2.410	70 d		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
octamethylcyclotetrasiloxane 556-67-2	12.400	28 d		Pimephales promelas	EPA OTS 797.1520 (Fish Bioconcentration Test-Rainbow Trout)

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
3- (Trimethoxysilyl)propylamine 13822-56-5	-1,3	20 °C	QSAR (Quantitative Structure Activity Relationship)
Hexamethyldisiloxane 107-46-0	5,06	20 °C	other guideline:
octamethylcyclotetrasiloxane 556-67-2	6,98	21,7 °C	other guideline:

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
Trimethoxy(methyl)silane	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
1185-55-3	Bioaccumulative (vPvB) criteria.
3-(Trimethoxysilyl)propylamine	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
13822-56-5	Bioaccumulative (vPvB) criteria.
Hexamethyldisiloxane	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
107-46-0	Bioaccumulative (vPvB) criteria.
Hexamethyldisilizane	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
999-97-3	Bioaccumulative (vPvB) criteria.
octamethylcyclotetrasiloxane	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
556-67-2	Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water. Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

	SECTION 14: Transport information
14.1.	UN number or ID number
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.2.	UN proper shipping name
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.3.	Transport hazard class(es)
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.4.	Packing group
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.5.	Environmental hazards
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.6.	Special precautions for user
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.7.	Maritime transport in bulk according to IMO instruments
	not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture				
Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):		Not applicable		
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):		Not applicable		
Persistent organic pollutants (Regulation (EU) 2019/1021):		Not applicable		
VOC content (2010/75/EC)	< 5 %			

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK:

WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV)) Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 11

Page 19 of 19

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text
of all abbreviations indicated by codes in this safety data sheet are as follows:
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H361f Suspected of damaging fertility.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very
	bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.