



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 28

LOCTITE PC 6311 GY known as LOCTITE BF VHGR GRAY KT .95GA
E

SDS No. : 436608
V003.0

Revision: 08.03.2023

printing date: 14.03.2023

Replaces version from: 02.07.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE PC 6311 GY known as LOCTITE BF VHGR GRAY KT .95GA E

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Coating

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 3
H226 Flammable liquid and vapour.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)
p-Chloro-a,a,a-trifluorotoluene

Signal word:

Warning

Hazard statement:

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

Supplemental information

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Precautionary statement:
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 Avoid release to the environment.
P280 Wear protective gloves.

**Precautionary statement:
Response**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

**Precautionary statement:
Storage**

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Quartz (SiO ₂), <1% respirable 14808-60-7 238-878-4	20- 40 %			
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	5- < 10 %	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411 Eye Irrit. 2, H319	Skin Irrit. 2; H315; C ≥ 5 % Eye Irrit. 2; H319; C ≥ 5 %	
p-Chloro-a,a,a-trifluorotoluene 98-56-6 202-681-1	5- < 10 %	Aquatic Chronic 2, H411 Flam. Liq. 3, H226 Skin Sens. 1B, H317		
heptan-2-one 110-43-0 203-767-1 01-2119902391-49	5- < 10 %	Acute Tox. 4, Oral, H302 Acute Tox. 4, Inhalation, H332 Flam. Liq. 3, H226 STOT SE 3, H336	inhalation:ATE = 16,71 mg/l;	EU OEL
Xylene - mixture of isomers 1330-20-7 215-535-7 01-2119488216-32	1- < 3 %	Asp. Tox. 1, H304 Acute Tox. 4, Inhalation, H332 Acute Tox. 4, Dermal, H312 Skin Irrit. 2, H315 Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412	dermal:ATE = 1.700 mg/kg oral:ATE = 3.523 mg/kg inhalation:ATE = 11 mg/l;vapour	EU OEL
1-methoxy-2-propanol 107-98-2 203-539-1 01-2119457435-35	1- < 3 %	Flam. Liq. 3, H226 STOT SE 3, H336		EU OEL
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6 265-199-0 01-2119455851-35	1- < 2,5 %	Aquatic Chronic 2, H411 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 STOT SE 3, H335		
Titanium dioxide 13463-67-7 236-675-5 01-2119489379-17	1- < 3 %	Carc. 2, Inhalation, H351		

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Refer to Technical Data Sheet

Store in a cool, dry place.

Do not store near sources of heat or ignition, or reactive materials.

7.3. Specific end use(s)

Coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Aluminium oxide 1344-28-1			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Aluminium oxide 1344-28-1		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Aluminium oxide 1344-28-1		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Heptan-2-one 110-43-0 [HEPTAN-2-ONE]			Skin designation:	Can be absorbed through the skin.	ECTLV
Heptan-2-one 110-43-0 [HEPTAN-2-ONE]	100	475	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Heptan-2-one 110-43-0 [HEPTAN-2-ONE]	50	238	Time Weighted Average (TWA):	Indicative	ECTLV
Heptan-2-one 110-43-0			Skin designation:	Can be absorbed through the skin.	TRGS 900
Heptan-2-one 110-43-0		238	Exposure limit(s):	2	TRGS 900
Heptan-2-one 110-43-0			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	50	221	Time Weighted Average (TWA):	Indicative	ECTLV
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	100	442	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Xylene 1330-20-7			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Xylene 1330-20-7			Skin designation:	Can be absorbed through the skin.	TRGS 900
Xylene 1330-20-7	50	220	Exposure limit(s):	2	TRGS 900
1-Methoxypropan-2-ol 107-98-2 [1-METHOXYPROPANOL-2]	100	375	Time Weighted Average (TWA):	Indicative	ECTLV
1-Methoxypropan-2-ol 107-98-2 [1-METHOXYPROPANOL-2]	150	568	Short Term Exposure Limit (STEL):	Indicative	ECTLV
1-Methoxypropan-2-ol 107-98-2	100	370	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
1-Methoxypropan-2-ol 107-98-2			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Titanium dioxide			Short Term Exposure	Category II: substances with a	TRGS 900

13463-67-7			Classification:	resorptive effect.	
Titanium dioxide 13463-67-7		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Titanium dioxide 13463-67-7		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Heptan-2-one 110-43-0	aqua (freshwater)		0,0982 mg/l				
Heptan-2-one 110-43-0	aqua (marine water)		0,00982 mg/l				
Heptan-2-one 110-43-0	aqua (intermittent releases)		0,982 mg/l				
Heptan-2-one 110-43-0	sediment (freshwater)				1,89 mg/kg		
Heptan-2-one 110-43-0	sediment (marine water)				0,189 mg/kg		
Heptan-2-one 110-43-0	Soil				0,321 mg/kg		
Heptan-2-one 110-43-0	sewage treatment plant (STP)		12,5 mg/l				
Xylene - mixture of isomeres 1330-20-7	aqua (freshwater)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	sediment (freshwater)				12,46 mg/kg		
Xylene - mixture of isomeres 1330-20-7	Soil				2,31 mg/kg		
Xylene - mixture of isomeres 1330-20-7	aqua (marine water)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	Freshwater - intermittent		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	sewage treatment plant (STP)		6,58 mg/l				
Xylene - mixture of isomeres 1330-20-7	sediment (marine water)				12,46 mg/kg		
Xylene - mixture of isomeres 1330-20-7	Predator						no potential for bioaccumulation
1-methoxy-2-propanol 107-98-2	aqua (freshwater)		10 mg/l				
1-methoxy-2-propanol 107-98-2	aqua (marine water)		1 mg/l				
1-methoxy-2-propanol 107-98-2	aqua (intermittent releases)		100 mg/l				
1-methoxy-2-propanol 107-98-2	sediment (freshwater)				52,3 mg/kg		
1-methoxy-2-propanol 107-98-2	sediment (marine water)				5,2 mg/kg		
1-methoxy-2-propanol 107-98-2	Soil				4,59 mg/kg		
1-methoxy-2-propanol 107-98-2	sewage treatment plant (STP)		100 mg/l				
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	aqua (freshwater)						
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	aqua (marine water)						
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	sewage treatment plant (STP)						
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	sediment (freshwater)						
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	sediment (marine water)						
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	Air						no hazard identified
Solvent naphtha (petroleum), light arom.,	Soil						

<0.1% Benzene 64742-95-6							
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	Predator						

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Heptan-2-one 110-43-0	Workers	inhalation	Long term exposure - systemic effects		394,25 mg/m3	
Heptan-2-one 110-43-0	Workers	inhalation	Acute/short term exposure - systemic effects		1516 mg/m3	
Heptan-2-one 110-43-0	Workers	dermal	Long term exposure - systemic effects		54,27 mg/kg	
Heptan-2-one 110-43-0	General population	inhalation	Long term exposure - systemic effects		84,31 mg/m3	
Heptan-2-one 110-43-0	General population	dermal	Long term exposure - systemic effects		23,32 mg/kg	
Heptan-2-one 110-43-0	General population	oral	Long term exposure - systemic effects		23,32 mg/kg	
Xylene - mixture of isomeres 1330-20-7	Workers	inhalation	Long term exposure - systemic effects		221 mg/m3	no potential for bioaccumulation
Xylene - mixture of isomeres 1330-20-7	Workers	inhalation	Acute/short term exposure - systemic effects		442 mg/m3	no potential for bioaccumulation
Xylene - mixture of isomeres 1330-20-7	Workers	inhalation	Long term exposure - local effects		221 mg/m3	no potential for bioaccumulation
Xylene - mixture of isomeres 1330-20-7	Workers	inhalation	Acute/short term exposure - local effects		442 mg/m3	no potential for bioaccumulation
Xylene - mixture of isomeres 1330-20-7	Workers	dermal	Long term exposure - systemic effects		212 mg/kg	no potential for bioaccumulation
Xylene - mixture of isomeres 1330-20-7	General population	inhalation	Long term exposure - systemic effects		65,3 mg/m3	no potential for bioaccumulation
Xylene - mixture of isomeres 1330-20-7	General population	inhalation	Acute/short term exposure - systemic effects		260 mg/m3	no potential for bioaccumulation
Xylene - mixture of isomeres 1330-20-7	General population	inhalation	Long term exposure - local effects		65,3 mg/m3	no potential for bioaccumulation
Xylene - mixture of isomeres 1330-20-7	General population	inhalation	Acute/short term exposure - local effects		260 mg/m3	no potential for bioaccumulation
Xylene - mixture of isomeres 1330-20-7	General population	dermal	Long term exposure - systemic effects		125 mg/kg	no potential for bioaccumulation
Xylene - mixture of isomeres 1330-20-7	General population	oral	Long term exposure - systemic effects		12,5 mg/kg	no potential for bioaccumulation
1-methoxy-2-propanol 107-98-2	Workers	Inhalation	Acute/short term exposure - local effects		553,5 mg/m3	
1-methoxy-2-propanol 107-98-2	Workers	dermal	Long term exposure - systemic effects		183 mg/kg	
1-methoxy-2-propanol 107-98-2	Workers	Inhalation	Long term exposure - systemic effects		369 mg/m3	
1-methoxy-2-propanol 107-98-2	General population	dermal	Long term exposure - systemic effects		78 mg/kg	
1-methoxy-2-propanol 107-98-2	General population	Inhalation	Long term exposure - systemic effects		43,9 mg/m3	
1-methoxy-2-propanol 107-98-2	General population	oral	Long term exposure - systemic effects		33 mg/kg	

1-methoxy-2-propanol 107-98-2	Workers	inhalation	Acute/short term exposure - systemic effects		553,5 mg/m3	
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	Workers	inhalation	Long term exposure - systemic effects		151 mg/m3	no hazard identified
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	Workers	dermal	Long term exposure - systemic effects		12,5 mg/kg	no hazard identified
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	General population	inhalation	Long term exposure - systemic effects		32 mg/m3	no hazard identified
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	General population	dermal	Long term exposure - systemic effects		7,5 mg/kg	no hazard identified
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	General population	oral	Long term exposure - systemic effects		7,5 mg/kg	no hazard identified
Titanium dioxide 13463-67-7	Workers	inhalation	Long term exposure - local effects		0,17 mg/m3	
Titanium dioxide 13463-67-7	General population	inhalation	Long term exposure - local effects		0,028 mg/m3	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Aluminium oxide 1344-28-1	Aluminum	Urine	Sampling time: End of shift.	200 µg/l	DE BAT		
Xylene 1330-20-7	Methylhippuric (toluric) acid (all isomers)	Urine	Sampling time: End of shift.	2.000 mg/l	DE BGW		
1-Methoxypropan-2-ol 107-98-2	1-Methoxypropan-2-ol	Urine	Sampling time: End of shift.	15 mg/l	DE BGW		

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.
Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	Currently under determination
Colour	Grey
Odor	mild
Physical state	liquid
Melting point	Currently under determination
Initial boiling point	115,6 °C (240.1 °F)
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	27,22 °C (81 °F) Estimated
Auto-ignition temperature	Currently under determination
Decomposition temperature	Currently under determination
pH	Not available.
Viscosity (kinematic)	Currently under determination
Solubility (qualitative)	Negligible
(Solvent: Water)	
Partition coefficient: n-octanol/water	Currently under determination
Vapour pressure	40 mm hg Estimated
(20 °C (68 °F))	
Density	15,5 - 16,5 lb/gal LCT CERT; Certificate of analysis
()	
Relative vapour density:	Currently under determination
Particle characteristics	Currently under determination

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants.
Reaction with strong acids.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Quartz (SiO ₂), <1% respirable 14808-60-7	LD50	> 5.050 mg/kg	rat	not specified
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
p-Chloro-a,a,a- trifluorotoluene 98-56-6	LD50	5.546 mg/kg	rat	not specified
heptan-2-one 110-43-0	LD50	1.600 mg/kg	rat	not specified
Xylene - mixture of isomeres 1330-20-7	LD50	3.523 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))
Xylene - mixture of isomeres 1330-20-7	Acute toxicity estimate (ATE)	3.523 mg/kg		Expert judgement
1-methoxy-2-propanol 107-98-2	LD50	3.739 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	LD50	3.492 mg/kg	rat	not specified
Titanium dioxide 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Quartz (SiO ₂), <1% respirable 14808-60-7	LD50	> 2.000 mg/kg	not specified	not specified
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
p-Chloro-a,a,a- trifluorotoluene 98-56-6	LD50	> 3.300 mg/kg	rabbit	not specified
heptan-2-one 110-43-0	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Xylene - mixture of isomeres 1330-20-7	LD50	1.700 mg/kg	rabbit	not specified
Xylene - mixture of isomeres 1330-20-7	Acute toxicity estimate (ATE)	1.700 mg/kg		Expert judgement
1-methoxy-2-propanol 107-98-2	LD50	> 2.000 mg/kg	rat	EU Method B.3 (Acute Toxicity (Dermal))
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	LD50	> 3.160 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Titanium dioxide 13463-67-7	LD50	> 10.000 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
p-Chloro-a,a,a-trifluorotoluene 98-56-6	LC50	> 32,03 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
heptan-2-one 110-43-0	LC50	> 16,7 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
heptan-2-one 110-43-0	Acute toxicity estimate (ATE)	16,71 mg/l				Expert judgement
Xylene - mixture of isomeres 1330-20-7	LC50	11 mg/l	vapour	4 h	rat	not specified
Xylene - mixture of isomeres 1330-20-7	Acute toxicity estimate (ATE)	11 mg/l	vapour			Expert judgement
1-methoxy-2-propanol 107-98-2	LC50	55 mg/l	vapour	4 h	rat	not specified
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	LC50	> 10,2 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Titanium dioxide 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not irritating	4 h	rabbit	not specified
p-Chloro-a,a,a-trifluorotoluene 98-56-6	not irritating	24 h	rabbit	Patch Test
heptan-2-one 110-43-0	moderately irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Xylene - mixture of isomeres 1330-20-7	moderately irritating		rabbit	not specified
1-methoxy-2-propanol 107-98-2	not irritating	4 h	rabbit	EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion)
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	mildly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
p-Chloro-a,a,a- trifluorotoluene 98-56-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
heptan-2-one 110-43-0	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Xylene - mixture of isomeres 1330-20-7	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1-methoxy-2-propanol 107-98-2	not irritating		rabbit	EU Method B.5 (Acute Toxicity: Eye Irritation / Corrosion)
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
p-Chloro-a,a,a- trifluorotoluene 98-56-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
heptan-2-one 110-43-0	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Xylene - mixture of isomeres 1330-20-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
1-methoxy-2-propanol 107-98-2	not sensitising	Guinea pig maximisation test	guinea pig	EU Method B.6 (Skin Sensitisation)
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	not sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
p-Chloro-a,a,a- trifluorotoluene 98-56-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
p-Chloro-a,a,a- trifluorotoluene 98-56-6	negative	in vitro mammalian chromosome aberration test	with and without		
p-Chloro-a,a,a- trifluorotoluene 98-56-6	negative	in vitro mammalian cell transformation assay	with and without		
heptan-2-one 110-43-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
heptan-2-one 110-43-0	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
heptan-2-one 110-43-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Xylene - mixture of isomeres 1330-20-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Xylene - mixture of isomeres 1330-20-7	negative	in vitro mammalian chromosome aberration test	with and without		EU Method B.10 (Mutagenicity)
Xylene - mixture of isomeres 1330-20-7	negative	sister chromatid exchange assay in mammalian cells	with and without		EU Method B.19 (Sister Chromatid Exchange Assay In Vitro)
1-methoxy-2-propanol 107-98-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1-methoxy-2-propanol 107-98-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
1-methoxy-2-propanol 107-98-2	negative	mammalian cell gene mutation assay	without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	negative	sister chromatid exchange assay in mammalian cells	with and without		OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	in vitro mammalian cell micronucleus test	without		equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average	negative	oral: gavage		mouse	not specified

molecular weight≤700) 25068-38-6					
p-Chloro-a,a,a-trifluorotoluene 98-56-6	negative	oral: gavage		rat	not specified
Xylene - mixture of isomers 1330-20-7	negative	intraperitoneal		rat	OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)
1-methoxy-2-propanol 107-98-2	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	negative	inhalation		rat	EPA OPPTS 870.5395 (In Vivo Mammalian Cytogenics Tests: Erythrocyte Micronucleus Assay)
Titanium dioxide 13463-67-7	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not carcinogenic	dermal	2 y daily	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not carcinogenic	oral: gavage	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Xylene - mixture of isomers 1330-20-7	not carcinogenic	oral: gavage	103 w 5 d/w	rat	male/female	EU Method B.32 (Carcinogenicity Test)
1-methoxy-2-propanol 107-98-2	not carcinogenic	inhalation: vapour	2 y 6 hr/day, 5 days/wk	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Titanium dioxide 13463-67-7	not carcinogenic	oral: feed	103 w daily	rat	male/female	not specified

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOAEL P >= 50 mg/kg NOAEL F1 >= 750 mg/kg NOAEL F2 >= 750 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
p-Chloro-a,a,a-trifluorotoluene 98-56-6	NOAEL F1 45 mg/kg	One generation study	oral: gavage	rat	OECD Guideline 415 (One-Generation Reproduction Toxicity Study)
heptan-2-one 110-43-0	NOAEL P 1000 ppm	screening	inhalation: vapour	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
1-methoxy-2-propanol 107-98-2	NOAEL P 300 ppm NOAEL F1 1000 ppm NOAEL F2 1000 ppm	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Titanium dioxide 13463-67-7	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg	one-generation study	oral: feed	rat	OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOAEL 50 mg/kg	oral: gavage	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
p-Chloro-a,a,a-trifluorotoluene 98-56-6	NOAEL 40 mg/kg	oral: gavage	3 m daily	rat	not specified
p-Chloro-a,a,a-trifluorotoluene 98-56-6	NOAEL >= 5.5 mg/m3	inhalation	4 m 24 h/d	rat	not specified
heptan-2-one 110-43-0	NOAEL 500 mg/kg	oral: gavage	13 w daily	rat	not specified
Xylene - mixture of isomeres 1330-20-7	NOAEL 150 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
1-methoxy-2-propanol 107-98-2	NOAEL 1000 ppm	inhalation	13 weeks 6 hours/day; 5 days/week	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
1-methoxy-2-propanol 107-98-2	NOAEL 919 mg/kg	oral: gavage	35 d 5 d/w	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Titanium dioxide 13463-67-7	NOAEL > 1.000 mg/kg	oral: gavage	92 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	< 1 mm ² /s	40 °C	not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains / surface water / ground water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Quartz (SiO ₂), <1% respirable 14808-60-7	LC50	> 1.000 mg/l	96 h	not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	LC50	1,75 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
p-Chloro-a,a,a-trifluorotoluene 98-56-6	NOEC	0,54 mg/l		Pimephales promelas	OECD Guideline 210 (fish early lite stage toxicity test)
p-Chloro-a,a,a-trifluorotoluene 98-56-6	LC50	3 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
heptan-2-one 110-43-0	LC50	131 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Xylene - mixture of isomeres 1330-20-7	LC50	2,6 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Xylene - mixture of isomeres 1330-20-7	NOEC	> 1,3 mg/l	56 d	Oncorhynchus mykiss	other guideline:
1-methoxy-2-propanol 107-98-2	LC50	20.800 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	LL50	8,2 mg/l	96 h	Pimephales promelas	EPA-660 (Methods for Acute Toxicity Tests with Fish, Macroinvertebrates and Amphibians)
Titanium dioxide 13463-67-7	LC50	Toxicity > Water solubility	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Quartz (SiO ₂), <1% respirable 14808-60-7	EC50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	EC50	1,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
p-Chloro-a,a,a-trifluorotoluene 98-56-6	EC50	2 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
heptan-2-one 110-43-0	EC50	> 90,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Xylene - mixture of isomeres 1330-20-7	EC50	3,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1-methoxy-2-propanol 107-98-2	EC50	23.300 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	EL50	4,5 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Xylene - mixture of isomeres 1330-20-7	NOEC	0,96 mg/l	7 d	Ceriodaphnia dubia	other guideline:
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	NOELR	2,6 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	21 d	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Quartz (SiO ₂), <1% respirable 14808-60-7	EC50	> 1.000 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
p-Chloro-a,a,a-trifluorotoluene 98-56-6	NOEC	0,41 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
heptan-2-one 110-43-0	EC50	98,2 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
heptan-2-one 110-43-0	NOEC	42,68 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Xylene - mixture of isomers 1330-20-7	EC50	4,36 mg/l	73 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Xylene - mixture of isomers 1330-20-7	EC10	1,9 mg/l	73 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1-methoxy-2-propanol 107-98-2	EC50	> 1.000 mg/l	7 d	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	EL50	3,1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	NOELR	0,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Quartz (SiO ₂), <1% respirable 14808-60-7	EC0	> 1.000 mg/l	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
p-Chloro-a,a,a-trifluorotoluene 98-56-6	EC50	103,6 mg/l	3 h	activated sludge, domestic	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
heptan-2-one 110-43-0	EC50	690 mg/l	16 h	Pseudomonas putida	ISO 10712: Determination of the inhibitory effect of water constituents on bacteria (Pseudomonas cell inhibition test)
1-methoxy-2-propanol 107-98-2	EC0	> 1.000 mg/l	30 min		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Titanium dioxide 13463-67-7	EC0	Toxicity > Water solubility	24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
p-Chloro-a,a,a-trifluorotoluene 98-56-6		aerobic	19,2 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
heptan-2-one 110-43-0	readily biodegradable	aerobic	69 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO ₂ in Sealed Vessels (Headspace Test)
Xylene - mixture of isomeres 1330-20-7	readily biodegradable	aerobic	90 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
1-methoxy-2-propanol 107-98-2	readily biodegradable	aerobic	90 %	29 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	readily biodegradable	aerobic	77 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Xylene - mixture of isomeres 1330-20-7	25,9	56 d		Oncorhynchus mykiss	not specified

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	3,242	25 °C	EU Method A.8 (Partition Coefficient)
p-Chloro-a,a,a-trifluorotoluene 98-56-6	3,7	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
heptan-2-one 110-43-0	2,26	30 °C	EU Method A.8 (Partition Coefficient)
Xylene - mixture of isomeres 1330-20-7	3,16	20 °C	not specified
1-methoxy-2-propanol 107-98-2	-0,49		not specified
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	2,13 - 4,58		QSAR (Quantitative Structure Activity Relationship)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Quartz (SiO ₂), <1% respirable 14808-60-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
heptan-2-one 110-43-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Xylene - mixture of isomeres 1330-20-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
1-methoxy-2-propanol 107-98-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Solvent naphtha (petroleum), light arom., <0.1% Benzene 64742-95-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Titanium dioxide 13463-67-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Do not empty into drains / surface water / ground water.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	1263
RID	1263
ADN	1263
IMDG	1263
IATA	1263

14.2. UN proper shipping name

ADR	PAINT
RID	PAINT
ADN	PAINT
IMDG	PAINT
IATA	Paint

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D/E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	11 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV))
Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 3

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.



Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No. : 416782

V003.0

LOCTITE PC 6311 GY known as LOCTITE BF VHGR GRAY KT
.95GA E

Revision: 08.03.2023

printing date: 14.03.2023

Replaces version from: 07.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE PC 6311 GY known as LOCTITE BF VHGR GRAY KT .95GA E

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Coating

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids

Category 3

H226 Flammable liquid and vapour.

Skin corrosion

Category 1B

H314 Causes severe skin burns and eye damage.

Serious eye damage

Category 1

H318 Causes serious eye damage.

Specific target organ toxicity - single exposure

Category 3

H336 May cause drowsiness or dizziness.

Target organ: Central nervous system

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

1-methoxy-2-propanol

Amidoamine Resin

Signal word: Danger

Hazard statement:
H226 Flammable liquid and vapour.
H314 Causes severe skin burns and eye damage.
H336 May cause drowsiness or dizziness.

Precautionary statement:
Prevention
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapours.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement:
Response
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor.

Precautionary statement:
Storage
P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Amidoamine Resin 68443-08-3	10- 20 %	Acute Tox. 4, Oral, H302 Skin Corr. 1B, H314		
1-methoxy-2-propanol 107-98-2 203-539-1 01-2119457435-35	2,5- < 25 %	Flam. Liq. 3, H226 STOT SE 3, H336		EU OEL

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

Vapors may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

Combustion behaviour:

Solvent containing flammable product. In case of fire toxic gases are released.

5.1. Extinguishing media

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

Fine water spray

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from sources of ignition - no smoking.
Use only in well-ventilated areas.
Vapours should be extracted to avoid inhalation.
Avoid skin and eye contact.
See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.
Do not eat, drink or smoke while working.
Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Refer to Technical Data Sheet
Store in a cool, dry place.
Do not store near sources of heat or ignition, or reactive materials.

7.3. Specific end use(s)

Coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
1-Methoxypropan-2-ol 107-98-2 [1-METHOXYPROPANOL-2]	100	375	Time Weighted Average (TWA):	Indicative	ECTLV
1-Methoxypropan-2-ol 107-98-2 [1-METHOXYPROPANOL-2]	150	568	Short Term Exposure Limit (STEL):	Indicative	ECTLV
1-Methoxypropan-2-ol 107-98-2	100	370	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
1-Methoxypropan-2-ol 107-98-2			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
1-methoxy-2-propanol 107-98-2	aqua (freshwater)		10 mg/l				
1-methoxy-2-propanol 107-98-2	aqua (marine water)		1 mg/l				
1-methoxy-2-propanol 107-98-2	aqua (intermittent releases)		100 mg/l				
1-methoxy-2-propanol 107-98-2	sediment (freshwater)				52,3 mg/kg		
1-methoxy-2-propanol 107-98-2	sediment (marine water)				5,2 mg/kg		
1-methoxy-2-propanol 107-98-2	Soil				4,59 mg/kg		
1-methoxy-2-propanol 107-98-2	sewage treatment plant (STP)		100 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
1-methoxy-2-propanol 107-98-2	Workers	Inhalation	Acute/short term exposure - local effects		553,5 mg/m3	
1-methoxy-2-propanol 107-98-2	Workers	dermal	Long term exposure - systemic effects		183 mg/kg	
1-methoxy-2-propanol 107-98-2	Workers	Inhalation	Long term exposure - systemic effects		369 mg/m3	
1-methoxy-2-propanol 107-98-2	General population	dermal	Long term exposure - systemic effects		78 mg/kg	
1-methoxy-2-propanol 107-98-2	General population	Inhalation	Long term exposure - systemic effects		43,9 mg/m3	
1-methoxy-2-propanol 107-98-2	General population	oral	Long term exposure - systemic effects		33 mg/kg	
1-methoxy-2-propanol 107-98-2	Workers	inhalation	Acute/short term exposure - systemic effects		553,5 mg/m3	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
1-Methoxypropan-2-ol 107-98-2	1-Methoxypropan-2-ol	Urine	Sampling time: End of shift.	15 mg/l	DE BGW		

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	Currently under determination
Colour	Amber
Odor	mild
Physical state	liquid
Melting point	Currently under determination
Initial boiling point	120 °C (248 °F)
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	38,00 °C (100.4 °F)
Auto-ignition temperature	Currently under determination
Decomposition temperature	Currently under determination
pH	Not available.
Viscosity (kinematic)	Currently under determination
Solubility (qualitative)	Negligible
(Solvent: Water)	
Partition coefficient: n-octanol/water	Currently under determination
Vapour pressure	Currently under determination
Density	8,1 - 8,2 lb/gal LCT CERT; Certificate of analysis
()	
Relative vapour density:	Currently under determination
Particle characteristics	Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Strong oxidizing agents.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.
Heat, flames, sparks and other sources of ignition.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information

General toxicological information:

Inhalation of vapors in high concentration may cause irritation of respiratory system

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
1-methoxy-2-propanol 107-98-2	LD50	3.739 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
1-methoxy-2-propanol 107-98-2	LD50	> 2.000 mg/kg	rat	EU Method B.3 (Acute Toxicity (Dermal))

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
1-methoxy-2-propanol 107-98-2	LC50	55 mg/l	vapour	4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
1-methoxy-2-propanol 107-98-2	not irritating	4 h	rabbit	EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
1-methoxy-2-propanol 107-98-2	not irritating		rabbit	EU Method B.5 (Acute Toxicity: Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
1-methoxy-2-propanol 107-98-2	not sensitising	Guinea pig maximisation test	guinea pig	EU Method B.6 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
1-methoxy-2-propanol 107-98-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1-methoxy-2-propanol 107-98-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
1-methoxy-2-propanol 107-98-2	negative	mammalian cell gene mutation assay	without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1-methoxy-2-propanol 107-98-2	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
1-methoxy-2-propanol 107-98-2	not carcinogenic	inhalation: vapour	2 y 6 hr/day, 5 days/wk	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
1-methoxy-2-propanol 107-98-2	NOAEL P 300 ppm NOAEL F1 1000 ppm NOAEL F2 1000 ppm	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
1-methoxy-2-propanol 107-98-2	NOAEL 1000 ppm	inhalation	13 weeks 6 hours/day; 5 days/week	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
1-methoxy-2-propanol 107-98-2	NOAEL 919 mg/kg	oral: gavage	35 d 5 d/w	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1-methoxy-2-propanol 107-98-2	LC50	20.800 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1-methoxy-2-propanol 107-98-2	EC50	23.300 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

No data available.

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1-methoxy-2-propanol 107-98-2	EC50	> 1.000 mg/l	7 d	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1-methoxy-2-propanol 107-98-2	EC0	> 1.000 mg/l	30 min		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
1-methoxy-2-propanol 107-98-2	readily biodegradable	aerobic	90 %	29 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
1-methoxy-2-propanol 107-98-2	-0,49		not specified

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
1-methoxy-2-propanol 107-98-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Do not empty into drains / surface water / ground water.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

14 06 03 Other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	2924
RID	2924
ADN	2924
IMDG	2924
IATA	2924

14.2. UN proper shipping name

ADR	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propylenglycol monomethyl ether,Amidoamine resin)
RID	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propylenglycol monomethyl ether,Amidoamine resin)
ADN	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propylenglycol monomethyl ether,Amidoamine resin)
IMDG	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propylenglycol monomethyl ether,Amidoamine resin)
IATA	Flammable liquid, corrosive, n.o.s. (Propylenglycol monomethyl ether,Amidoamine resin)

14.3. Transport hazard class(es)

ADR	3 (8)
RID	3 (8)
ADN	3 (8)
IMDG	3 (8)
IATA	3 (8)

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
-----	----------------

	Tunnelcode: (D/E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	21,00 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: WGK 3: highly hazardous to water (Ordinance on facilities for handling substances that are hazardous to water (AwSV))
Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 3

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H336 May cause drowsiness or dizziness.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2:	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.