



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 18

TEROSON PU 8597 HMLC

SDS No. : 352582

V004.1

Revision: 21.12.2023

printing date: 27.12.2023

Replaces version from: 14.11.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TEROSON PU 8597 HMLC

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

adhesive and sealant for direct glazing

#### 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Respiratory sensitizer

Category 1

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

#### 2.2. Label elements

##### Label elements (CLP):

##### Hazard pictogram:



##### Contains

Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatobenzene]

Hexanedioic acid, polymer with 1,6-hexanediol and 1,1'-methylenebis[4-isocyanatobenzene]

4,4'-methylenediphenyl diisocyanate

**Signal word:** Danger

**Hazard statement:** H317 May cause an allergic skin reaction.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Supplemental information** As from 24 August 2023 adequate training is required before industrial or professional use.  
Further information: <https://www.feica.eu/PUinfo>

**Precautionary statement:** P261 Avoid breathing dust/fume/spray.  
**Prevention** P280 Wear protective gloves.

**Precautionary statement:** P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor.  
**Response**

### 2.3. Other hazards

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):**

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

<b>Hazardous components CAS-No. EC Number REACH-Reg No.</b>	<b>Concentration</b>	<b>Classification</b>	<b>Specific Conc. Limits, M- factors and ATEs</b>	<b>Add. Information</b>
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatobenzene] 59675-67-1	1- < 5 %	Acute Tox. 4, Inhalation, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Resp. Sens. 1, H334 STOT SE 3, H335 STOT RE 2, H373	oral:ATE = > 5.000 mg/kg inhalation:ATE = 1,5 mg/l;dust/mist	
Hexanedioic acid, polymer with 1,6-hexanediol and 1,1'-methylenebis[4-isocyanatobenzene] 31075-20-4	1- < 3 %	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 STOT SE 3, H335 Resp. Sens. 1, H334 STOT RE 2, H373		
Oxydipropyl dibenzoate 27138-31-4 248-258-5 01-2119529241-49	0,25- < 2,5 %	Aquatic Chronic 3, H412		
4,4'- methylenediphenyl diisocyanate 101-68-8 202-966-0 01-2119457014-47	0,1- < 1 %	Carc. 2, H351 Acute Tox. 4, Inhalation, H332 STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 % Resp. Sens. 1; H334; C >= 0,1 % STOT SE 3; H335; C >= 5 %	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Fresh air, oxygen supply, warmth; seek specialist medical attention.

Delayed effects possible after inhalation.

**Skin contact:**

IF ON SKIN: Wash with plenty of soap and water.

In case of adverse health effects seek medical advice.

**Ingestion:**

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

SKIN: Rash, Urticaria.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media:

All common extinguishing agents are suitable.

#### Extinguishing media which must not be used for safety reasons:

High pressure waterjet

### 5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

### 5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

### 6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

Remove mechanically.

### 6.4. Reference to other sections

See advice in section 8

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

### 7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Ensure good ventilation/extraction.

Store in a cool place.

Temperatures between + 10 °C and + 25 °C

Keep container tightly sealed.

Store in a cool, dry place.

Temperatures between + 5 °C and + 35 °C

### 7.3. Specific end use(s)

adhesive and sealant for direct glazing

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational Exposure Limits**Valid for  
Germany

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Carbon black 1333-86-4		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Carbon black 1333-86-4		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Carbon black 1333-86-4			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
4,4'-Methylenediphenyl diisocyanate 101-68-8			Skin designation:	Can be absorbed through the skin.	TRGS 900
4,4'-Methylenediphenyl diisocyanate 101-68-8			STEL (Short Term Exposure Limit) factor:	1 Substance listed with both Peak factor and STEL factor. The Peak factor is supplied with the AGW values.	TRGS 900
4,4'-Methylenediphenyl diisocyanate 101-68-8		0,05	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
4,4'-Methylenediphenyl diisocyanate 101-68-8			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Oxydipropyl dibenzoate 27138-31-4	aqua (freshwater)		0,02 mg/l				
Oxydipropyl dibenzoate 27138-31-4	aqua (marine water)		0,002 mg/l				
Oxydipropyl dibenzoate 27138-31-4	sewage treatment plant (STP)		10 mg/l				
Oxydipropyl dibenzoate 27138-31-4	sediment (freshwater)				8,03 mg/kg		
Oxydipropyl dibenzoate 27138-31-4	sediment (marine water)				0,803 mg/kg		
Oxydipropyl dibenzoate 27138-31-4	Soil				1 mg/kg		
Oxydipropyl dibenzoate 27138-31-4	oral				333 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (freshwater)		0,0037 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (intermittent releases)		0,037 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (marine water)		0,00037 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	sediment (freshwater)				11,7 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	sediment (freshwater)				1,17 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	Soil				2,33 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	Predator						no potential for bioaccumulation

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Oxydipropyl dibenzoate 27138-31-4	Workers	dermal	Acute/short term exposure - systemic effects		170 mg/kg	
Oxydipropyl dibenzoate 27138-31-4	Workers	Inhalation	Acute/short term exposure - systemic effects		35,08 mg/m3	
Oxydipropyl dibenzoate 27138-31-4	Workers	Inhalation	Long term exposure - systemic effects		8,8 mg/m3	
Oxydipropyl dibenzoate 27138-31-4	Workers	dermal	Long term exposure - systemic effects		10 mg/kg	
Oxydipropyl dibenzoate 27138-31-4	General population	dermal	Acute/short term exposure - systemic effects		80 mg/kg	
Oxydipropyl dibenzoate 27138-31-4	General population	Inhalation	Acute/short term exposure - systemic effects		8,7 mg/m3	
Oxydipropyl dibenzoate 27138-31-4	General population	oral	Acute/short term exposure - systemic effects		80 mg/kg	
Oxydipropyl dibenzoate 27138-31-4	General population	dermal	Long term exposure - systemic effects		0,22 mg/kg	
Oxydipropyl dibenzoate 27138-31-4	General population	Inhalation	Long term exposure - systemic effects		8,69 mg/m3	
Oxydipropyl dibenzoate 27138-31-4	General population	oral	Long term exposure - systemic effects		5 mg/kg	
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	inhalation	Long term exposure - local effects		0,05 mg/m3	no potential for bioaccumulation
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	inhalation	Acute/short term exposure - local effects		0,1 mg/m3	no potential for bioaccumulation
4,4'- methylenediphenyl diisocyanate 101-68-8	General population	inhalation	Long term exposure - local effects		0,025 mg/m3	no potential for bioaccumulation
4,4'- methylenediphenyl diisocyanate 101-68-8	General population	inhalation	Acute/short term exposure - local effects		0,05 mg/m3	no potential for bioaccumulation

**Biological Exposure Indices:**

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
4,4'-Methylenediphenyl diisocyanate 101-68-8	4,4'-Diaminodiphenylmethane	Creatinine in urine	Sampling time: End of shift.	10 µg/g	DE BAT	BAT values reflect the total physical load of workplace substances absorbed through inhalation, dermally, etc. With occupational exposure to MDI, parameter 4,4'-Diaminodiphenylmethane (MDA) in the urine covers all components of a complex MDI mixture, since both monomers and oligomers of the MDI are degraded independent of the exposure path of the monomeric MDI. In contrast, the MAK value for MDI takes into account only the monomer MDI portion.	

**8.2. Exposure controls:**

Engineering controls:

Use only in well ventilated areas.

Respiratory protection:

The product should only be used at workplaces with intensive ventilation/extraction.

If intensive ventilation/extraction is not possible respiratory protection equipment with ABEK P2 filter (EN 14387) should be worn.



**Hand protection:**

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Protective goggles

Protective eye equipment should conform to EN166.

**Skin protection:**

Wear protective equipment.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Advices to personal protection equipment:**

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Delivery form	paste
Colour	black
Odor	Faintly, specific
Physical state	solid
Melting point	Not applicable, Determination technically not possible
Solidification temperature	Not applicable, Product is a solid.
Initial boiling point	Not applicable, Decomposes $> 140^{\circ}\text{C}$ ( $284^{\circ}\text{F}$ ).
Flammability	The product is not flammable.
Explosive limits	Not applicable, Product is a solid.
Flash point	; no method / method unknown No flash point up to $100^{\circ}\text{C}$
Auto-ignition temperature	Not applicable, Product is a solid.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product reacts with water.
Viscosity (kinematic)	Not applicable, Product is a solid.
Viscosity, dynamic (; $20^{\circ}\text{C}$ ( $68^{\circ}\text{F}$ ); Conc.: 100 % product)	$3.500\text{ Pa}\cdot\text{s}$ Dummy
Solubility (qualitative) ( $20^{\circ}\text{C}$ ( $68^{\circ}\text{F}$ ); Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure ( $20^{\circ}\text{C}$ ( $68^{\circ}\text{F}$ ))	Mixture $< 0,1\text{ hPa}$
Density ( $20^{\circ}\text{C}$ ( $68^{\circ}\text{F}$ ))	$1,22 - 1,27\text{ g/cm}^3$ no method / method unknown
Relative vapour density:	Not applicable, Product is a solid.
Particle characteristics	Not applicable, mixture is a paste.

### 9.2. Other information

Other information not applicable for this product

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None if used for intended purpose.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

None if used for intended purpose.

### 10.5. Incompatible materials

None if used properly.

### 10.6. Hazardous decomposition products

No decomposition if used according to specifications.

## SECTION 11: Toxicological information

### General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	Acute toxicity estimate (ATE)	> 5.000 mg/kg		Expert judgement
Oxydipropyl dibenzoate 27138-31-4	LD50	3.914 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	LD50	> 2.000 mg/kg	rat	other guideline:

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Oxydipropyl dibenzoate 27138-31-4	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	Acute toxicity estimate (ATE)	1,5 mg/l	dust/mist	4 h		Expert judgement
Oxydipropyl dibenzoate 27138-31-4	LC50	> 200 mg/l	dust/mist	4 h	rat	not specified

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Oxydipropyl dibenzoate 27138-31-4	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
4,4'- methylenediphenyl diisocyanate 101-68-8	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Oxydipropyl dibenzoate 27138-31-4	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
4,4'- methylenediphenyl diisocyanate 101-68-8	irritating		human	Weight of evidence

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	sensitising	Respiratory sensitisation	guinea pig	not specified
Oxydipropyl dibenzoate 27138-31-4	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
4,4'- methylenediphenyl diisocyanate 101-68-8	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
4,4'- methylenediphenyl diisocyanate 101-68-8	sensitising	Respiratory sensitisation	guinea pig	not specified

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Oxydipropyl dibenzoate 27138-31-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Oxydipropyl dibenzoate 27138-31-4	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Oxydipropyl dibenzoate 27138-31-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	carcinogenic	inhalation: aerosol	2 y 6 h/d	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Oxydipropyl dibenzoate 27138-31-4	NOAEL P > 10000 ppm  NOAEL F1 10000 ppm  NOAEL F2 10000 ppm	Two generation study	oral: feed	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

**STOT-single exposure:**

No data available.

**STOT-repeated exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	NOAEL 0,0002 mg/l	inhalation: aerosol	2 years 6 h/d; 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Oxydipropyl dibenzoate 27138-31-4	NOAEL 1.000 mg/kg	oral: feed	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOAEL 0,0002 mg/l	inhalation: aerosol	main: 2 y; satellite:1 y 6 h/d; 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

**Aspiration hazard:**

No data available.

**11.2 Information on other hazards**

not applicable

**SECTION 12: Ecological information****General ecological information:**

Do not empty into drains, soil or bodies of water.

**12.1. Toxicity****Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatobenzene] 59675-67-1	LC50	> 1.000 mg/l	96 h	not specified	not specified
Oxydipropyl dibenzoate 27138-31-4	LC50	3,7 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	LL50	> 100 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)

**Toxicity (aquatic invertebrates):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatobenzene] 59675-67-1	EC50	> 1.000 mg/l	48 h	not specified	not specified
Oxydipropyl dibenzoate 27138-31-4	EL50	19,3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	EC50	> 100 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)

**Chronic toxicity (aquatic invertebrates):**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Oxydipropyl dibenzoate 27138-31-4	NOEC	2,2 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	NOEC	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

**Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatobenzene] 59675-67-1	EC50	> 1.640 mg/l	72 h	not specified	not specified
Oxydipropyl dibenzoate 27138-31-4	EL50	4,9 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Oxydipropyl dibenzoate 27138-31-4	EL10	0,89 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	EL50	> 100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOELR	100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatobenzene] 59675-67-1	IC50	> 100 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Oxydipropyl dibenzoate 27138-31-4	EC50	> 100 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	EC50	> 1.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

#### 12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Oxydipropyl dibenzoate 27138-31-4	readily biodegradable	aerobic	85 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

#### 12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	92 - 200	28 d		Cyprinus carpio	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)

#### 12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Oxydipropyl dibenzoate 27138-31-4	3,9	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
4,4'- methylenediphenyl diisocyanate 101-68-8	4,51	22 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

#### 12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Hexanedioic acid, polymer with 1,6-hexanediol and 1,1'-methylenebis[4-isocyanatobenzene] 31075-20-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Oxydipropyl dibenzoate 27138-31-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
4,4'- methylenediphenyl diisocyanate 101-68-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

#### 12.6. Endocrine disrupting properties

not applicable

#### 12.7. Other adverse effects

No data available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.



## SECTION 14: Transport information

- 14.1. UN number or ID number**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Maritime transport in bulk according to IMO instruments**  
not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	0,3 %

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

### National regulations/information (Germany):

WGK: WGK 1: slightly hazardous to water (Ordinance on facilities for handling substances that are hazardous to water (AwSV) )  
Classification according to AwSV, Annex 1 (5.2)

BG regulations, rules, infos:

BG data sheet: BGI 524 Hazardous substances: polyurethane production and processing / isocyanates (M 044)

Storage class according to TRGS 510: 11

## SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

### Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**