



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 24

TEROSON VR 625 400ML DE/PL/HUCZ

SDS No. : 563063  
V004.0

Revision: 14.09.2023

printing date: 18.09.2023

Replaces version from: 26.04.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TEROSON VR 625 400ML DE/PL/HUCZ

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Rust converter

#### 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

[SDSinfo.Adhesive@henkel.com](mailto:SDSinfo.Adhesive@henkel.com)

#### 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Aerosols	Category 1
H222 Extremely flammable aerosol.	
H229 Pressurized container: May burst if heated.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Serious eye damage	Category 1
H318 Causes serious eye damage.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Specific target organ toxicity - repeated exposure	Category 2
H373 May cause damage to organs through prolonged or repeated exposure.	

**2.2. Label elements****Label elements (CLP):****Hazard pictogram:****Contains**

Reaction mass of ethylbenzene and xylene

acetone

butan-1-ol

Bisphenol A diglycidyl ether-bisphenol A copolymer

**Signal word:**

Danger

**Hazard statement:**

H222 Extremely flammable aerosol.  
 H229 Pressurized container: May burst if heated.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statement:  
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P260 Do not breathe spray.  
 P280 Wear protective gloves/eye protection.

**Precautionary statement:  
Response**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER or doctor/ physician.

**Precautionary statement:  
Storage**

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50.DEGREE.C/122.DEGREE.F.

**2.3. Other hazards**

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

The solvent vapors are heavier than air and may collect in high concentrations at floor level.

Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
dimethyl ether 115-10-6 204-065-8 01-2119472128-37	25- < 50 %	Flam. Gas 1A, H220 Press. Gas Liquef. Gas, H280		EU OEL
acetone 67-64-1 200-662-2 01-2119471330-49	10- < 25 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336		EU OEL EUEXPL2D
Reaction mass of ethylbenzene and xylene  905-588-0 01-2119486136-34 01-2119488216-32 01-2119539452-40	10- < 25 %	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, Dermal, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, Inhalation, H332 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412		
butan-1-ol 71-36-3 200-751-6 01-2119484630-38	3- < 10 %	Flam. Liq. 3, H226 Acute Tox. 4, Oral, H302 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336		
Propan-2-ol 67-63-0 200-661-7 01-2119457558-25	2,5- < 10 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336		
Tannins 1401-55-4 215-753-2	2,5- < 10 %	Skin Irrit. 2, Dermal, H315 Eye Irrit. 2, H319 Aquatic Chronic 3, H412		
1-methoxy-2-propanol 107-98-2 203-539-1 01-2119457435-35	2,5- < 10 %	Flam. Liq. 3, H226 STOT SE 3, H336		EU OEL
Bisphenol A diglycidyl ether- bisphenol A copolymer 25036-25-3	1- < 2,5 %	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319		

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

The hazard classification of this product is based solely on the mixture present within the aerosol, excluding the propellant gases. The information provided in Section 3 is based on the combination of the mixture and propellant gases.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Inhalation:

Fresh air, oxygen supply, warmth; seek specialist medical attention.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water.

In case of adverse health effects seek medical advice.

**Eye contact:**

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

**Ingestion:**

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

SKIN: Rash, Urticaria.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

Vapors may cause drowsiness and dizziness.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media:**

Carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

Water jet (solvent-containing product).

**5.2. Special hazards arising from the substance or mixture**

In case of fire toxic gases can be released.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus.

Wear protective equipment.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

Danger of slipping on spilled product.

**6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

**6.3. Methods and material for containment and cleaning up**

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

**6.4. Reference to other sections**

See advice in section 8

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

- Ground/bond container and receiving equipment.
- Use explosion proof electric equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid open flames and sources of ignition.

## Hygiene measures:

- Wash hands before work breaks and after finishing work.
- Do not eat, drink or smoke while working.
- Take off contaminated clothing and wash before reuse.

**7.2. Conditions for safe storage, including any incompatibilities**

- Ensure good ventilation/extraction.
- Storage at 10 to 35°C is recommended.
- Do not store or use near heat, spark, open flame or other sources of ignition.
- Store in a cool place.
- Keep away from heat and direct sunlight.
- Keep container in a well ventilated place.
- Ensure that storage and workrooms are adequately ventilated.

**7.3. Specific end use(s)**

Rust converter

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational Exposure Limits

Valid for  
Germany

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Dimethyl ether 115-10-6 [DIMETHYLETHER]	1.000	1.920	Time Weighted Average (TWA):	Indicative	ECLTV
Dimethyl ether 115-10-6	1.000	1.900	Exposure limit(s):	8	TRGS 900
Dimethyl ether 115-10-6			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Acetone 67-64-1 [ACETONE]	500	1.210	Time Weighted Average (TWA):	Indicative	ECLTV
Acetone 67-64-1	500	1.200	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Acetone 67-64-1			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Propan-2-ol 67-63-0			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Propan-2-ol 67-63-0	200	500	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
1-Methoxypropan-2-ol 107-98-2 [1-METHOXYPROPANOL-2]	100	375	Time Weighted Average (TWA):	Indicative	ECLTV
1-Methoxypropan-2-ol 107-98-2 [1-METHOXYPROPANOL-2]	150	568	Short Term Exposure Limit (STEL):	Indicative	ECLTV
1-Methoxypropan-2-ol 107-98-2	100	370	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
1-Methoxypropan-2-ol 107-98-2			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Butan-1-ol 71-36-3			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Butan-1-ol 71-36-3	100	310	Exposure limit(s):	1 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Dimethyl ether 115-10-6	aqua (freshwater)		0,155 mg/l				
Dimethyl ether 115-10-6	sediment (freshwater)				0,681 mg/kg		
Dimethyl ether 115-10-6	Soil				0,045 mg/kg		
Dimethyl ether 115-10-6	sewage treatment plant (STP)		160 mg/l				
Dimethyl ether 115-10-6	aqua (marine water)		0,016 mg/l				
Dimethyl ether 115-10-6	aqua (intermittent releases)		1,549 mg/l				
Dimethyl ether 115-10-6	sediment (marine water)				0,069 mg/kg		
acetone 67-64-1	aqua (intermittent releases)		21 mg/l				
acetone 67-64-1	sewage treatment plant (STP)		100 mg/l				
acetone 67-64-1	sediment (freshwater)				30,4 mg/kg		
acetone 67-64-1	sediment (marine water)				3,04 mg/kg		
acetone 67-64-1	Soil				29,5 mg/kg		
acetone 67-64-1	aqua (freshwater)		10,6 mg/l				
acetone 67-64-1	aqua (marine water)		1,06 mg/l				
Reaction mass of ethylbenzene and xylene	aqua (freshwater)		0,327 mg/l				
Reaction mass of ethylbenzene and xylene	aqua (marine water)		0,327 mg/l				
Reaction mass of ethylbenzene and xylene	sewage treatment plant (STP)		6,58 mg/l				
Reaction mass of ethylbenzene and xylene	sediment (freshwater)				12,46 mg/kg		
Reaction mass of ethylbenzene and xylene	sediment (marine water)				12,46 mg/kg		
Reaction mass of ethylbenzene and xylene	soil				2,31 mg/kg		
butan-1-ol 71-36-3	aqua (freshwater)		0,082 mg/l				
butan-1-ol 71-36-3	aqua (marine water)		0,0082 mg/l				
butan-1-ol 71-36-3	aqua (intermittent releases)		2,25 mg/l				
butan-1-ol 71-36-3	sewage treatment plant (STP)		2476 mg/l				
butan-1-ol 71-36-3	sediment (freshwater)				0,324 mg/kg		
butan-1-ol 71-36-3	sediment (marine water)				0,032 mg/kg		
butan-1-ol 71-36-3	Soil				0,017 mg/kg		
butan-1-ol 71-36-3	Air						no hazard identified
butan-1-ol 71-36-3	oral						no potential for bioaccumulation
Propan-2-ol 67-63-0	aqua (freshwater)		140,9 mg/l				
Propan-2-ol 67-63-0	aqua (marine water)		140,9 mg/l				

Propan-2-ol 67-63-0	sediment (freshwater)				552 mg/kg		
Propan-2-ol 67-63-0	sediment (marine water)				552 mg/kg		
Propan-2-ol 67-63-0	Soil				28 mg/kg		
Propan-2-ol 67-63-0	aqua (intermittent releases)		140,9 mg/l				
Propan-2-ol 67-63-0	sewage treatment plant (STP)		2251 mg/l				
Propan-2-ol 67-63-0	oral				160 mg/kg		
1-methoxy-2-propanol 107-98-2	aqua (freshwater)		10 mg/l				
1-methoxy-2-propanol 107-98-2	aqua (marine water)		1 mg/l				
1-methoxy-2-propanol 107-98-2	aqua (intermittent releases)		100 mg/l				
1-methoxy-2-propanol 107-98-2	sediment (freshwater)				52,3 mg/kg		
1-methoxy-2-propanol 107-98-2	sediment (marine water)				5,2 mg/kg		
1-methoxy-2-propanol 107-98-2	Soil				4,59 mg/kg		
1-methoxy-2-propanol 107-98-2	sewage treatment plant (STP)		100 mg/l				



**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
acetone 67-64-1	Workers	Inhalation	Acute/short term exposure - local effects		2420 mg/m <sup>3</sup>	
acetone 67-64-1	Workers	dermal	Long term exposure - systemic effects		186 mg/kg	
acetone 67-64-1	Workers	Inhalation	Long term exposure - systemic effects		1210 mg/m <sup>3</sup>	
acetone 67-64-1	General population	dermal	Long term exposure - systemic effects		62 mg/kg	
acetone 67-64-1	General population	Inhalation	Long term exposure - systemic effects		200 mg/m <sup>3</sup>	
acetone 67-64-1	General population	oral	Long term exposure - systemic effects		62 mg/kg	
Reaction mass of ethylbenzene and xylene	Workers	inhalation	Long term exposure - systemic effects		221 mg/m <sup>3</sup>	
Reaction mass of ethylbenzene and xylene	Workers	inhalation	Long term exposure - local effects		221 mg/m <sup>3</sup>	
Reaction mass of ethylbenzene and xylene	Workers	dermal	Long term exposure - systemic effects		212 mg/kg	
Reaction mass of ethylbenzene and xylene	General population	inhalation	Long term exposure - systemic effects		65,3 mg/m <sup>3</sup>	
Reaction mass of ethylbenzene and xylene	General population	dermal	Long term exposure - systemic effects		125 mg/kg	
Reaction mass of ethylbenzene and xylene	General population	oral	Long term exposure - systemic effects		12,5 mg/kg	
Reaction mass of ethylbenzene and xylene	Workers	inhalation	Acute/short term exposure - systemic effects		442 mg/m <sup>3</sup>	
Reaction mass of ethylbenzene and xylene	Workers	inhalation	Acute/short term exposure - local effects		442 mg/m <sup>3</sup>	
Reaction mass of ethylbenzene and xylene	General population	inhalation	Acute/short term exposure - systemic effects		260 mg/m <sup>3</sup>	
Reaction mass of ethylbenzene and xylene	General population	inhalation	Long term exposure - local effects		65,3 mg/m <sup>3</sup>	
Reaction mass of ethylbenzene and xylene	General population	inhalation	Acute/short term exposure - local effects		260 mg/m <sup>3</sup>	
butan-1-ol 71-36-3	Workers	Inhalation	Long term exposure - local effects		310 mg/m <sup>3</sup>	no hazard identified
butan-1-ol 71-36-3	General population	dermal	Long term exposure - systemic effects		3,125 mg/kg	no hazard identified
butan-1-ol 71-36-3	General population	Inhalation	Long term exposure - systemic effects		55,357 mg/m <sup>3</sup>	no hazard identified
butan-1-ol 71-36-3	General population	inhalation	Long term exposure - local effects		155 mg/m <sup>3</sup>	no hazard identified
butan-1-ol 71-36-3	General population	oral	Long term exposure - systemic effects		1,562 mg/kg	no hazard identified
Propan-2-ol 67-63-0	Workers	dermal	Long term exposure - systemic effects		888 mg/kg	
Propan-2-ol 67-63-0	Workers	inhalation	Long term exposure -		500 mg/m <sup>3</sup>	

			systemic effects			
Propan-2-ol 67-63-0	General population	dermal	Long term exposure - systemic effects		319 mg/kg	
Propan-2-ol 67-63-0	General population	inhalation	Long term exposure - systemic effects		89 mg/m3	
Propan-2-ol 67-63-0	General population	oral	Long term exposure - systemic effects		26 mg/kg	
1-methoxy-2-propanol 107-98-2	Workers	Inhalation	Acute/short term exposure - local effects		553,5 mg/m3	
1-methoxy-2-propanol 107-98-2	Workers	dermal	Long term exposure - systemic effects		183 mg/kg	
1-methoxy-2-propanol 107-98-2	Workers	Inhalation	Long term exposure - systemic effects		369 mg/m3	
1-methoxy-2-propanol 107-98-2	General population	dermal	Long term exposure - systemic effects		78 mg/kg	
1-methoxy-2-propanol 107-98-2	General population	Inhalation	Long term exposure - systemic effects		43,9 mg/m3	
1-methoxy-2-propanol 107-98-2	General population	oral	Long term exposure - systemic effects		33 mg/kg	
1-methoxy-2-propanol 107-98-2	Workers	inhalation	Acute/short term exposure - systemic effects		553,5 mg/m3	

### Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Acetone 67-64-1	acetone	Urine	Sampling time: End of shift.	80 mg/l	DE BGW		
Propan-2-ol 67-63-0	acetone	Blood	Sampling time: End of shift.	25 mg/l	DE BGW		
Propan-2-ol 67-63-0 [2-PROPANOL]	acetone	Urine	Sampling time: End of shift.	25 mg/l	DE BGW		
1-Methoxypropan-2-ol 107-98-2	1-Methoxypropan-2-ol	Urine	Sampling time: End of shift.	15 mg/l	DE BGW		
Butan-1-ol 71-36-3	1-butanol	Creatinine in urine	Sampling time: Prior to shift.	2 mg/g	DE BAT		
Butan-1-ol 71-36-3	1-butanol	Creatinine in urine	Sampling time: End of shift.	10 mg/g	DE BAT		
Butan-1-ol 71-36-3	1-Butanol (with hydrolysis)	Urine	Sampling time: Before the next shift.	2 mg/g	DE BGW		
[Butan-1-ol (1-Butanol)] Butan-1-ol 71-36-3 [Butan-1-ol (1-Butanol)]	1-Butanol (with hydrolysis)	Urine	Sampling time: End of work week.	10 mg/g	DE BGW		

### 8.2. Exposure controls:

Engineering controls:  
Use only in well ventilated areas.

Respiratory protection:  
In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).  
This recommendation should be matched to local conditions.

**Hand protection:**

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR;  $\geq 0.7$  mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR;  $\geq 0.7$  mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Goggles which can be tightly sealed.  
Protective eye equipment should conform to EN166.

**Skin protection:**

Wear protective equipment.  
Protective clothing that covers arms and legs.  
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Advices to personal protection equipment:**

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Delivery form	aerosol
Colour	light brown
Odor	characteristic
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	Not available.
Initial boiling point	-24,8 °C (-12.6 °F)
Flammability	Extremely flammable aerosol.
Explosive limits	
lower	1,1 % (V);
upper	20,0 % (V);
Flash point	-42 °C (-43.6 °F)
Auto-ignition temperature	235 °C (455 °F)
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	2,5
(20 °C (68 °F); Conc.: 100 % product)	
Viscosity (kinematic)	$\leq 20,5$ mm <sup>2</sup> /s
(40 °C (104 °F); )	
Solubility (qualitative)	Not miscible or difficult to mix
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure	Mixture
(20 °C (68 °F))	3300 hPa
Vapour pressure	
(50 °C (122 °F))	6500 hPa
Density	
(20 °C (68 °F))	0,794 g/cm <sup>3</sup> no method / method unknown
Relative vapour density:	Not available.
Particle characteristics	Not applicable
	Product is a liquid

**9.2. Other information****9.2.1. Information with regard to physical hazard classes**

Aerosols: Classified as Aerosol category 1 because it contains more

than 1 % (by mass) flammable components or has a heat of combustion of at least 20 kJ/g and is not submitted to the flammability classification procedures

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Oxidizers.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Heat, flames, sparks and other sources of ignition.

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

No decomposition if used according to specifications.

## SECTION 11: Toxicological information

### General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
acetone 67-64-1	LD50	5.800 mg/kg	rat	not specified
Reaction mass of ethylbenzene and xylene	LD50	3.523 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))
butan-1-ol 71-36-3	LD50	790 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Propan-2-ol 67-63-0	LD50	5.840 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Tannins 1401-55-4	LD50	2.260 mg/kg	rat	not specified
1-methoxy-2-propanol 107-98-2	LD50	3.739 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))
Bisphenol A diglycidyl ether-bisphenol A copolymer 25036-25-3	LD50	> 2.000 mg/kg	rat	not specified

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
acetone 67-64-1	LD50	> 15.688 mg/kg	rabbit	Draize Test
butan-1-ol 71-36-3	LD50	3.430 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Propan-2-ol 67-63-0	LD50	12.870 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
1-methoxy-2-propanol 107-98-2	LD50	> 2.000 mg/kg	rat	EU Method B.3 (Acute Toxicity (Dermal))
Bisphenol A diglycidyl ether-bisphenol A copolymer 25036-25-3	LD50	> 2.000 mg/kg	rat	not specified

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
dimethyl ether 115-10-6	LC50	164000 ppm	gas	4 h	rat	not specified
acetone 67-64-1	LC50	76 mg/l	vapour	4 h	rat	not specified
butan-1-ol 71-36-3	LC50	> 17,76 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
1-methoxy-2-propanol 107-98-2	LC50	55 mg/l	vapour	4 h	rat	not specified

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
acetone 67-64-1	not irritating		guinea pig	not specified
Reaction mass of ethylbenzene and xylene	moderately irritating		rabbit	not specified
butan-1-ol 71-36-3	irritating	2 h	rabbit	not specified
Propan-2-ol 67-63-0	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1-methoxy-2-propanol 107-98-2	not irritating	4 h	rabbit	EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
acetone 67-64-1	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Reaction mass of ethylbenzene and xylene	moderately irritating		rabbit	not specified
butan-1-ol 71-36-3	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Propan-2-ol 67-63-0	Category II		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1-methoxy-2-propanol 107-98-2	not irritating		rabbit	EU Method B.5 (Acute Toxicity: Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

<b>Hazardous substances CAS-No.</b>	<b>Result</b>	<b>Test type</b>	<b>Species</b>	<b>Method</b>
acetone 67-64-1	not sensitising	Guinea pig maximisation test	guinea pig	not specified
Reaction mass of ethylbenzene and xylene	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
butan-1-ol 71-36-3	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
1-methoxy-2-propanol 107-98-2	not sensitising	Guinea pig maximisation test	guinea pig	EU Method B.6 (Skin Sensitisation)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

<b>Hazardous substances CAS-No.</b>	<b>Result</b>	<b>Type of study / Route of administration</b>	<b>Metabolic activation / Exposure time</b>	<b>Species</b>	<b>Method</b>
dimethyl ether 115-10-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
dimethyl ether 115-10-6	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
dimethyl ether 115-10-6	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
acetone 67-64-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
acetone 67-64-1	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
acetone 67-64-1	negative	mammalian cell gene mutation assay	without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Reaction mass of ethylbenzene and xylene	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Reaction mass of ethylbenzene and xylene	negative	in vitro mammalian chromosome aberration test	with and without		EU Method B.10 (Mutagenicity)
Reaction mass of ethylbenzene and xylene	negative	sister chromatid exchange assay in mammalian cells	with and without		EU Method B.19 (Sister Chromatid Exchange Assay In Vitro)
butan-1-ol 71-36-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		Ames Test
butan-1-ol 71-36-3	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
butan-1-ol 71-36-3	negative	in vitro mammalian cell micronucleus test	without		not specified
Propan-2-ol 67-63-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1-methoxy-2-propanol 107-98-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1-methoxy-2-propanol 107-98-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
1-methoxy-2-propanol 107-98-2	negative	mammalian cell gene mutation assay	without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
dimethyl ether 115-10-6	not carcinogenic	inhalation	2 y 6 h/d, 5 d/w	rat	male/female	equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
acetone 67-64-1	not carcinogenic	dermal	424 d 3 times per week	mouse	female	not specified
Reaction mass of ethylbenzene and xylene	not carcinogenic	oral: gavage	103 w 5 d/w	rat	male/female	EU Method B.32 (Carcinogenicity Test)
Propan-2-ol 67-63-0		inhalation: vapour	104 w 6 h/d, 5 d/w	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)
1-methoxy-2-propanol 107-98-2	not carcinogenic	inhalation: vapour	2 y 6 hr/day, 5 days/wk	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
dimethyl ether 115-10-6	NOAEL P 2.5 %	other	inhalation: gas	rat	other guideline:
dimethyl ether 115-10-6	NOAEL P 1.6 %	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Reaction mass of ethylbenzene and xylene	NOAEL P 500 ppm NOAEL F1 500 ppm	one-generation study	inhalation: vapour	rat	not specified
butan-1-ol 71-36-3	NOAEL P 500 mg/kg	Two generation study	oral: gavage	rat	not specified
butan-1-ol 71-36-3	NOAEL P 2000 ppm NOAEL F1 2000 ppm	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Propan-2-ol 67-63-0	NOAEL P 853 mg/kg	One generation study	oral: drinking water	rat	equivalent or similar to OECD Guideline 415 (One-Generation Reproduction Toxicity Study)
Propan-2-ol 67-63-0	NOAEL P 500 mg/kg NOAEL F1 1.000 mg/kg	Two generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
1-methoxy-2-propanol 107-98-2	NOAEL P 300 ppm NOAEL F1 1000 ppm NOAEL F2 1000 ppm	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

**STOT-single exposure:**

No data available.



**STOT-repeated exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
dimethyl ether 115-10-6	NOAEL 47,106 mg/l NOAEL 2.5 %	inhalation: gas	2 y 6 h/d; 5 d/w	rat	equivalent or similar to OECD Guideline 452 (Chronic Toxicity Studies)
acetone 67-64-1	NOAEL 900 mg/kg	oral: drinking water	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Reaction mass of ethylbenzene and xylene	NOAEL 250 mg/kg	oral: gavage	103 w 5 d/w	rat	other guideline:
Reaction mass of ethylbenzene and xylene	NOAEL 150 mg/kg	oral: gavage	90 days daily	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
butan-1-ol 71-36-3	NOAEL 125 mg/kg	oral: gavage	13 w daily	rat	not specified
Propan-2-ol 67-63-0		inhalation: vapour	104 w 6 h/d; 5 d/w	rat	OECD Guideline 451 (Carcinogenicity Studies)
1-methoxy-2-propanol 107-98-2	NOAEL 1000 ppm	inhalation	13 weeks 6 hours/day; 5 days/week	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
1-methoxy-2-propanol 107-98-2	NOAEL 919 mg/kg	oral: gavage	35 d 5 d/w	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

**Aspiration hazard:**

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Reaction mass of ethylbenzene and xylene	< 0,9 mm <sup>2</sup> /s	20 °C	not specified	
Propan-2-ol 67-63-0	1,8 mm <sup>2</sup> /s	40 °C	ASTM Standard D7042	

**11.2 Information on other hazards**

not applicable

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains, soil or bodies of water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
dimethyl ether 115-10-6	LC50	> 4.000 mg/l	96 h	Poecilia reticulata	OECD Guideline 203 (Fish, Acute Toxicity Test)
acetone 67-64-1	LC50	8.120 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction mass of ethylbenzene and xylene	LC50	2,6 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction mass of ethylbenzene and xylene	NOEC	> 1,3 mg/l	56 d	Oncorhynchus mykiss	other guideline:
butan-1-ol 71-36-3	LC50	1.376 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propan-2-ol 67-63-0	LC50	> 9.640 - 10.000 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Tannins 1401-55-4	LC50	37 mg/l	96 h	Gambusia affinis	OECD Guideline 203 (Fish, Acute Toxicity Test)
1-methoxy-2-propanol 107-98-2	LC50	20.800 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)

#### Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
dimethyl ether 115-10-6	EC50	> 4.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
acetone 67-64-1	EC50	8.800 mg/l	48 h	Daphnia pulex	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Reaction mass of ethylbenzene and xylene	IC50	> 1 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
butan-1-ol 71-36-3	EC50	1.328 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1-methoxy-2-propanol 107-98-2	EC50	23.300 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
acetone 67-64-1	NOEC	2.212 mg/l	28 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Reaction mass of ethylbenzene and xylene	NOEC	1,17 mg/l	7 d	Ceriodaphnia dubia	other guideline:
butan-1-ol 71-36-3	NOEC	4,1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Propan-2-ol	NOEC	30 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia

67-63-0					magna, Reproduction Test)
---------	--	--	--	--	---------------------------

**Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
dimethyl ether 115-10-6	EC50	> 1.000 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
acetone 67-64-1	NOEC	530 mg/l	8 d	Microcystis aeruginosa	DIN 38412-09
Reaction mass of ethylbenzene and xylene	EC50	4,36 mg/l	73 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass of ethylbenzene and xylene	NOEC	0,44 mg/l	73 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
butan-1-ol 71-36-3	EC50	225 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
butan-1-ol 71-36-3	NOEC	129 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	NOEC	1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1-methoxy-2-propanol 107-98-2	EC50	> 1.000 mg/l	7 d	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

**Toxicity (microorganisms):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
dimethyl ether 115-10-6	EC10	> 1.600 mg/l	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
acetone 67-64-1	EC10	1.000 mg/l	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
Reaction mass of ethylbenzene and xylene	NOEC	157 mg/l	3 h	activated sludge, domestic	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
butan-1-ol 71-36-3	EC10	2.476 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
1-methoxy-2-propanol 107-98-2	EC0	> 1.000 mg/l	30 min		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

**12.2. Persistence and degradability**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
dimethyl ether 115-10-6	readily biodegradable	aerobic	> 60 %	28 d	OECD 301 A - F
acetone 67-64-1	readily biodegradable	aerobic	81 - 92 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
Reaction mass of ethylbenzene and xylene	readily biodegradable	aerobic	87,8 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
butan-1-ol 71-36-3	readily biodegradable	aerobic	70 - 81 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
Propan-2-ol 67-63-0	readily biodegradable	aerobic	70 - 84 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
1-methoxy-2-propanol 107-98-2	readily biodegradable	aerobic	90 %	29 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)

### 12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Reaction mass of ethylbenzene and xylene	25,9	56 d		Oncorhynchus mykiss	other guideline:

**12.4. Mobility in soil**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
dimethyl ether 115-10-6	0,07	25 °C	QSAR (Quantitative Structure Activity Relationship)
acetone 67-64-1	-0,24		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Reaction mass of ethylbenzene and xylene	3,16	20 °C	other guideline:
butan-1-ol 71-36-3	1	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Propan-2-ol 67-63-0	0,05		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
1-methoxy-2-propanol 107-98-2	-0,49		not specified

**12.5. Results of PBT and vPvB assessment**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
dimethyl ether 115-10-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
acetone 67-64-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Reaction mass of ethylbenzene and xylene	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
butan-1-ol 71-36-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Propan-2-ol 67-63-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
1-methoxy-2-propanol 107-98-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**12.6. Endocrine disrupting properties**

not applicable

**12.7. Other adverse effects**

No data available.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

## SECTION 14: Transport information

### 14.1. UN number or ID number

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

### 14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS
IATA	Aerosols, flammable

### 14.3. Transport hazard class(es)

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

### 14.4. Packing group

ADR  
RID  
ADN  
IMDG  
IATA

### 14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

### 14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	85 %

**VOC Paints and Varnishes (EU):**

Regulatory Basis:	Directive 2004/42/EC
Product (sub)category:	B(a) Preparatory and cleaning products
Phase I (from 1.1.2007):	850,00 g/l
max. VOC content:	676 g/l

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**National regulations/information (Germany):**

WGK:	WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV) ) Classification according to AwSV, Annex 1 (5.2)
------	---

BG regulations, rules, infos:

BG data sheet: BGI 621 Solvents  
BG information : Guidance document for the handling of epoxy resins.

Storage class according to TRGS 510: 2B

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

**Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**