



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 13

BONDERITE C-AD 0508

SDS No. : 280517
V006.0

Revision: 01.06.2023

printing date: 05.06.2023

Replaces version from: 18.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

BONDERITE C-AD 0508

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Industrial Cleaning Agents

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

SDSinfo.Adhesive@henkel.com

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye damage

Category 1

H318 Causes serious eye damage.

Chronic hazards to the aquatic environment

Category 3

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Coco amine ethoxylate

Signal word:

Danger

Hazard statement:	H318 Causes serious eye damage. H412 Harmful to aquatic life with long lasting effects.
Precautionary statement: Prevention	P280 Wear eye protection/face protection.
Precautionary statement: Response	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/doctor/...

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Fatty alcohol, C12-14, EO/PO 68439-51-0	20- 40 %	Aquatic Chronic 3, H412		
Coco amine ethoxylate 61791-14-8	10- 20 %	Aquatic Chronic 3, H412 Acute Tox. 4, Oral, H302 Eye Dam. 1, H318		
2-(2-butoxyethoxy)ethanol 112-34-5 203-961-6 01-2119475104-44	10- 20 %	Eye Irrit. 2, H319		EU OEL

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

Declaration of ingredients according to Detergent Regulation 648/2004/EC

> 30 %	non-ionic surfactants
5 - 15 %	amphoteric surfactants

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Immediately wash skin thoroughly with soap and water.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Drink 1-2 glasses of water, do not induce vomiting, administer an antifoaming agent (sab simplex), seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

Water spray jet

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in fires.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

Additional information:

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin and eye contact.

Ensure that workrooms are adequately ventilated.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.
Store in a cool, well-ventilated place.

7.3. Specific end use(s)

Industrial Cleaning Agents

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
2-(2-Butoxyethoxy)ethanol 112-34-5 [2-(2-BUTOXYETHOXY)ETHANOL]	10	67,5	Time Weighted Average (TWA):	Indicative	ECTLV
2-(2-Butoxyethoxy)ethanol 112-34-5 [2-(2-BUTOXYETHOXY)ETHANOL]	15	101,2	Short Term Exposure Limit (STEL):	Indicative	ECTLV
2-(2-Butoxyethoxy)ethanol 112-34-5	10	67	Exposure limit(s):	1.5 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
2-(2-Butoxyethoxy)ethanol 112-34-5			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
2-(2-butoxyethoxy)ethanol 112-34-5	aqua (freshwater)		1,1 mg/l				
2-(2-butoxyethoxy)ethanol 112-34-5	aqua (marine water)		0,11 mg/l				
2-(2-butoxyethoxy)ethanol 112-34-5	Freshwater - intermittent		11 mg/l				
2-(2-butoxyethoxy)ethanol 112-34-5	sediment (freshwater)				4,4 mg/kg		
2-(2-butoxyethoxy)ethanol 112-34-5	sediment (marine water)				0,44 mg/kg		
2-(2-butoxyethoxy)ethanol 112-34-5	oral				56 mg/kg		
2-(2-butoxyethoxy)ethanol 112-34-5	Soil				0,32 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2-(2-butoxyethoxy)ethanol 112-34-5	Workers	inhalation	Acute/short term exposure - local effects		101,2 mg/m ³	
2-(2-butoxyethoxy)ethanol 112-34-5	Workers	inhalation	Long term exposure - local effects		67,5 mg/m ³	
2-(2-butoxyethoxy)ethanol 112-34-5	General population	oral	Long term exposure - systemic effects		6,25 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/suction at the workplace.

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; ≥ 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; ≥ 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Delivery form	liquid
Colour	brownish
Odor	characteristic
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Initial boiling point	100 °C (212 °F)no method / method unknown Aqueous solution
Flammability	The product is not flammable.
Explosive limits	Not applicable, The product is not flammable.
Flash point	Not applicable

Auto-ignition temperature	Not applicable, The product is not flammable.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH (20 °C (68 °F); Conc.: 100 % product)	8,5 PH-value, potentiometer
Viscosity (kinematic)	Currently under determination
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	fully miscible
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure (50 °C (122 °F))	Mixture 103 mbar
Vapour pressure (55 °C (131 °F))	123 mbar
Density (20 °C (68 °F))	1,022 - 1,032 g/cm ³ density, hydrometer
Relative vapour density: (20 °C)	< 1
Particle characteristics	Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong acids.
Reaction with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.
In case of fire toxic gases can be released.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	LD50	> 2.000 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))
Coco amine ethoxylate 61791-14-8	LD50	1.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2-(2- butoxyethoxy)ethanol 112-34-5	LD50	> 2.000 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
2-(2-butoxyethoxy)ethanol 112-34-5	LD50	2.764 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	slightly irritating	4 h	rabbit	EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion)
Fatty alcohol, C12-14, EO/PO 68439-51-0	moderately irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Coco amine ethoxylate 61791-14-8	not irritating	2 h	rabbit	not specified
2-(2-butoxyethoxy)ethanol 112-34-5	not irritating		rabbit	Draize Test

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	slightly irritating	24 h	rabbit	EU Method B.5 (Acute Toxicity: Eye Irritation / Corrosion)
Fatty alcohol, C12-14, EO/PO 68439-51-0	slightly irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2-(2-butoxyethoxy)ethanol 112-34-5	moderately irritating		rabbit	not specified

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	not sensitising	Guinea pig maximisation test	guinea pig	EU Method B.6 (Skin Sensitisation)
2-(2-butoxyethoxy)ethanol 112-34-5	not sensitising	Guinea pig maximisation test	guinea pig	Magnusson and Kligman Method

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-(2- butoxyethoxy)ethanol 112-34-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Carcinogenicity

No data available.

Reproductive toxicity:

No data available.

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	NOAEL 300 mg/kg	oral: gavage	90 days once daily, 5 times a week	rat	EU Method B.26 (Sub- Chronic Oral Toxicity Test: Repeated Dose 90- Day Oral Toxicity Study in Rodents)
2-(2- butoxyethoxy)ethanol 112-34-5	NOAEL < 50 mg/kg	oral: gavage	90 days 5 days/week	rat	not specified
2-(2- butoxyethoxy)ethanol 112-34-5	NOAEL 2 - 6 ppm	inhalation	90 days	rat	not specified
2-(2- butoxyethoxy)ethanol 112-34-5	NOAEL > 2.000 mg/kg	dermal	13 weeks 6 hours/day, 5 days/week	rat	not specified

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

The biodegradability of the surfactants contained in the product is in accordance with the requirements of the EU Detergent Regulation (EC/648/2004).

The surfactants contained in the products are primary biodegradable to at least 90% on average.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	LC50	1,4 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Coco amine ethoxylate 61791-14-8	LC50	> 1 - < 10 mg/l	96 h	Leuciscus idus	DIN 38412-15
2-(2-butoxyethoxy)ethanol 112-34-5	LC50	1.300 mg/l	96 h	Lepomis macrochirus	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	EC50	6,4 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Coco amine ethoxylate 61791-14-8	EC50	27 mg/l	24 h	Daphnia magna	not specified
2-(2-butoxyethoxy)ethanol 112-34-5	EC50	3.300 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

No data available.

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	EC50	> 1 - 10 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)
Fatty alcohol, C12-14, EO/PO 68439-51-0	EC10	> 0,1 - 1 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)
2-(2-butoxyethoxy)ethanol 112-34-5	NOEC	> 100 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-(2-butoxyethoxy)ethanol 112-34-5	EC50	> 100 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	EC0	10 mg/l	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
Coco amine ethoxylate 61791-14-8	EC0	45 mg/l	30 min		not specified
2-(2-butoxyethoxy)ethanol 112-34-5	EC10	> 1.995 mg/l	30 min	activated sludge, industrial	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	readily biodegradable	not specified	> 60 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Coco amine ethoxylate 61791-14-8	readily biodegradable	no data	83 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
2-(2-butoxyethoxy)ethanol 112-34-5	inherently biodegradable	aerobic	100 %	9 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
2-(2-butoxyethoxy)ethanol 112-34-5	readily biodegradable	aerobic	> 60 %	28 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Coco amine ethoxylate 61791-14-8	1,24		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2-(2-butoxyethoxy)ethanol 112-34-5	1	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Fatty alcohol, C12-14, EO/PO 68439-51-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-(2-butoxyethoxy)ethanol 112-34-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

If acidic or alkaline products are discharged into wastewater installations care must be taken that the discharged wastewater has a pH in the range pH 6 - 10, as pH variations could cause disorders in wastewater channels and biological sewage treatment plants. The local discharge regulations take precedence.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

EWC/EAK 070608

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

- 14.1. UN number or ID number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Maritime transport in bulk according to IMO instruments**
not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	0 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK:	WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV)) Classification according to AwSV, Annex 1 (5.2)
Storage class according to TRGS 510:	10

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2:	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.