

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 1

SDS No.: 164639

V005.0

Revision: 07.02.2024

printing date: 08.02.2024

Replaces version from: 29.07.2022

Kit/Multi-component Product

LOCTITE EA M-121HP MEDICAL EPOXY

1. SDS No.439062 - LOCTITE EA M-121HP A

2. SDS No.157227 - LOCTITE EA M-121HP B



LOCTITE EA M-121HP A

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 17

SDS No.: 439062 V005.0

Revision: 07.02.2024

printing date: 08.02.2024

Replaces version from: 07.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE EA M-121HP A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Part A of 2-K-Epoxy Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains R

RP Bisphenol F-epichlorohydrin resin, MW<=700

SDS No.: 439062 V005.0 Page 2 of 17

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Acrylic polymers Dodecane-1-thiol

Signal word: Warning

Hazard statement: H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statement: P273 Avoid release to the environment.

Prevention P280 Wear protective gloves.

Precautionary statement: P302+P352 IF ON SKIN: Wash with plenty of soap and water.

Response P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
RP Bisphenol F-epichlorohydrin resin, MW<=700 28064-14-4	25- 50 %	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Eye Irrit. 2, H319 Aquatic Chronic 2, H411	Skin Irrit. 2; H315; C >= 5 % Eye Irrit. 2; H319; C >= 5 %	
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxir ane 1675-54-3 01-2119456619-26	25- 50 %	Eye Irrit. 2, H319 Aquatic Chronic 2, H411 Skin Sens. 1, H317 Skin Irrit. 2, H315	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 %	
Acrylic polymers 25101-28-4	10- 20 %	Skin Sens. 1, H317 Eye Irrit. 2, H319		
Dodecane-1-thiol 112-55-0 203-984-1 01-2119491318-31	0,01-< 0,1 %	Skin Corr. 1C, H314 Aquatic Chronic 1, H410 Skin Sens. 1A, H317 Eye Dam. 1, H318 Aquatic Acute 1, H400	M acute = 10 M chronic = 10	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the H - statements and other abbreviations see section 16 "Other information".

SDS No.: 439062 V005.0 Page 3 of 17

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eve contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SDS No.: 439062 V005.0 Page 4 of 17

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact. See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.

Protect against contamination.

Ensure that storage and workrooms are adequately ventilated.

Store in a cool, dry place.

Refer to Technical Data Sheet.

7.3. Specific end use(s)

Part A of 2-K-Epoxy Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Germany

None

SDS No.: 439062 V005.0 Page 5 of 17

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value	Value			Remarks
	Сотрытение	periou	mg/l	ppm	mg/kg	others	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	aqua (freshwater)		0,006 mg/l	ppm	mg/ng	others	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Freshwater - intermittent		0,018 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	aqua (marine water)		0,001 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Marine water - intermittent		0,002 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	sewage treatment plant (STP)		10 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	sediment (freshwater)				0,341 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	sediment (marine water)				0,034 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Soil				0,065 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	oral				11 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Air						no hazard identified

SDS No.: 439062 V005.0 Page 6 of 17

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	inhalation	Long term exposure - systemic effects		4,93 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	dermal	Long term exposure - systemic effects		0,75 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	inhalation	Long term exposure - systemic effects		0,87 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	dermal	Long term exposure - systemic effects		0,0893 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	inhalation	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	inhalation	Acute/short term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	dermal	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	dermal	Acute/short term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	inhalation	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	inhalation	Acute/short term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	dermal	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	dermal	Acute/short term exposure - local effects			no hazard identified

SDS No.: 439062 V005.0 Page 7 of 17

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly

ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form liquid

Colour Pale yellow, to, Off white

Odor Faint, Epoxy Physical state liquid

Melting point Not applicable, Product is a liquid

 $\begin{array}{lll} \mbox{Solidification temperature} & < 23 \ ^{\circ}\mbox{C} \ (< 73.4 \ ^{\circ}\mbox{F}) \\ \mbox{Initial boiling point} & > 149,0 \ ^{\circ}\mbox{C} \ (> 300.2 \ ^{\circ}\mbox{F}) \\ \mbox{Flammability} & \mbox{The product is not flammable.} \\ \end{array}$

Explosive limits Not applicable, The product is not flammable. Flash point > 96,11 °C (> 205 °F); Setaflash Closed Cup Auto-ignition temperature Not applicable, The product is not flammable.

Decomposition temperature $> 100 \, ^{\circ}\text{C} (> 212 \, ^{\circ}\text{F});$

pH Not applicable, Product is non-soluble (in water).

Viscosity (kinematic) 20.000 - 80.000 mm2/s

(25 °C (77 °F);)

Viscosity, dynamic Not determined

0

Solubility (qualitative)

Not miscible or difficult to mix

(20 °C (68 °F); Solvent: Water)

SDS No.: 439062 V005.0 Page 8 of 17

Negligible

Partially miscible

1,1 g/cm3 None

Solubility (qualitative)

(20 °C (68 °F); Solvent: ketones)

Solubility (qualitative)

(Solvent: Water)

Partition coefficient: n-octanol/water Not applicable

Mixture Vapour pressure < 0,1 hPa

(20 °C (68 °F)) Density

(20 °C (68 °F))

Relative vapour density: (20 °C)

Particle characteristics Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants. Reaction with strong acids.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
RP Bisphenol F-	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
epichlorohydrin resin,				Toxicity)
MW<=700				
28064-14-4				
2,2'-[(1-	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
methylethylidene)bis(4,1-				
phenyleneoxymethylene)]				
bisoxirane				
1675-54-3				
Acrylic polymers	LD50	> 10.000 mg/kg	mouse	not specified
25101-28-4				
Dodecane-1-thiol	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
112-55-0				

SDS No.: 439062 V005.0 Page 9 of 17

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
RP Bisphenol F-	LD50	> 2.000 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute
epichlorohydrin resin,				Dermal Toxicity)
MW<=700				•
28064-14-4				
2,2'-[(1-	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
methylethylidene)bis(4,1-				
phenyleneoxymethylene)]				
bisoxirane				
1675-54-3				
Dodecane-1-thiol	LD50	> 2.000 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute
112-55-0				Dermal Toxicity)

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
RP Bisphenol F- epichlorohydrin resin, MW<=700 28064-14-4	irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	not irritating	4 h	rabbit	not specified
Dodecane-1-thiol 112-55-0	Category 1C (corrosive)	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	not irritating	time	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
RP Bisphenol F-	Sub-Category 1A	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
epichlorohydrin resin,	(sensitising)	assay (LLNA)		Local Lymph Node Assay)
MW<=700				
28064-14-4				
2,2'-[(1-	sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
methylethylidene)bis(4,1-		assay (LLNA)		Local Lymph Node Assay)
phenyleneoxymethylene)]				
bisoxirane				
1675-54-3				
Dodecane-1-thiol	sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
112-55-0		assay (LLNA)		Local Lymph Node Assay)

SDS No.: 439062 V005.0 Page 10 of 17

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
RP Bisphenol F- epichlorohydrin resin, MW<=700 28064-14-4	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
Dodecane-1-thiol 112-55-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Dodecane-1-thiol 112-55-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
RP Bisphenol F- epichlorohydrin resin, MW<=700 28064-14-4	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
RP Bisphenol F- epichlorohydrin resin, MW<=700 28064-14-4	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	negative	oral: gavage		mouse	not specified
Dodecane-1-thiol 112-55-0	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	not carcinogenic	dermal	2 y daily	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	not carcinogenic	oral: gavage	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

SDS No.: 439062 V005.0 Page 11 of 17

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Test type	Route of	Species	Method
CAS-No.	110 1 Ft B 7 7 0 7		application		OF OF OUR ALL OF
RP Bisphenol F-	NOAEL P > 750 mg/kg	two-	oral: gavage	rat	OECD Guideline 416 (Two-
epichlorohydrin resin,		generation			Generation Reproduction
MW<=700	NOAEL F1 750 mg/kg	study			Toxicity Study)
28064-14-4		-			
	NOAEL F2 750 mg/kg				
2,2'-[(1-	NOAEL P >= 50 mg/kg	Two	oral: gavage	rat	OECD Guideline 416 (Two-
methylethylidene)bis(4,1-		generation			Generation Reproduction
phenyleneoxymethylene)]	NOAEL F1 $>= 750 \text{ mg/kg}$	study			Toxicity Study)
bisoxirane	8 8				3 37
1675-54-3	NOAEL F2 $>= 750 \text{ mg/kg}$				
	1				

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Route of	Exposure time /	Species	Method
CAS-No.		application	Frequency of		
			treatment		
RP Bisphenol F-	NOAEL 250 mg/kg	oral: gavage	13 w	rat	OECD Guideline 408
epichlorohydrin resin,			daily		(Repeated Dose 90-Day
MW<=700					Oral Toxicity in Rodents)
28064-14-4					
2,2'-[(1-	NOAEL 50 mg/kg	oral: gavage	14 w	rat	OECD Guideline 408
methylethylidene)bis(4,1-			daily		(Repeated Dose 90-Day
phenyleneoxymethylene)]					Oral Toxicity in Rodents)
bisoxirane					
1675-54-3					

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SDS No.: 439062 V005.0 Page 12 of 17

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
RP Bisphenol F- epichlorohydrin resin, MW<=700 28064-14-4	LC50	5,7 mg/l		Ide, silver or golden orfe (Leuciscus idus)	OECD Guideline 203 (Fish, Acute Toxicity Test)
	LC50	1,75 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Dodecane-1-thiol 112-55-0	LC50	Toxicity > Water solubility	96 h	Oncorhynchus mykiss	EPA OTS 797.1400 (Fish Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
RP Bisphenol F- epichlorohydrin resin, MW<=700 28064-14-4	EC50	3,5 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]biso xirane 1675-54-3	EC50	1,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Dodecane-1-thiol 112-55-0	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
RP Bisphenol F- epichlorohydrin resin,	NOEC	0,3 mg/l	21 d	1 &	OECD 211 (Daphnia magna, Reproduction Test)
MW<=700					,
28064-14-4					
2,2'-[(1-	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
methylethylidene)bis(4,1-					magna, Reproduction Test)
phenyleneoxymethylene)]biso					
xirane					
1675-54-3					

Toxicity (Algae):

SDS No.: 439062 V005.0 Page 13 of 17

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value	Value	Exposure time	Species	Method
RP Bisphenol F- epichlorohydrin resin, MW<=700 28064-14-4	EC50	9,4 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]biso xirane 1675-54-3	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]biso xirane 1675-54-3	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dodecane-1-thiol 112-55-0	EC50	0,0145 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dodecane-1-thiol 112-55-0	EC10	0,0145 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
RP Bisphenol F-	IC50	> 100 mg/l	3 h	activated sludge	OECD Guideline 209
epichlorohydrin resin,					(Activated Sludge,
MW<=700					Respiration Inhibition Test)
28064-14-4					
2,2'-[(1-	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
methylethylidene)bis(4,1-				_	
phenyleneoxymethylene)]biso					
xirane					
1675-54-3					

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
RP Bisphenol F- epichlorohydrin resin, MW<=700 28064-14-4	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]biso xirane 1675-54-3	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Dodecane-1-thiol 112-55-0	not readily biodegradable.	aerobic	39,2 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Bioconcentratio	Exposure time	Temperature	Species	Method
CAS-No.	n factor (BCF)				
RP Bisphenol F-	31			not specified	not specified
epichlorohydrin resin,					
MW<=700					
28064-14-4					

SDS No.: 439062 V005.0 Page 14 of 17

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
RP Bisphenol F-	3,242		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
epichlorohydrin resin,			Method)
MW<=700			
28064-14-4			
2,2'-[(1-	3,242	25 °C	EU Method A.8 (Partition Coefficient)
methylethylidene)bis(4,1-			
phenyleneoxymethylene)]biso			
xirane			
1675-54-3			
Dodecane-1-thiol	> 6,5	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
112-55-0			Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Dodecane-1-thiol 112-55-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SDS No.: 439062 V005.0 Page 15 of 17

SECTION 14: Transport information

14.1. UN number or ID number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADIX ENVIRONMENTALLI HAZARDOUS SUBSTANCE, LIOUID, N.O.S. (EDC	ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIOUID, N.O.S. (Epop	v
---	-----	---	---

resin)

RID ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy

resin)

ADN ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy

resin)

IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy

resin)

IATA Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
ΙΔΤΔ	C

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous

IMDG Marine Pollutant

IATA Environmentally Hazardous

14.6. Special precautions for user

ADR	not applicable
	Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SDS No.: 439062 V005.0 Page 16 of 17

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Not applicable Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Not applicable Persistent organic pollutants (Regulation (EU) 2019/1021): Not applicable

VOC content < 3 %

(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: WGK 2: significantly water endangering (Ordinance on facilities for handling

substances that are hazardous to water (AwSV)) Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 10

SDS No.: 439062 V005.0 Page 17 of 17

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL:

Substance with a Union workplace exposure limit

EU EXPLD 1:

Substance listed in Annex I, Reg (EC) No. 2019/1148

EU EXPLD 2

Substance listed in Annex II, Reg (EC) No. 2019/1148

SVHC:

Substance of very high concern (REACH Candidate List)

PBT:

Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.



LOCTITE EA M-121HP B

Safety Data Sheet according to (EC) No 1907/2006 as amendedPage 1 of 22

SDS No.: 157227

V005.0 Revision: 07.02.2024

printing date: 08.02.2024

Replaces version from: 07.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE EA M-121HP B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Part B of 2-Component Epoxy Adhesive.

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin corrosion Sub-category 1B

H314 Causes severe skin burns and eye damage.

Serious eye damage Category 1

H318 Causes serious eye damage.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

SDS No.: 157227 V005.0 Page 2 of 22



Contains Amines, polyethylenepoly-, tetraethylenepentamine fraction

Amines, polyethylenepoly-, triethylenetetramine fraction

3,6,9,12-tetraazatetradecamethylenediamine

amines, polyethylenepoly-

Signal word:	Danger
Hazard statement:	H314 Causes severe skin burns and eye damage.
	H317 May cause an allergic skin reaction.
	H411 Toxic to aquatic life with long lasting effects.
Supplemental information	EUH071 Corrosive to the respiratory tract.
Precautionary statement:	P273 Avoid release to the environment.
Prevention	P280 Wear protective gloves/protective clothing/eye protection/face protection.
1 revention	1 280 Wear protective groves/protective clothing/eye protection/race protection.
Precautionary statement:	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Response	Rinse skin with water [or shower].
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P310 Immediately call a POISON CENTER or doctor.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

SDS No.: 157227 V005.0 Page 3 of 22

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7 500-381-8	50- 100 %	Aquatic Chronic 2, H411 Eye Dam. 1, H318		
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7 292-587-7, 292-587-7 01-2119487290-37	10- 20 %	Acute Tox. 4, Dermal, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 2, H411 Eye Dam. 1, H318		
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8 292-588-2 01-2119487919-13	5- < 10 %	Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 3, H412		
3,6,9,12- tetraazatetradecamethylenediami ne 4067-16-7 223-775-9 01-2119485826-22	0,1-< 1 %	Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312	M acute = 1 M chronic = 1	
amines, polyethylenepoly- 68131-73-7 268-626-9 01-2119485823-28	0,1-< 1 %	Acute Tox. 4, Dermal, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 4, Oral, H302	M acute = 1 M chronic = 1	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

SKIN: Rash, Urticaria.

SDS No.: 157227 V005.0 Page 4 of 22

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.

Protect against contamination.

Ensure that storage and workrooms are adequately ventilated.

Store in a cool, dry place.

Keep away from heat and direct sunlight.

Refer to Technical Data Sheet.

7.3. Specific end use(s)

Part B of 2-Component Epoxy Adhesive.

SDS No.: 157227 V005.0 Page 5 of 22

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for Germany

None

SDS No.: 157227 V005.0 Page 6 of 22

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
	•		mg/l	ppm	mg/kg	others	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	aqua (freshwater)		0,004 mg/l				
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	Freshwater - intermittent		0,043 mg/l				
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	aqua (marine water)		0 mg/l				
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	sewage treatment plant (STP)		3,84 mg/l				
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	sediment (freshwater)				434,02 mg/kg		
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	sediment (marine water)				43,4 mg/kg		
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	Soil				86,78 mg/kg		
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	Predator						no potential for bioaccumulation
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	aqua (freshwater)		0,01 mg/l				
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	aqua (marine water)		0,001 mg/l				
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	aqua (intermittent releases)		0,068 mg/l				
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	sediment (freshwater)				3,198 mg/kg		
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	sediment (marine water)				0,32 mg/kg		
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Soil				2,5 mg/kg		
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	sewage treatment plant (STP)		4,6 mg/l				
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Air						no hazard identified
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Predator						no potential for bioaccumulation
Amines, polyethylenepoly-, triethylenetetramine fraction	aqua (intermittent		0,2 mg/l				

SDS No.: 157227 V005.0 Page 7 of 22

100040 07 9	I1\	1 1	1 1	1
90640-67-8	releases)	0.027 //		
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	aqua (freshwater)	0,027 mg/l		
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	aqua (marine water)	0,003 mg/l		
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	sediment (freshwater)		8,572 mg/kg	
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	sediment (marine water)		0,857 mg/kg	
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	Soil		1,25 mg/kg	
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	sewage treatment plant (STP)	0,13 mg/l		
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	oral			no potential for bioaccumulation
3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7	aqua (freshwater)	0,005 mg/l		
3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7	aqua (marine water)	0,001 mg/l		
3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7	sewage treatment plant (STP)	4,2 mg/l		
3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7	sediment (freshwater)		1,59 mg/kg	
3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7	sediment (marine water)		0,159 mg/kg	
3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7	Soil		3,4 mg/kg	
3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7	Freshwater - intermittent	0,017 mg/l		
3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7	Marine water - intermittent	0,002 mg/l		
amines, polyethylenepoly- 68131-73-7	aqua (freshwater)	0,0016 mg/l		
amines, polyethylenepoly- 68131-73-7	aqua (marine water)	0,0016 mg/l		
amines, polyethylenepoly- 68131-73-7	aqua (intermittent releases)	0,016 mg/l		
amines, polyethylenepoly- 68131-73-7	sewage treatment plant (STP)	3,19 mg/l		
amines, polyethylenepoly- 68131-73-7	sediment (freshwater)		0,14 mg/kg	
amines, polyethylenepoly- 68131-73-7	sediment (marine water)		0,14 mg/kg	
amines, polyethylenepoly- 68131-73-7	Air			no hazard identified
amines, polyethylenepoly- 68131-73-7	Soil		10 mg/kg	
amines, polyethylenepoly- 68131-73-7	oral		0,29 mg/kg	

SDS No.: 157227 V005.0 Page 8 of 22

Derived No-Effect Level (DNEL):

Amines, polyethylenepoly-, estreethylenepoly-,	Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Amines, polychylespepoly- interactive propertions fraction 90640-66-7 Amines, polychylespepoly- interactive produptions of the state o	tetraethylenepentamine fraction		_	exposure -		1,29 mg/m3	no hazard identified
tetratety-free-pentatine fraction 90640 66-7 Annines, polyethylesproly-, control tetratety-free-pentatine fraction 90640 67-8 Annines, polyethylesproly-, control tetratety-free-pentat						1	
99840-66-7 Amines, polyethylenepoly-, tetruethylenepentamine fraction 90640-66-7 Amine		Workers	inhalation			6940 mg/m3	no hazard identified
Amines, polyethylenepoly- tetrnethylenepolamine fraction 90640-66-7 Amines, polyethylenepoly- tetrnethylenepolamine fraction 90640-66-7 Amines, polyethylenepoly- tetrnethylenepolamine fraction 90640-66-7 Amines, polyethylenepoly- population 90640-66-7 Amines, polyethylenepoly- tetrnethylenepolamine fraction 90640-66-7 Amines, polyethylenepoly-							
sexposure - systemic effects 0.036 mg/cm2 no hazard identified exposure - local effects		W/1	41			0.74 /1	
9,9040-66-7 Amines, polyethylenepoly-, eterately benepartamine fraction 9,0040-66-7 Amines, polyethylenepoly-, eterately benepartamine fraction 9,0040-66-7 Amines, polyethylenepoly-, eterately benepartamine fraction 9,0040-66-7 Amines, polyethylenepoly-, epolythone polythone		Workers	dermal			0,74 mg/kg	no hazard identified
Amines, polyethylenepoly, terrently hereportainine fraction population popula	* 1			1			
terranethyleneportamine fraction 90640-66-7 Amines, polyethylenepoly-, General population 90640-66-8 G		Workers	dermal	-		0.036 mg/cm2	no hazard identified
90640-66-7 Amines, polyethylenepotly-, ceneral population population population systemic effects shamines, polyethylenepotly-, ceneral population shamines, polyethylenepotl		Workers	dermar			0,030 mg/cm2	no nazara racininea
tetratetylepespentamine fraction 900401-66-7 Amines, polyethylenepoly-, tetrachylepespentamine fraction 900401-66-7 General 900401-66-7 Ge							
tetratetylepespentamine fraction 900401-66-7 Amines, polyethylenepoly-, tetrachylepespentamine fraction 900401-66-7 General 900401-66-7 Ge		General	inhalation			0,38 mg/m3	no hazard identified
Amines, polyethylenepoly-, etraethylenepoly-markine fraction population popul		population					
tertaethylenepentamine fraction 90640-66-7 Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-67-8 Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-67-8 Amines, polyethylenepoly-, triethylenetertamine fraction 90640-67-8 Amines,	90640-66-7			systemic effects			
90640-66-7 Amines, polyethylenepoly-, tetraethylenepenamine fraction 90640-66-7 Amines, polyethylenepoly-, tetraethylenetamine fraction 90640-66-7 Amines, polyethylenepoly-, tetraethylenetamine fraction 90640-66-7 Amines, polyethylenepoly-, tetraethylenetamine fraction 90640-67 Amines, polyethylenepoly-, tetraethylenetamine 90640-67 Amines, polyethyle		General	inhalation	Acute/short term		2071 mg/m3	no hazard identified
Amines, polyethylenepoly- tetracelylenepethamine fraction 90640-66-7 Amines, polyethylenepoly- tetracelylenepethamine fraction 90640-66-7 Amines, polyethylenepoly-, tetracelylenepethamine fraction 90640-67-8 Amines, polyethylenepoly-, trichylenetetramine fraction 90640-67-8 Amines, polyethylenepoly- trichylenetetramine fraction 90640-67-8 Amines, polyethylenepoly-, trichylenetetramine fraction 90640-67-8 Amines, polyethylenepoly- trichylenetetramine fraction 90640-67-8 Amines, polyethylenepoly- trichylenetetramine fraction 90640-67-8 Amines, polyethylenepoly- trichylenetramine fraction 90640-67-8 Amines, polyethyl		population					
tetrachlylenepenhamine fraction 90640-66-7 Animes, polyethylenepoly, tetrachlylenepoly, tetrachlylenepenhamine fraction 90640-66-7 Animes, polyethylenepoly, tetrachlylenepoly, tet			1				
90640-66-7 Animes, polyethylenepoly-, tetraethylenepemamine fraction 90640-66-7 Animes, polyethylenepoly-, triethyleneteramine fraction 90640-67-8 Animes, polyethylenepoly-, triethyleneteramine fraction 90640-67-8 Animes, polyethylenepoly-, triethyleneteramine fraction 90640-67-8 Animies, polyethylenepoly-, General population 90640-67-8 Animies, polyethylenepoly-, General population 90640-67-8 Animies, polyethylenepoly-, General population 90640-67-8 Animes, polyethylenepoly-, General population 90640-67-6 Animes, polyethylenepoly-, General population 90640-67-8 Animes, polyethylenepoly- 90640-67-8 Animes, polyethylenep			dermal			0,32 mg/kg	no hazard identified
Amines, polyethylenepoly- tetracthylenepenamine fraction 90640-6-7 Amines, polyethylenepoly-, General population 90640-6-7 Amines, polyethylenepoly- tetracthylenepenamine fraction 90640-6-7 Amines, polyethylenepoly- tetracthylenepenamine fraction 90640-6-7 Amines, polyethylenepoly- tirethyleneteramine fraction 90640-6-7 Beneral population 90640-6-7 Amines, polyethylenepoly- tirethyleneteramine fraction 90640-6-7 Beneral population 90640		population					
tetraethylenepentamine fraction population p		C1	J 1	7		10 //	hdid. (C. 1
90640-6-7 Amines, polyethylenepoly-, tetraethylenepentamine fraction population of exposure - local effects should be exposure - local effects should local effects should be exposure - local			dermal			10 mg/kg	no nazard identified
Amines, polyethylenepoly-, tetracthylenepentamine fraction 90640-66-7 Amines, polyethylenepoly-, deneral population 90640-67-8 Aso, 912-tetrazatetradecamethylenediamine 90640-67-6-7 Ago, 912-tetrazatetradecamethylenediamine 90640-67-6-7 Amines, polyethylenepoly- 90640-67-8 Aso, 912-tetrazatetradecamethylenediamine 90640-67-6-7 Ago, 912-tetrazatetradecamethylenediamine 90640-67-6-7 Amines, polyethylenepoly- 90640-67-8 Ago, 912-tetrazatetradecamethylenediamine 90640-67-6-7 Ago, 912-tetrazatetradecamethylenediamine 90640-67-6-7 Ago, 912-tetrazatetradecamethylenediamine 90640-67-6-7 Ago, 912-tetrazatetradecamethylenediamine 90640-67-67 Ag		population					
tetraethylenepentamine fraction 90pollation Reposure local		General	dermal			0.56 mg/cm ²	no hazard identified
90640-66-7 Amines, polyethylenepoly-, letraethylenepentamine fraction population yold-0-67 Amines, polyethylenepoly-, letraethylenepentamine fraction yold-0-67 Amines, polyethylenepoly-, letraethylenetetramine fraction yold-0-67 Amines, polyethylenepoly-, letraethyl			dermai			0,50 mg/cm2	no nazard identified
Amines, polyethylenepoly-, tetraketylenefetramine fraction population general dermal population systemic effects amines, polyethylenepoly-, tetraketylenepoly-, tetrak		L obminion					
tetraethylenepentamine fraction 90640-66-7 Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7 Amines, polyethylenepoly-, General population 90640-66-7 Amines, polyethylenepoly-, General cetraethylenepentamine fraction 90640-66-7 Amines, polyethylenepoly-, General population 90640-66-7 Amines, polyethylenepoly-, Workers Inhalation Inh		General	dermal	Acute/short term		1.29 mg/cm2	no hazard identified
90640-66-7 Amines, polyethylenepoly-, General population 90640-66-7 Amines, polyethylenepoly-, General ctraethylenepentamine fraction 90640-66-7 Amines, polyethylenepoly-, General population 90640-66-7 Amines, polyethylenepoly-, General ctraethylenepentamine fraction 90640-67-8 Amines, polyethylenepoly-, General population 90640-67-8 Anines, polyethylenepoly-, General population 90640-67-8				exposure - local		,	
tetraethylenepentamine fraction 90640-66-7 Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-67-8 Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-67-8 Amines, polyethylenepoly-, triethylenepentamine fraction 90640-67-8 Amines, polyethylenepoly-, triethylenepertamine fraction 90640-67-8 Amines, polyethylenepoly-, triethyleneteramine fraction 90640-67-8 Amines, polyethylenepoly-, triethyleneteramine fraction 90640-67-8 Amines, polyethylenepoly-, triethyleneteramine fraction 90640-67-8 3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 Ageneral population General popu	90640-66-7			effects			
Systemic effects Systemic e	Amines, polyethylenepoly-,	General	oral	Long term		0,53 mg/kg	no hazard identified
Amines, polyethylenepoly-, tetraetylenepentamine fraction population population population systemic effects suspense and population population population population systemic effects suspense polyethylenepoly-, triethylenetetramine fraction population po		population		1			
tetraethylenepentamine fraction 90040-66-7 Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8 Amines, polyethylenediamine 4067-16-7 3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 9,3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 9,3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 9,3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 9,0,12 tetraazatetradecamethylenediamine 4067-16-7 9,0,2 tetraazatetradecamethylenediamine 4067-16-7 9,0,2 tetraazatetradecamethylenediamine 4067-16-7 9,0,2 tetraazatetradecamethylenediamine 4067-16-7 9,0,2				-			
90640-66-7			oral			26 mg/kg	no hazard identified
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8 Amines, polyethylenediamine 4067-16-7 Amines, polyethylenepoly- 813-73-7 Amines, polyethylenepoly- 8131-73-7 Amines, polyethylenepoly- 909tlation Amines, polyethylenepoly- 90		population					
triethylenetetramine fraction 90640-67-8 Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8 3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 \$\frac{1}{3}\$.		W/1	T-1-1-4:	•		0.54/2	
Systemic effects Systemic e		Workers	Innalation			0,54 mg/m3	
Amines, polyethylenepoly- triethylenetetramine fraction population Systemic effects Amines, polyethylenepoly- triethylenetetramine fraction population Amines, polyethylenepoly- population Systemic effects Amines, polyethylenepoly- triethylenetetramine fraction population Systemic effects Anopotential for bioaccumulation Dolad 67-8 Anopotential for bioaccumulation Dolad for-8 Systemic effects Active/short term exposure - systemic effects Anopotential for bioaccumulation Dolad for-8 Dolad for-8 Systemic effects Dolad for-8 Systemic effects Dolad for-8 Dolad for-8 Systemic effects Dolad for-8 Systemic effects Dolad for-8 Dola							bloaccumulation
triethylenetetramine fraction 90640-67-8 Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8 Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8 3.6.9.12-tetraazatetradecamethylenediamine 4067-16-7 3.6.9.12-tetraazatetradecamethylenediamine 4067-16-7 3.6.9.12-tetraazatetradecamethylenediamine 4067-16-7 4067-16-7 4068131-73-7 407-16-7 408-7-16-7 409-8-8-8-8-8-8-8-8-8-8-8-8-8-8-8-8-8-8-8		General	Inhalation			0.096 mg/m3	no potential for
Systemic effects Systemic effects Systemic effects Cancel						0,000 1119 1110	
triethylenetetramine fraction 90640-67-8 3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 407-16-7 4068131-73-7 4068131-73-7 407-10-10-10-10-10-10-10-10-10-10-10-10-10-							
Systemic effects Systemic e	Amines, polyethylenepoly-,	General	oral	Long term		0,14 mg/kg	no potential for
3,6,9,12-tetrazatetradecamethylenediamine 4067-16-7 4067-16-7 407-16-7 408-16-7 408-16-7 408-16-7 409-	triethylenetetramine fraction	population					
Augustion Aug						1	
3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 Workers inhalation Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers inhalation Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers inhalation Acute/short term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers inhalation Acute/short term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers dermal Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 General inhalation Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 General inhalation Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 General inhalation Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 General inhalation Long term exposure - local effects amines, polyethylenepoly- 68131-73-7 General inhalation Long term exposure - local effects amines, polyethylenepoly- 68131-73-7 General inhalation Long term exposure - local effects amines, polyethylenepoly- 68131-73-7 General inhalation Long term exposure - local effects amines, polyethylenepoly- 68131-73-7 General inhalation Long term exposure - local effects amines, polyethylenepoly- 68131-73-7 General inhalation Long term exposure - local effects amines, polyethylenepoly- 68131-73-7 General inhalation Long term exposure - local effects amines, polyethylenepoly- 68131-73-7 General inhalation Long term exposure - local effects amines, polyethylenepoly- 68131-73-7	3,6,9,12-tetraazatetradecamethylenediamine		oral			0,21 mg/kg	
3.6,9,12-tetraazatetradecamethylenediamine 4067-16-7 Inhalation	4067-16-7	population					
4067-16-7populationexposure - systemic effects3.6.9,12-tetraazatetradecamethylenediamine 4067-16-7WorkersinhalationLong term exposure - systemic effects0,82 mg/m3amines, polyethylenepoly-68131-73-7WorkersinhalationLong term exposure - systemic effects1,59 mg/m3no hazard identifiedamines, polyethylenepoly-68131-73-7WorkersinhalationAcute/short term exposure - systemic effects8550 mg/m3no hazard identifiedamines, polyethylenepoly-68131-73-7WorkersdermalLong term exposure - systemic effects0,91 mg/kgno hazard identifiedamines, polyethylenepoly-68131-73-7WorkersdermalLong term exposure - local effects44 μg/cm2/dayno hazard identifiedamines, polyethylenepoly-68131-73-7General populationLong term exposure - local effects44 μg/cm2/dayno hazard identified	260124-4	Comp. 1	11. 1 /1			0.14 / 2	
Systemic effects Systemic e			inhalation			0,14 mg/m3	
3,6,9,12-tetraazatetradecamethylenediamine 4067-16-7 Workers inhalation Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers inhalation Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers inhalation Acute/short term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers dermal Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers dermal Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Gernal amines, polyethylenepoly- 68131-73-7 General population inhalation Long term exposure - local effects amines, polyethylenepoly- 68131-73-7 General population inhalation Long term exposure - local effects 0,46 mg/m3 no hazard identified no hazard identified on hazard identified exposure - local effects no hazard identified	4007-10-7	population					
4067-16-7 exposure - systemic effects amines, polyethylenepoly-68131-73-7 Workers inhalation exposure - systemic effects 1,59 mg/m3 no hazard identified amines, polyethylenepoly-68131-73-7 Workers inhalation exposure - systemic effects 8550 mg/m3 no hazard identified amines, polyethylenepoly-68131-73-7 Workers dermal Long term exposure - systemic effects 0,91 mg/kg no hazard identified amines, polyethylenepoly-68131-73-7 Workers dermal Long term exposure - local effects 44 μg/cm2/day no hazard identified amines, polyethylenepoly-68131-73-7 General population inhalation Long term exposure - local effects 0,46 mg/m3 no hazard identified	3.6.9.12-tetragagatetradecamethylanediamina	Workers	inhalation			0.82 mg/m ²	
systemic effects amines, polyethylenepoly- 68131-73-7 Workers inhalation Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers inhalation Acute/short term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers dermal Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers dermal Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 General amines, polyethylenepoly- 68131-73-7 General population systemic effects 1,59 mg/m3 no hazard identified 0,91 mg/kg no hazard identified 44 μg/cm2/day no hazard identified 9,46 mg/m3 no hazard identified 1,59 mg/m3 no hazard identified		WOIKEIS	iiiiiaiatiOli			0,02 mg/m3	
amines, polyethylenepoly- 68131-73-7Workersinhalation exposure - systemic effects1,59 mg/m3no hazard identifiedamines, polyethylenepoly- 68131-73-7Workersinhalation exposure - systemic effects8550 mg/m3no hazard identifiedamines, polyethylenepoly- 	1007 10 7						
68131-73-7 exposure - systemic effects amines, polyethylenepoly-68131-73-7 Workers inhalation Acute/short term exposure - systemic effects 8550 mg/m3 no hazard identified amines, polyethylenepoly-68131-73-7 Workers dermal Long term exposure - systemic effects 0,91 mg/kg no hazard identified amines, polyethylenepoly-68131-73-7 Workers dermal Long term exposure - local effects 44 μg/cm2/day no hazard identified amines, polyethylenepoly-68131-73-7 General population inhalation Long term exposure - local exposure - 0,46 mg/m3 no hazard identified	amines, polyethylenepoly-	Workers	inhalation			1.59 mg/m3	no hazard identified
systemic effects amines, polyethylenepoly- 68131-73-7 Workers inhalation Acute/short term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers dermal Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers dermal Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 General amines, polyethylenepoly- 68131-73-7 General population systemic effects 0,91 mg/kg no hazard identified 44 μg/cm2/day no hazard identified 10,46 mg/m3 no hazard identified 10,46 mg/m3 no hazard identified 10,46 mg/m3 no hazard identified						,	3 100
amines, polyethylenepoly- 68131-73-7 Workers inhalation Acute/short term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers dermal Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers dermal Long term exposure - systemic effects Acute/short term exposure - systemic effects Acute/sh						<u> </u>	<u> </u>
68131-73-7 exposure - systemic effects amines, polyethylenepoly-68131-73-7 Workers dermal Long term exposure - systemic effects 0,91 mg/kg no hazard identified amines, polyethylenepoly-68131-73-7 Workers dermal Long term exposure - local effects 44 μg/cm2/day no hazard identified amines, polyethylenepoly-68131-73-7 General population inhalation Long term exposure - 0,46 mg/m3 no hazard identified	amines, polyethylenepoly-	Workers	inhalation			8550 mg/m3	no hazard identified
amines, polyethylenepoly- 68131-73-7 Workers dermal Long term exposure - systemic effects amines, polyethylenepoly- 68131-73-7 Workers dermal Long term exposure - local effects amines, polyethylenepoly- 68131-73-7 General population General population workers dermal Long term exposure - local effects 0,91 mg/kg no hazard identified no hazard identified no hazard identified 0,46 mg/m3 no hazard identified						-	
68131-73-7 exposure - systemic effects amines, polyethylenepoly-68131-73-7 Workers dermal Long term exposure - local effects 44 μg/cm2/day no hazard identified amines, polyethylenepoly-68131-73-7 General population inhalation exposure - local effects 0,46 mg/m3 no hazard identified			1				
systemic effects amines, polyethylenepoly- 68131-73-7 Workers dermal Long term exposure - local effects amines, polyethylenepoly- 68131-73-7 General population Systemic effects Long term exposure - local effects 0,46 mg/m3 no hazard identified no hazard identified exposure -		Workers	dermal	Long term		0,91 mg/kg	no hazard identified
amines, polyethylenepoly- 68131-73-7 Workers dermal Long term exposure - local effects amines, polyethylenepoly- 68131-73-7 General population General population Morkers dermal Long term exposure - local effects 0,46 mg/m3 no hazard identified no hazard identified	68131-73-7						
68131-73-7 exposure - local effects amines, polyethylenepoly- 68131-73-7 General population General exposure - local effects Inhalation Long term exposure - local effects 0,46 mg/m3 no hazard identified							
effects contact contac		Workers	dermal			44 μg/cm2/day	no hazard identified
amines, polyethylenepoly- 68131-73-7 General inhalation Long term exposure - 0,46 mg/m3 no hazard identified	68131-73-7						
68131-73-7 population exposure -		Comp. 1	11. 1 /			0.46 / 2	11'1 .'C' 1
			inhalation			0,46 mg/m3	no hazard identified
cyctamic affacts	00131-73-7	population		exposure - systemic effects			

SDS No.: 157227 V005.0 Page 9 of 22

amines, polyethylenepoly-68131-73-7	General population	inhalation	Acute/short term exposure - systemic effects	2542 mg/m3	no hazard identified
amines, polyethylenepoly- 68131-73-7	General population	dermal	Long term exposure - systemic effects	0,4 mg/kg	no hazard identified
amines, polyethylenepoly- 68131-73-7	General population	dermal	Acute/short term exposure - systemic effects	13 mg/kg	no hazard identified
amines, polyethylenepoly- 68131-73-7	General population	dermal	Long term exposure - local effects	0,68 mg/cm2	no hazard identified
amines, polyethylenepoly- 68131-73-7	General population	dermal	Acute/short term exposure - local effects	1,59 mg/cm2	no hazard identified
amines, polyethylenepoly- 68131-73-7	General population	oral	Long term exposure - systemic effects	0,65 mg/kg	no hazard identified
amines, polyethylenepoly- 68131-73-7	General population	oral	Acute/short term exposure - systemic effects	32 mg/kg	no hazard identified

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

SDS No.: 157227 V005.0 Page 10 of 22

Delivery form liquid
Colour Amber
Odor mild
Physical state liquid

Melting point Not applicable, Product is a liquid

Solidification temperature $< -30 \,^{\circ}\text{C} (< -22 \,^{\circ}\text{F})$ Initial boiling point $> 100 \,^{\circ}\text{C} (> 212 \,^{\circ}\text{F})$

Flammability The product is not flammable.

Explosive limits Not applicable, The product is not flammable.

Flash point $> 160 \,^{\circ}\text{C} (> 320 \,^{\circ}\text{F})$

Auto-ignition temperature Not applicable, The product is not flammable.

Decomposition temperature > 100 °C (> 212 °F);

pH Not applicable, Product is non-soluble (in water).

Viscosity (kinematic) 2.000 - 4.000 mm2/s

(25 °C (77 °F);)
Solubility (qualitative)

Partially miscible

(20 °C (68 °F); Solvent: Water)

Solubility (qualitative) Moderate soluble
Partition coefficient: n-octanol/water Not applicable
Mixture

Vapour pressure < 0,1 hPa (20 °C (68 °F))

(20 °C (68 °F))
Relative vapour density: >1

(20 °C)

Particle characteristics Not applicable
Product is a liquid

9.2. Other information

Density

Other information not applicable for this product

SECTION 10: Stability and reactivity

1,0 g/cm3 None

10.1. Reactivity

Reacts with strong oxidants.

Acids.

Reaction with strong acids.

Strong bases.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

Rapid polymerisation may generate excessive heat and pressure.

May produce fumes when heated to decomposition. Fumes may contain carbon monoxide and other toxic fumes.

SDS No.: 157227 V005.0 Page 11 of 22

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	LD50	3.221 mg/kg	rat	not specified
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	LD50	1.716 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
3,6,9,12- tetraazatetradecamethylen ediamine 4067-16-7	LD50	1.716,2 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
amines, polyethylenepoly-68131-73-7	LD50	1.716,2 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Amines,	LD50	1.260 mg/kg	rabbit	not specified
polyethylenepoly-,				
tetraethylenepentamine				
fraction				
90640-66-7				
Amines,	LD50	1.465 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
polyethylenepoly-,				
triethylenetetramine				
fraction				
90640-67-8				
3,6,9,12-	LD50	1.465,4 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
tetraazatetradecamethylen				
ediamine				
4067-16-7				
amines, polyethylenepoly-	LD50	1.465,4 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
68131-73-7				

SDS No.: 157227 V005.0 Page 12 of 22

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Amines,	corrosive		Corrositex	OECD Guideline 435 (In Vitro Membrane Barrier Test
polyethylenepoly-,			Biobarrier	Method for Skin Corrosion)
tetraethylenepentamine			Membrane	
fraction			(reconstituted	
90640-66-7			collagen matrix)	
Amines,	corrosive		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
polyethylenepoly-,				
triethylenetetramine				
fraction				
90640-67-8				
amines, polyethylenepoly-	Category 1B			OECD Guideline 435 (In Vitro Membrane Barrier Test
68131-73-7	(corrosive)			Method for Skin Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	Category 1 (irreversible effects on the eye)		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
amines, polyethylenepoly-68131-73-7	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Sensitizing	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	Sensitizing	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
amines, polyethylenepoly-68131-73-7	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

SDS No.: 157227 V005.0 Page 13 of 22

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	positive	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	positive	sister chromatid exchange assay in mammalian cells	with and without		equivalent or similar to OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
amines, polyethylenepoly-68131-73-7	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
amines, polyethylenepoly-68131-73-7	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	not carcinogenic	dermal	lifetime three times/w	mouse	male	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

No data available.

SDS No.: 157227 V005.0 Page 14 of 22

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	LOAEL 50 mg/kg	oral: gavage	26 w daily	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	NOAEL 200 mg/kg	dermal	20 d 6 h/d, 5 d/w	rabbit	OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	LOAEL 50 mg/kg	oral: gavage	26 w daily	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
amines, polyethylenepoly-68131-73-7	NOAEL 350 mg/kg	oral: gavage	4 and 8 weeks daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SDS No.: 157227 V005.0 Page 15 of 22

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16- 18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	LC50	7,07 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	LC50	420 mg/l	96 h	Poecilia reticulata	OECD Guideline 203 (Fish, Acute Toxicity Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	LC50	330 mg/l	96 h	Pimephales promelas	other guideline:
3,6,9,12- tetraazatetradecamethylenedia mine 4067-16-7	LC50	180 mg/l	96 h	Poecilia reticulata	EU Method C.1 (Acute Toxicity for Fish)
amines, polyethylenepoly-68131-73-7	LC50	100 mg/l	96 h	Poecilia reticulata	EU Method C.1 (Acute Toxicity for Fish)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16- 18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	EC50	7,07 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	EC50	24,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	EC50	31 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3,6,9,12- tetraazatetradecamethylenedia mine 4067-16-7	EC50	17,5 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
amines, polyethylenepoly- 68131-73-7	EC50	2,2 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

SDS No.: 157227 V005.0 Page 16 of 22

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	EC10	1,9 mg/l	21 d	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	EC10	1,9 mg/l	21 day	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)
3,6,9,12- tetraazatetradecamethylenedia mine 4067-16-7	EC10	1,9 mg/l	21 d	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)

Toxicity (Algae):

SDS No.: 157227 V005.0 Page 17 of 22

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Fatty acids, C18-unsatd., dimers, oligomeric reaction	EC50	4,34 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella	OECD Guideline 201 (Alga, Growth Inhibition Test)
products with fatty acids, C16-				subcapitata)	
18 and C18-unsatd., branched					
and linear and					
triethylenetetramine 157707-72-7					
Fatty acids, C18-unsatd.,	NOEC	0,5 mg/l	72 h	Raphidocelis subcapitata (new	OECD Guideline 201 (Alga,
dimers, oligomeric reaction				name: Pseudokirchneriella	Growth Inhibition Test)
products with fatty acids, C16-				subcapitata)	
18 and C18-unsatd., branched					
and linear and					
triethylenetetramine 157707-72-7					
Amines, polyethylenepoly-,	EC50	6,8 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga,
tetraethylenepentamine					Growth Inhibition Test)
fraction					
90640-66-7					
Amines, polyethylenepoly-,	NOEC	0,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga,
tetraethylenepentamine					Growth Inhibition Test)
fraction					
90640-66-7					
Amines, polyethylenepoly-,	EC50	20 mg/l	72 h	Selenastrum capricornutum	OECD Guideline 201 (Alga,
triethylenetetramine fraction				(new name: Pseudokirchneriella	Growth Inhibition Test)
90640-67-8				subcapitata)	
Amines, polyethylenepoly-,	EC10	1,34 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga,
triethylenetetramine fraction				(reported as Raphidocelis	Growth Inhibition Test)
90640-67-8				subcapitata)	
3,6,9,12-	EC50	1,7 mg/l	72 h	Raphidocelis subcapitata (new	OECD Guideline 201 (Alga,
tetraazatetradecamethylenedia				name: Pseudokirchneriella	Growth Inhibition Test)
mine				subcapitata)	
4067-16-7					
3,6,9,12-	NOEC	0,25 mg/l	72 h	Raphidocelis subcapitata (new	OECD Guideline 201 (Alga,
tetraazatetradecamethylenedia				name: Pseudokirchneriella	Growth Inhibition Test)
mine				subcapitata)	
4067-16-7	L				
amines, polyethylenepoly-	EC50	0,5 mg/l	72 h	Selenastrum capricornutum	OECD Guideline 201 (Alga,
68131-73-7				(new name: Pseudokirchneriella subcapitata)	Growth Inhibition Test)
amines, polyethylenepoly-	NOEC	0,16 mg/l	72 h	Selenastrum capricornutum	OECD Guideline 201 (Alga,
68131-73-7				(new name: Pseudokirchneriella	Growth Inhibition Test)
				subcapitata)	

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_	_	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16- 18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	EC50	384 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	EC50	97,3 mg/l	2 h	other:	other guideline:
3,6,9,12- tetraazatetradecamethylenedia mine 4067-16-7	EC50	164 mg/l	2 h	other:	other guideline:

SDS No.: 157227 V005.0 Page 18 of 22

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16- 18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	not readily biodegradable.	aerobic	> 0 - < 60 %	74 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	not readily biodegradable.	aerobic	0 %	162 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	not inherently biodegradable	aerobic	17 %	84 d	OECD Guideline 302 A (Inherent Biodegradability: Modified SCAS Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	not readily biodegradable.	aerobic	0 %	162 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	not inherently biodegradable	aerobic	20 %	84 d	OECD Guideline 302 A (Inherent Biodegradability: Modified SCAS Test)
3,6,9,12- tetraazatetradecamethylenedia mine 4067-16-7	not readily biodegradable.	aerobic	0 %	162 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
3,6,9,12- tetraazatetradecamethylenedia mine 4067-16-7	not inherently biodegradable	aerobic	18 %	84 d	OECD Guideline 302 A (Inherent Biodegradability: Modified SCAS Test)
amines, polyethylenepoly- 68131-73-7	not readily biodegradable.	aerobic	0 %	162 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
amines, polyethylenepoly-68131-73-7	not inherently biodegradable	aerobic	16 %	84 day	OECD Guideline 302 A (Inherent Biodegradability: Modified SCAS Test)

12.3. Bioaccumulative potential

No data available.

SDS No.: 157227 V005.0 Page 19 of 22

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16- 18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	10,34		QSAR (Quantitative Structure Activity Relationship)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	-3,16		QSAR (Quantitative Structure Activity Relationship)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	-2,65		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
3,6,9,12- tetraazatetradecamethylenedia mine 4067-16-7	< 1		not specified
amines, polyethylenepoly- 68131-73-7	-3,67		QSAR (Quantitative Structure Activity Relationship)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with fatty acids, C16-18 and C18-unsatd., branched and linear and triethylenetetramine 157707-72-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
amines, polyethylenepoly-68131-73-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

SDS No.: 157227 V005.0 Page 20 of 22

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes
for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We
will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	2735
RID	2735
ADN	2735
IMDG	2735
IATA	2735

14.2. UN proper shipping name

ADR

	amines, Triethylenetetramine, dimer fatty acid(C18) poly amido amine resin)
RID	AMINES, LIQUID, CORROSIVE, N.O.S. (Aliphatic
	amines, Triethylenetetramine, dimer fatty acid(C18) poly amido amine resin)
ADN	AMINES, LIQUID, CORROSIVE, N.O.S. (Aliphatic
	amines Triethylenetetramine dimer fatty acid(C18)poly amido amine resin)

amines, i rietnylenetetramine, dimer ratty acid(C18) poly amido amine resi

AMINES, LIQUID, CORROSIVE, N.O.S. (Aliphatic

IMDG AMINES, LIQUID, CORROSIVE, N.O.S. (Aliphatic

amines, Triethylenetetramine, dimer fatty acid(C18) poly amido amine resin)

IATA Amines, liquid, corrosive, n.o.s. (Aliphatic amines, Triethylenetetramine, dimer fatty

acid(C18)poly amido amine resin)

14.3. Transport hazard class(es)

ADR	8
RID	8
ADN	8
IMDG	8
IATA	8

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous

SDS No.: 157227 V005.0 Page 21 of 22

ADN Environmentally Hazardous

IMDG Marine Pollutant IATA not applicable

14.6. Special precautions for user

ADR not applicable
Tunnelcode: (E)
RID not applicable
ADN not applicable
IMDG not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

not applicable

IATA

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):

Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable

Not applicable

VOC content < 3 %

(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: WGK 2: significantly water endangering (Ordinance on facilities for handling

substances that are hazardous to water (AwSV)) Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 8B

SDS No.: 157227 V005.0 Page 22 of 22

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL: Substance with a Union workplace exposure limit
EU EXPLD 1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2 Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC: Substance of very high concern (REACH Candidate List)
PBT: Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.