



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 14

LOCTITE LB 8156 400G EGFD

SDS No. : 283267  
V003.0

Revision: 13.01.2023  
printing date: 20.02.2023

Replaces version from: 31.01.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE LB 8156 400G EGFD

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Lubricant

#### 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA  
Henkelstr. 67  
40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Chronic hazards to the aquatic environment

Category 3

H412 Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Label elements (CLP):

Hazard pictogram:



Signal word:

Warning

<b>Hazard statement:</b>	H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects.
<b>Supplemental information</b>	Contains: Polysulfides, di-tert-Bu May produce an allergic reaction.
<b>Precautionary statement: Prevention</b>	P280 Wear protective gloves.
<b>Precautionary statement: Response</b>	P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

### 2.3. Other hazards

None if used properly.

Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
dilithium azelate 38900-29-7 254-184-4 01-2120119814-57	5- < 10 %	Acute Tox. 4, Oral, H302		
Ethyl 3-[[bis(1-methylethoxy)phosphinothioyl]thio]propionate 71735-74-5 275-965-6 01-2119976328-24	5- < 10 %	Aquatic Chronic 2, H411		
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9 288-917-4 01-2119521201-61	1- < 2,5 %	Aquatic Chronic 2, H411 Eye Dam. 1, H318 Skin Irrit. 2, H315		
Isoalkylphenyl phosphorothioate 126019-82-7 406-940-1	0,25- < 2,5 %	Aquatic Chronic 2, H411		
Zinc bis[O,O-bis(2-ethylhexyl)]bis(dithiophosphate) 4259-15-8 224-235-5 01-2119493635-27	1- < 2,5 %	Eye Dam. 1, H318 Aquatic Chronic 2, H411	Eye Dam. 1; H318; C > 50 % ===== oral:ATE = 2.500 mg/kg	
Polysulfides, di-tert-Bu 68937-96-2 273-103-3 01-2119540515-43	0,1- < 1 %	Skin Sens. 1, H317 Aquatic Chronic 3, H412	oral:ATE = 2.500 mg/kg	

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

#### Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

#### Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

#### Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

Prolonged or repeated contact may cause skin irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media:

water, carbon dioxide, foam, powder

#### Extinguishing media which must not be used for safety reasons:

High pressure waterjet

### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### Additional information:

In case of fire, keep containers cool with water spray.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

### 6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

### 6.4. Reference to other sections

See advice in section 8

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid skin and eye contact.  
See advice in section 8

#### Hygiene measures:

Wash hands before work breaks and after finishing work.  
Do not eat, drink or smoke while working.  
Good industrial hygiene practices should be observed.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place.  
Keep away from heat and direct sunlight.  
Refer to Technical Data Sheet

### 7.3. Specific end use(s)

Lubricant

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational Exposure Limits

Valid for  
Germany

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Titanium dioxide 13463-67-7			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Titanium dioxide 13463-67-7		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Titanium dioxide 13463-67-7		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	aqua (freshwater)		0,002 mg/l				
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	aqua (marine water)		0,0002 mg/l				
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	sediment (freshwater)				19,3 mg/kg		
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	sediment (marine water)				1,93 mg/kg		
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	Soil				15,7 mg/kg		
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	sewage treatment plant (STP)		100 mg/l				
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	aqua (intermittent releases)		0,02 mg/l				
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	aqua (freshwater)		0,004 mg/l				
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	aqua (marine water)		0,0046 mg/l				
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	sediment (freshwater)				0,0701 mg/kg		
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	sediment (marine water)				0,00701 mg/kg		
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	Soil				0,0548 mg/kg		
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	sewage treatment plant (STP)		3,8 mg/l				
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	oral				8,3 mg/kg		

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	Workers	inhalation	Long term exposure - systemic effects		6,6 mg/m <sup>3</sup>	
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	Workers	dermal	Long term exposure - systemic effects		9,6 mg/kg	
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	General population	inhalation	Long term exposure - systemic effects		1,67 mg/m <sup>3</sup>	
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	General population	dermal	Long term exposure - systemic effects		4,8 mg/kg	
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	General population	oral	Long term exposure - systemic effects		0,19 mg/kg	
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	Workers	inhalation	Long term exposure - systemic effects		6,6 mg/m <sup>3</sup>	
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	Workers	dermal	Long term exposure - systemic effects		9,6 mg/kg	
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	General population	inhalation	Long term exposure - systemic effects		1,67 mg/m <sup>3</sup>	
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	General population	dermal	Long term exposure - systemic effects		4,8 mg/kg	
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	General population	oral	Long term exposure - systemic effects		0,19 mg/kg	

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to &gt; 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to &gt; 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.  
Protective eye equipment should conform to EN166.

**Skin protection:**

Wear suitable protective clothing.  
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Advices to personal protection equipment:**

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.  
Personal protective equipment should conform to the relevant EN standard.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state	liquid
Delivery form	paste
Colour	white
Odor	characteristic
Melting point	Not applicable, Product is a liquid
Initial boiling point	Not available.
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	96 °C (204.8 °F)
Auto-ignition temperature	Currently under determination
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Currently under determination
Viscosity (kinematic)	Currently under determination
Viscosity, dynamic (; 20 °C (68 °F))	100.000 mPa.s no method
Solubility (qualitative) (Solvent: Water)	Not miscible or difficult to mix
Partition coefficient: n-octanol/water	Not applicable Mixture
Vapour pressure	Currently under determination
Density (20 °C (68 °F))	0,9 g/cm <sup>3</sup> None
Relative vapour density:	Currently under determination
Particle characteristics	Not applicable Product is a liquid

**9.2. Other information**

Other information not applicable for this product

**SECTION 10: Stability and reactivity****10.1. Reactivity**

None if used properly.

**10.2. Chemical stability**

Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

See section reactivity

**10.4. Conditions to avoid**

Stable under normal conditions of storage and use.

**10.5. Incompatible materials**

None if used properly.

**SECTION 11: Toxicological information****General toxicological information:**

Prolonged or repeated contact may cause skin irritation.

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	LD50	3.080 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	LD50	2.000 - 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Polysulfides, di-tert-Bu 68937-96-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Polysulfides, di-tert-Bu 68937-96-2	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
dilithium azelate 38900-29-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	LD50	> 20.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Polysulfides, di-tert-Bu 68937-96-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

**Acute inhalative toxicity:**

No data available.

**Skin corrosion/irritation:**

No data available.



**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	moderately irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Polysulfides, di-tert-Bu 68937-96-2	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

No data available.

**Carcinogenicity**

No data available.

**Reproductive toxicity:**

No data available.

**STOT-single exposure:**

No data available.

**STOT-repeated exposure::**

No data available.

**Aspiration hazard:**

No data available.

**11.2 Information on other hazards**

not applicable

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
dilithium azelate 38900-29-7	LC50	> 100 mg/l	96 h	Cyprinus carpio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethyl 3-[[bis(1-methylethoxy)phosphinothioyl]thio]propionate 71735-74-5	LC50	1,73 mg/l	96 h	Danio rerio (reported as Brachydanio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Zinc bis[O,O-bis(2-ethylhexyl)]bis(dithiophosphate) 4259-15-8	LL50	4,4 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

#### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
dilithium azelate 38900-29-7	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethyl 3-[[bis(1-methylethoxy)phosphinothioyl]thio]propionate 71735-74-5	EC50	4,01 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Zinc bis[O,O-bis(2-ethylhexyl)]bis(dithiophosphate) 4259-15-8	EL50	75 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Polysulfides, di-tert-Bu 68937-96-2	EL50	63 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl 3-[[bis(1-methylethoxy)phosphinothioyl]thio]propionate 71735-74-5	EC10	0,196 mg/l	21 day	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	NOEC	0,4 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

#### Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
dilithium azelate 38900-29-7	EC50	> 100 mg/lo	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
dilithium azelate 38900-29-7	NOEC	> 100 mg/lo	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethyl 3-[[bis(1-methylethoxy)phosphinothioyl]thio]propionate 71735-74-5	EC50	8,28 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethyl 3-[[bis(1-methylethoxy)phosphinothioyl]thio]propionate 71735-74-5	EC10	3,93 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	NOEC	1 mg/l	96 h		OECD Guideline 201 (Alga, Growth Inhibition Test)
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	EC50	2,1 mg/l	96 h		OECD Guideline 201 (Alga, Growth Inhibition Test)
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	NOEC	1 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	EC50	> 1 - 5 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Polysulfides, di-tert-Bu 68937-96-2	EL50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Polysulfides, di-tert-Bu 68937-96-2	NOELR	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl 3-[[bis(1-methylethoxy)phosphinothioyl]thio]propionate 71735-74-5	IC50	100 mg/l	3 h	activated sludge, domestic	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	EC 50	11 - 36 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

### 12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
dilithium azelate 38900-29-7	readily biodegradable	aerobic	> 79 - < 89 %	19 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Ethyl 3-[[bis(1-methylethoxy)phosphinothioyl]thio]propionate 71735-74-5	not readily biodegradable.	aerobic	33 %	28 day	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9		aerobic	1,5 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Isoalkylphenyl phosphorothioate 126019-82-7	not readily biodegradable.	aerobic	2 %	28 day	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Polysulfides, di-tert-Bu 68937-96-2	not readily biodegradable.	aerobic	13 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
dilithium azelate 38900-29-7	1,57	25 °C	not specified

### 12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

### 12.6. Endocrine disrupting properties

not applicable

### 12.7. Other adverse effects

No data available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

14 06 03 Other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

### SECTION 14: Transport information

- 14.1. UN number or ID number**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Maritime transport in bulk according to IMO instruments**  
not applicable

### SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 3 %

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**National regulations/information (Germany):**

WGK:	WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV) ) Classification according to AwSV, Annex 1 (5.2)
Storage class according to TRGS 510:	10

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2:	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

**Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**